

# Builders Statement



## InsulSafe® SP Fiber Glass Blowing Insulation For use in Blow-In-Blanket® System

Homeowner Name / Jobsite Name

Home Address

Installer / Contractor (sign)

Company Name

Date

Builder (sign)

Company Name

Date

Inspected By (sign if required)

Date

THICKNESS		R-VALUE		MIN. BAGS FOR 1000 FT <sup>2</sup>	MIN. BAGS FOR 100M <sup>2</sup>	DENSITY		MINIMUM WEIGHT		MAXIMUM NET COVERAGE	
in.	mm	R	RSI	#	#	lbs./ft <sup>3</sup>	kg/m <sup>3</sup>	lbs./ft <sup>2</sup>	kg/m <sup>2</sup>	ft <sup>2</sup>	m <sup>2</sup>
3 1/2 (2X4)	89	14	2.5	16.9	18.2	1.8	28.9	0.525	2.566	59.0	5.5
3 1/2 (2X4)	89	15	2.6	21.6	23.3	2.3	36.9	0.671	3.278	46.2	4.3
5 1/2 (2X6)	140	22	3.9	26.6	28.6	1.8	28.9	0.825	4.032	37.6	3.5
5 1/2 (2X6)	140	23	4.1	34.0	36.6	2.3	36.9	1.054	5.152	29.4	2.7
7 1/4 (2X8)	184	29	5.1	35.1	37.8	1.8	28.9	1.088	5.315	28.5	2.6
7 1/4 (2X8)	184	31	5.5	44.8	48.3	2.3	36.9	1.390	6.791	22.3	2.1
9 1/4 (2X10)	235	37	6.5	44.8	48.2	1.8	28.9	1.388	6.781	22.3	2.1
9 1/4 (2X10)	235	39	6.9	57.2	61.6	2.3	36.9	1.773	8.664	17.5	1.6

	R-VALUE	THICKNESS	NET AREA (SQ. FT.)	ULTRATHERM (✓)	NUMBER OF BAGS USED	BATTS/ROLLS (✓)
CEILINGS						
WALLS						
FLOORS						

### THERMAL PERFORMANCE — ATTIC BLOWING APPLICATION

- In accordance with the chart above, you must install the minimum number of bags per 1,000 sq. ft. of net area for each R-Value listed.
- The maximum net coverage must not exceed that specified for each R-Value.
- The installed insulation must be at or above the specified minimum thickness for each R-Value.
- Failure to install the required minimum weight per sq. ft. of insulation at or above the minimum thickness will result in reduced R-Value.
- This product should not be mixed with other blown insulations or the thermal claims will become invalid. R-Values are determined in accordance with ASTM C518. Complies with ASTM C 764 as Type 1 insulation. "R" means resistance to heat flow. The higher the R-Value, the greater the insulating power. To get the desired R-Value, it is essential that the insulation is installed properly.

**DANGER: RECESSED LIGHT FIXTURES—TO PREVENT OVERHEATING, DO NOT INSULATE ON TOP OR WITHIN 3" OF SUCH DEVICES. THIS WARNING DOES NOT APPLY TO TYPE IC LIGHT FIXTURES OR TO FLUORESCENT FIXTURES WITH THERMALLY PROTECTED BALLASTS.**

**THERMAL PERFORMANCE — BIBS® SIDEWALL APPLICATION (BASED ON A NOMINAL 28 LB. BAG)**

When installed in wall cavities, the following thermal performance is achieved at the thickness, weights and coverages specified.

THICKNESS		R-VALUE		MIN. BAGS FOR 1000 FT <sup>2</sup>	MIN. BAGS FOR 100M <sup>2</sup>	DENSITY		MINIMUM WEIGHT		MAXIMUM NET COVERAGE	
in.	mm	R	RSI	#	#	lbs./ft <sup>3</sup>	kg/m <sup>3</sup>	lbs./ft <sup>2</sup>	kg/m <sup>2</sup>	ft <sup>2</sup>	m <sup>2</sup>
3 1/2 (2X4)	89	14	2.5	16.9	18.2	1.8	28.9	0.525	2.566	59.0	5.5
3 1/2 (2X4)	89	15	2.6	21.6	23.3	2.3	36.9	0.671	3.278	46.2	4.3
5 1/2 (2X6)	140	22	3.9	26.6	28.6	1.8	28.9	0.825	4.032	37.6	3.5
5 1/2 (2X6)	140	23	4.1	34.0	36.6	2.3	36.9	1.054	5.152	29.4	2.7
7 1/4 (2X8)	184	29	5.1	35.1	37.8	1.8	28.9	1.088	5.315	28.5	2.6
7 1/4 (2X8)	184	31	5.5	44.8	48.3	2.3	36.9	1.390	6.791	22.3	2.1
9 1/4 (2X10)	235	37	6.5	44.8	48.2	1.8	28.9	1.388	6.781	22.3	2.1
9 1/4 (2X10)	235	39	6.9	57.2	61.6	2.3	36.9	1.773	8.664	17.5	1.6

R-Values are determined in accordance with ASTM C518. Complies with ASTM C764 as Type 1 insulation. "R" means resistance to heat flow. The higher the R-Value, the greater the insulating power. To get the marked R-Value, it is essential that the insulation is installed properly following the recommendations of CertainTeed Corporation and Blow-In-Blanket, Inc.

Blow-In-Blanket® System is a registered trademark of Blow-In-Blanket, Inc., Denver, CO 80223  
 InsulSafe® SP is a registered trademark of CertainTeed Corporation

**READ THIS BEFORE YOU BUY**

What you should know about R-Values:

The chart shows the R-Value of this insulation. R means resistance to heat flow. The higher the R-Value, the greater the insulating power. Compare insulation R-Values before you buy.

There are other factors to consider. The amount of insulation you need depends mainly on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel.

To get the marked R-Value, it is essential that this insulation be installed properly.



**ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:**

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE • FOUNDATIONS  
 GYPSUM • CEILINGS • INSULATION • PIPE

CertainTeed Corporation  
 P.O. Box 860  
 Valley Forge, PA 19482

Professional: 800-233-8990  
 Consumer: 800-782-8777  
[www.certainteed.com/insulation](http://www.certainteed.com/insulation)

