



Builders Statement

CertaSpray™ Closed Cell Spray Foam Insulation

Homeowner Name / Jobsite Name _____

Home Address _____

Installer / Contractor (sign) _____

Company Name _____

Date _____

Builder (sign) _____

Company Name _____

Date _____

Inspected By (sign if required) _____

Date _____

CertaSpray™ Closed Cell Spray Foam Insulation is a two-component spray foam applied as a spray insulation. The foam provides thermal insulation for the interior of buildings and reduces air infiltration through the building envelope.

THERMAL PERFORMANCE			
THICKNESS		AGED R-VALUE*	
(")	(mm)	(h-ft ² -°F)/Btu	(m ² -°C)/W
1	25	5.8**	1.02
1½	38	8.7**	1.53
2	51	11.6**	2.04
2½	64	16.0**	2.82
3	76	19.2	3.38
3½	89	22.4	3.94
4	102	25.6	4.51
4½	114	28.8	5.07
5	127	32.3	5.69
5½	140	35.5	6.25
6	152	38.7	6.82

Tested in accordance with ASTM C518 and/or C177 at 75°F (24°C) mean temperature

*Aged 90 days at 140°F.

****When applied at a thickness > 2-1/2", aged R-value is 6.4 per inch. When applied at a thickness ≤ 2-1/2", aged R-value is 5.8 per inch.**

CertainTeed CertaSpray™ Closed Cell Spray Foam Insulation has been installed at the following thicknesses:

Walls _____

Ceilings _____

Floors _____