



Submittal Form

ToughGard® Fiber Glass Duct Liner Products

CONTRACTOR NAME

JOB NAME

DATE

Please check the appropriate products below:

- ToughGard® T Textile Duct Liner ToughGard® Rigid Liner Board
 ToughGard® R Duct Liner

TECHNICAL DATA

ToughGard® Duct Liner Products		
PROPERTIES	PERFORMANCE	TEST METHOD
Operating Limits: Temperature Air Velocity	Maximum: 250°F (121°C) 6,000 fpm (30.5 m/s)	ASTM C411 ASTM C1071
Surface Burning Characteristics (Fire Hazard Classification)	Maximum: Flame Spread Index: 25 Smoke Developed Index: 50	NFPA 255 UL 723 ASTM E84
Water Vapor Sorption	≤ 3% by Weight	ASTM C1104
Corrosiveness	Pass	ASTM C665
Fungi Resistance	Pass; No growth	ASTM C665, ASTM C1138, ASTM G21
Bacteria Resistance	No growth	ASTM G22
Limited Combustible	Pass (<3,500 Btu/lb)	NFPA 259
Fire Safety Standards	Pass	NFPA 90A, NFPA 90B
Water Repellency rating	≥ 4 INDA IST 80.6-92	

Model Building Codes: (ICC, California Title 24)

This Submittal Form is provided to assist you in specifying and selecting the proper CertainTeed Insulation product. Basic product descriptions and performance data are included. For further information or technical assistance contact your local CertainTeed representative.

CertainTeed Corporation, P.O. Box 860, Valley Forge, PA 19482
1-800-233-8990

Visit our website at: <http://www.certainteed.com/insulation>
Customer Service 1-800-441-6720 • Fax 1-866-632-4329

Product	Description	Type	Thickness		R-Value		NRC	Applicable Standards
			in	mm	R	RSI		
ToughGard® T Textile Duct Liner	A textile-type fiber glass acoustical liner for HVAC sheet metal duct systems, operating velocities up to 6,000 fpm (30.5 m/s) and temperatures to 250°F (121°C), to absorb unwanted crosstalk, equipment and air rush noise.	150	1	25	4.0	0.70	0.65	Complies with ASTM 1071, Type I, rolls or Type II, sheets insulation. Thermal performance determined by ASTM C177 or ASTM C518. Acoustical performance determined by ASTM C423 using Type A mounting per ASTM E795.
		150	1½	38	6.0	1.06	0.80	
		150	2	51	8.0	1.41	0.90	
		R 4.2	1	25	4.2	0.74	0.70	
		200	½	13	2.0	0.35	0.45	
		200	1	25	4.2	0.74	0.70	
		200	1½	38	6.0	1.06	0.80	
		200	2	51	8.0	1.41	0.85	
		R 6.3	1½	38	6.3	1.11	0.90	
		300	½	13	2.1	0.37	0.45	
ToughGard® R Duct Liner	A fiber glass acoustical liner for HVAC sheet metal duct systems, operating at velocities up to 6,000 fpm (30.5 m/s) and temperatures to 250°F (121°C), to absorb unwanted crosstalk, equipment and air rush noise.	150	1	25	4.2	0.73	0.70	Complies with ASTM 1071, Type I, rolls insulation. Thermal performance determined by ASTM C177 or ASTM C518. Acoustical performance determined by ASTM C423 using Type A mounting per ASTM E795.
		150	1½	38	6.3	1.10	0.90	
		150	2	51	8.3	1.47	1.00	
		200	½	13	2.1	0.37	0.45	
ToughGard® Rigid Liner Board	A rigid board-type acoustical and thermal fiber glass insulation for lining the interior of sheet metal ducts and plenums in HVAC systems, operating at velocities up to 6000 fpm (30.5 m/s) and temperatures up to 250°F (121°C), to quiet HVAC noise by absorbing unwanted crosstalk, equipment and air rush noise and reduce unwanted heat gain or loss.	n/a	1	25	4.3	0.77	0.70	Complies with ASTM 1071, Type II, sheets insulation. Thermal performance determined by ASTM C177 or ASTM C518. Acoustical performance determined by ASTM C423 using Type A mounting per ASTM E795.
		n/a	1½	38	6.5	1.15	0.80	
		n/a	2	51	8.7	1.53	0.95	



ASK ABOUT OUR OTHER CERTAINTeed PRODUCTS AND SYSTEMS:

EXTERIOR: ROOFING • SIDING • WINDOWS • FENCE • RAILING • TRIM • DECKING • FOUNDATIONS • PIPE
INTERIOR: INSULATION • GYPSUM • CEILINGS

CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482

Professional: 800-233-8990
Consumer: 800-782-8777
www.certainteed.com/insulation

