

## Specification Sheet

### Features & Benefits:

- Made with proprietary Enhanced Glass Reinforced Gypsum substrate.
- Moisture resistant.
- Mold resistant core.
- Sag resistant.
- Vinyl faced.
- Exceptional indoor/outdoor performance in ceiling applications up to 95% relative humidity.
- Suitable for use as a component in certain clean room assemblies (ISO 14644-1 Class 5/Fed. Std. 209E Class 100/M3.5).
- Perfect for exterior soffits and canopies, parking garages, pools, spas, commercial kitchens, and locker, shower or therapy rooms.
- Scrubbable USDA/FSIS accepted Clean Room Facing (CRF) vinyl facing seals out moisture.
- Non-combustible core panel resists damage from blunt impact and chemical fumes.
- Approved by Canadian Food Inspection Agency (CFIA) for use in food establishments.

See reverse for additional product specifications.

### Applications:

- Exterior Soffits
- Exterior Canopies
- Parking Garages
- Pools
- Spas
- Commercial Kitchens
- Locker Rooms
- Shower Rooms
- Food Processing




### Attributes:

ITEM NUMBER	NOMINAL SIZE (Inches)	EDGE DETAIL	NRC	CAC	LR	RECYCLED CONTENT %
<b>SAFETONE® CLASS A</b>						
<b>White CRF</b>						
<b>1182-CRF-1SV</b>	24 x 24 x 1/2	Trim	—	<b>40</b>	0.78	0
<b>1180-CRF-1SV</b>	24 x 48 x 1/2	Trim	—	<b>42</b>	0.78	0

ASTM E 1264 Classification: Type XX, Pattern G, Fire Class A


### Finishes:

LR=Light Reflectance



**WHITE CRF**  
CRF-1 (LR=0.78)

### Edge Details:



**TRIM EDGE**  
(Square) 15/16" Grid



# Product Specification Details

## Acoustical Ceilings

### 09 51 00

#### PART 2: PRODUCTS

##### 2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

##### 2.2 MATERIALS

Acoustical Ceiling Units:

1. Type XX (gypsum base)
2. Form NA
3. Pattern G
4. 100% RH gypsum board lay-in panel with fine textured vinyl finish [White CRF]
5. Size 1/2" x [24" x 24"] [24" x 48"] [Custom]
6. Edge Detail Trim (Square)
7. Noise Reduction Coefficient (NRC) NA
8. Ceiling Attenuation Class (CAC) [40] [42]
9. Light Reflectance Coefficient (LR) 0.78
10. Recycled Content 0
11. Color White
12. Flame Spread Classification (ASTM E 84, CAN/ULC-S102M) Class A
13. Manufacturer, subject to compliance with requirements of this specification, CertainTeed Ceilings
14. Product Name Aquarock™

---

Distributed by:

---

Characteristics, properties or performance of materials or systems manufactured by CertainTeed herein described are derived from data obtained under controlled test conditions. CertainTeed makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. CertainTeed assumes no responsibility for the effects of structural movement.

NOTICE: The information in this document is subject to change without notice. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

---

#### ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • WINDOWS • DECKING • RAILING • FENCE  
INSULATION • GYPSUM • CEILINGS • FOUNDATIONS • PIPE

CertainTeed Corporation  
P.O. Box 860  
Valley Forge, PA 19482

Professional: 800-233-8990  
Consumer: 800-782-8777

[www.certainteed.com](http://www.certainteed.com) <http://blog.certainteed.com>

© 05/10 CertainTeed Corporation  
Code No. CTC-3990