

Cashmere[®] High NRC

PERFORMANCE SERIES MINERAL FIBER CEILING



Specification Sheet

Features & Benefits:

- Upscale appearance.
- Finely textured, highly decorative.
- Popular edge detail options.
- Effective noise reduction.
- No added formaldehyde.

See reverse for additional product specifications.

Applications:

- Healthcare
- Hospitality/Resorts
- Offices
- Conference Centers
- Education
- Galleries
- Airports
- Restaurants


Attributes:

ITEM NUMBER	NOMINAL SIZE (Inches)	EDGE DETAIL	NRC	CAC	LR	RECYCLED CONTENT %
SAFETONE[®] CLASS A						
CM-450-NRCP	24 x 24 x 3/4	Narrow Reveal	0.70	30	0.82	74
CM-454-NRCP	24 x 24 x 3/4	Reveal	0.70	30	0.82	74
CM-457-NRCP	24 x 24 x 3/4	Trim	0.70	30	0.82	74
CM-494-NRCP	24 x 48 x 3/4	Reveal	0.70	32	0.82	74
CM-497-NRCP	24 x 48 x 3/4	Trim	0.70	32	0.82	74


ASTM E 1264 Classification: Type III, Form 1, Pattern C E




Edge Details:




TRIM EDGE
(Square) 15/16" Grid



REVEAL EDGE
(Beveled) 15/16" Grid



NARROW REVEAL EDGE
(Corner Bevel) 3/16" Grid



NARROW REVEAL EDGE
(Corner Bevel)
3/16" Grid (Bolt Slot)



BioShield™
BioShield™ treatment **included** for added mold and mildew resistance.



Product Specification Details

Acoustical Ceilings

09 51 00

PART 2: PRODUCTS

2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

2.2 MATERIALS

Acoustical Ceiling Units:

1. Type III
2. Form 1
3. Pattern [C] [E]
4. Lightly textured nodular tiles and lay-in panels
5. Size 3/4" thick x [24" x 24"] [24" x 48"]
6. Edge Detail [Trim (Square)] [Reveal] [Narrow Reveal]
7. Noise Reduction Coefficient (NRC) 0.70
8. Ceiling Attenuation Class (CAC) [30] [32]
9. Light Reflectance Coefficient (LR) 0.82
10. Recycled Content 74
11. Color White
12. Flame Spread Classification (ASTM E 84, CAN/ULC-S102M) Class A
13. Manufacturer, subject to compliance with requirements of this specification, CertainTeed Ceilings
14. Product Name Cashmere® High NRC

Distributed by:

Characteristics, properties or performance of materials or systems manufactured by CertainTeed herein described are derived from data obtained under controlled test conditions. CertainTeed makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. CertainTeed assumes no responsibility for the effects of structural movement.

NOTICE: The information in this document is subject to change without notice. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • WINDOWS • DECKING • RAILING • FENCE
INSULATION • GYPSUM • CEILINGS • FOUNDATIONS • PIPE

CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482

Professional: 800-233-8990
Consumer: 800-782-8777

www.certainteed.com <http://blog.certainteed.com>

© 05/10 CertainTeed Corporation
Code No. CTC-4737