Cashmere® Style Edge

PERFORMANCE SERIES MINERAL FIBER CEILINGS

CertainTeed SAINT-GOBAIN

Specification Sheet

Features & Benefits:

- Upscale appearance.
- Finely textured with highly decorative edge detail choices.
- Scored options for added visual impact.
- No added formaldehyde.

See reverse for additional product specifications.

Applications:

- Conference Centers
- Resorts
- Hospitality
- Retail
- Education
- Restaurants
- Healthcare
- Offices
- Airports
- Galleries

Attributes:

ITEM NUMBER	NOMINAL SIZE (Inches)	EDGE DETAIL	UL CLASSIFIED NRC	UL CLASSIFIED CAC	LR	RECYCLED CONTENT %
SAFETONE® CLASS A Tier Edge Cashmere® Specifications						
CMTS-124	24 x 24 x 3/4	Tier Reveal 9/16" Grid	**0.60**	**35**	0.83	**74**
CMTS-124-1516	24 x 24 x 3/4	Tier Reveal 15/16" Grid	**0.60**	**35**	0.83	**74**
CMTS-412	24 x 24 x 3/4	Tier Reveal 9/16" Grid	**0.60**	**35**	0.83	**74**
CMTS-412-1516	24 x 24 x 3/4	Tier Reveal 15/16" Grid	**0.60**	**35**	0.83	**74**
SAFETONE® CLASS A Fluted Edge Cashmere® Specifications						
CMF-124	24 x 24 x 3/4	Fluted Reveal	**0.60**	**31**	0.83	**74**
SAFETONE® CLASS A Ogee Edge Cashmere® Specifications						
CMO-124	24 x 24 x 3/4	Ogee Reveal	**0.60**	**31**	0.83	**74**

ASTM E 1264 Classification: Type III, Form 1, Pattern E

Edge Details:

TIER REVEAL EDGE
15/16" Grid



TIER REVEAL EDGE
9/16" Grid



FLUTED REVEAL EDGE
9/16" Grid



OGEE REVEAL EDGE
9/16" Grid

Scoring Options:



24" x 24"
412

BioShield™
BioShield™ treatment **included** for added mold and mildew resistance.

Product Specification Details
Acoustical Ceilings
09 51 00

PART 2: PRODUCTS

2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

2.2 MATERIALS

Acoustical Ceiling Units:

1. Type III
2. Form 1
3. Pattern E
4. Lightly textured, surface scored to simulate four 12" x 12" nodular lay-in panels
5. Size 3⁄4" thick x 24" x 24"
6. Edge Detail [Tier] [Fluted] [Ogee]
7. Noise Reduction Coefficient (NRC) 0.60
8. Ceiling Attenuation Class (CAC) [31] [35]
9. Light Reflectance Coefficient (LR) 0.83
10. Recycled Content 74
11. Color White
12. Flame Spread Classification (ASTM E 84, CAN/ULC-S102M) Class A
13. Manufacturer, subject to compliance with requirements of this specification, CertainTeed Ceilings
14. Product Name Cashmere® Style Edge

Distributed by:

Characteristics, properties or performance of materials or systems manufactured by CertainTeed herein described are derived from data obtained under controlled test conditions. CertainTeed makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. CertainTeed assumes no responsibility for the effects of structural movement.

NOTICE: The information in this document is subject to change without notice. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • WINDOWS • DECKING • RAILING • FENCE
INSULATION • GYPSUM • CEILINGS • FOUNDATIONS • PIPE

CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482

Professional: 800-233-8990
Consumer: 800-782-8777

www.certainteed.com http://blog.certainteed.com

© 05/10 CertainTeed Corporation
Code No. CTC-4701

SAINT-GOBAIN