

## Specification Sheet

### Features & Benefits:

- Upscale appearance.
- Finely textured.
- Popular edge detail options.
- Available in 5 colors.
- No added formaldehyde.

### Applications:

- Galleries
- Resorts
- Hospitality
- Airports
- Retail
- Offices
- Education
- Healthcare
- Restaurants
- Salons

See reverse for additional product specifications.


### Attributes:

ITEM NUMBER	NOMINAL SIZE (Inches)	EDGE DETAIL	UL CLASSIFIED		LR	RECYCLED CONTENT %
			NRC	CAC		
<b>SAFETONE® CLASS A</b>						
CM-450	24 x 24 x 3/4	Narrow Reveal	0.60	35	0.83	74
CM-454	24 x 24 x 3/4	Reveal	0.60	35	0.83	74
CM-457	24 x 24 x 3/4	Trim	0.60	35	0.83	74
CM-490	24 x 48 x 3/4	Narrow Reveal	0.60	35	0.83	74
CM-494	24 x 48 x 3/4	Reveal	0.60	35	0.83	74
CM-497	24 x 48 x 3/4	Trim	0.60	35	0.83	74
<b>PROTECTONE®</b> (For specific UL fire resistant time-rated assemblies)						
PCM-450	24 x 24 x 3/4	Narrow Reveal	0.45	35	0.83	47
PCM-454	24 x 24 x 3/4	Reveal	0.45	35	0.83	47


ASTM E 1264 Classification: Type III, Form 1, Pattern E




### Edge Details:




**TRIM EDGE**  
(Square) 15/16" Grid



**REVEAL EDGE**  
(Beveled) 15/16" Grid



**NARROW REVEAL EDGE**  
(Corner Bevel) 3/16" Grid



**NARROW REVEAL EDGE**  
(Corner Bevel)  
3/16" Grid (Bolt Slot)



**BioShield™**  
BioShield™ treatment included for added mold and mildew resistance.



# Product Specification Details

## Acoustical Ceilings

### 09 51 00

#### PART 2: PRODUCTS

##### 2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

##### 2.2 MATERIALS

Acoustical Ceiling Units:

1. Type III
2. Form 1
3. Pattern E
4. Lightly textured nodular tiles and lay-in panels
5. Size 3/4" thick x [24" x 24"] [24" x 48"]
6. Edge Detail [Trim (Square)] [Reveal] [Narrow Reveal]
7. Noise Reduction Coefficient (NRC) [0.45] [0.60]
8. Ceiling Attenuation Class (CAC) 35
9. Light Reflectance Coefficient (LR) 0.83
10. Recycled Content [47] [74]
11. Color [White] [Beige Breeze] [Blondewood] [Silver Lining] [Wet Clay] [White Wash]
12. Flame Spread Classification (ASTM E 84, CAN/ULC-S102M) Class A
13. Underwriters Laboratories Inc. Fire-Resistance (ASTM E 119, CAN/ULC-S101M) Time-Rated Assembly\* [D203] [D205] [G208] [G218] [G248] [G255] [L201] [P204] [P259] [P260] [P261] [P262] [P264]
14. Manufacturer, subject to compliance with requirements of this specification, CertainTeed Ceilings
15. Product Name [Cashmere®] [Protectone® Cashmere®]

\* Relevant to Protectone® only. Refer to UL Fire Resistant Directory for specific design information.

---

Distributed by:

---

Characteristics, properties or performance of materials or systems manufactured by CertainTeed herein described are derived from data obtained under controlled test conditions. CertainTeed makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. CertainTeed assumes no responsibility for the effects of structural movement.

NOTICE: The information in this document is subject to change without notice. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

---

#### ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • WINDOWS • DECKING • RAILING • FENCE  
INSULATION • GYPSUM • CEILINGS • FOUNDATIONS • PIPE

CertainTeed Corporation  
P.O. Box 860  
Valley Forge, PA 19482

Professional: 800-233-8990  
Consumer: 800-782-8777

[www.certainteed.com](http://www.certainteed.com) <http://blog.certainteed.com>

© 05/10 CertainTeed Corporation  
Code No. CTC-4662