

Specification Sheet

Features & Benefits:

- Gypsum core with vinyl facing, vinyl backing and sealed edges.
- Specially designed for low particulate emission and maximum clean-ability.
- Surface suitable for cleaning with common disinfecting chemicals.
- Sanitary, scrubbable panels are USDA/FSIS/CFIA accepted.
- Approved by Canadian Food Inspection Agency (CFIA) for use in food establishments.
- Suitable for use as a component in certain clean room assemblies (ISO 14644-1 Class 5/Fed. Std. 209E Class 100/M3.5).
- Does not contain formaldehyde.

See reverse for additional product specifications.

Applications:

- Food Preparation Areas
- Laboratories
- Photo-processing
- Operating Rooms
- Clean Room Environments


Attributes:

ITEM NUMBER	NOMINAL SIZE (Inches)	EDGE DETAIL	NRC	CAC	LR	RECYCLED CONTENT %
SAFETONE® CLASS A						
White CRF						
1192-CRF-1	24 x 24 x 1/2	Trim	—	38	0.78	0
1190-CRF-1	24 x 48 x 1/2	Trim	—	40	0.78	0

ASTM E 1264 Classification: Type XX, Pattern G, Fire Class A




Finish:



WHITE CRF – CRF-1

Edge Detail:



TRIM EDGE
(Square) 15/16" Grid



Product Specification Details

Acoustical Ceilings

09 51 00

PART 2: PRODUCTS

2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

2.2 MATERIALS

Acoustical Ceiling Units:

1. Type XX (gypsum base)
2. Form NA
3. Pattern G
4. Fine textured, vinyl finish, edge sealed clean room gypsum lay-in panel.
5. Size 1/2" x [24" x 24"] [24" x 48"]
6. Edge Detail Trim (Square)
7. Noise Reduction Coefficient (NRC) NA
8. Ceiling Attenuation Class (CAC) [38] [40]
9. Light Reflectance Coefficient (LR) 0.78
10. Recycled Content 0
11. Color White
12. Flame Spread Classification (ASTM E 84, CAN/ULC-S102M) Class A
13. Manufacturer, subject to compliance with requirements of this specification, CertainTeed Ceilings
14. Product Name Envirogard™

Distributed by:

Characteristics, properties or performance of materials or systems manufactured by CertainTeed herein described are derived from data obtained under controlled test conditions. CertainTeed makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. CertainTeed assumes no responsibility for the effects of structural movement.

NOTICE: The information in this document is subject to change without notice. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • WINDOWS • DECKING • RAILING • FENCE
INSULATION • GYPSUM • CEILINGS • FOUNDATIONS • PIPE

CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482

Professional: 800-233-8990
Consumer: 800-782-8777

www.certainteed.com <http://blog.certainteed.com>

© 05/10 CertainTeed Corporation
Code No. CTC-3993