

Specification Sheet

Features & Benefits:

- Special pulverized-marble aggregate coating provides rugged durability.
- High humidity and sag resistant.
- Offers upscale look with additional durability.
- Lightly textured surface provides attractive finish with excellent light reflectance and durability.
- Micro perforated for sound absorption.
- No added formaldehyde.

See reverse for additional product specifications.

Applications:

- Education
- Retail
- Malls
- Offices
- Healthcare
- Restaurants
- Airports
- Reception Areas

Attributes:


ITEM NUMBER	NOMINAL SIZE (Inches)	EDGE DETAIL	UL CLASSIFIED		LR	RECYCLED CONTENT %
			NRC	CAC		
SAFETONE® CLASS A						
SHM-150	24 x 24 x 5/8	Narrow Reveal	0.50	33	0.88	36-45
SHM-154	24 x 24 x 5/8	Reveal	0.50	33	0.88	36-45
SHM-157	24 x 24 x 5/8	Trim	0.50	33	0.88	36-45
SHM-190	24 x 48 x 5/8	Narrow Reveal	0.50	35	0.88	36-45
SHM-194	24 x 48 x 5/8	Reveal	0.50	35	0.88	36-45
SHM-197	24 x 48 x 5/8	Trim	0.50	35	0.88	36-45

ASTM E 1264 Classification: Type III, Form 2, Pattern C E


* Metric sizes available




Edge Details:




TRIM EDGE
(Square) 15/16" Grid



REVEAL EDGE
(Beveled) 15/16" Grid



NARROW REVEAL EDGE
(Corner Bevel) 3/8" Grid



NARROW REVEAL EDGE
(Corner Bevel)
3/8" Grid (Bolt Slot)



BioShield™
BioShield™ treatment **included** for added mold and mildew resistance.



Product Specification Details

Acoustical Ceilings

09 51 00

PART 2: PRODUCTS

2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

2.2 MATERIALS

Acoustical Ceiling Units:

1. Type III
2. Form 2
3. Pattern C E
4. Micro perforated wet-felted lay-in panel
5. Size 5/8" thick x [24" x 24"] [24" x 48"]
6. Edge Detail [Trim (Square)] [Reveal] [Narrow Reveal]
7. Noise Reduction Coefficient (NRC) 0.50
8. Ceiling Attenuation Class (CAC) [33] [35]
9. Light Reflectance Coefficient (LR) 0.88
10. Recycled Content 36-45
11. Color White
12. Flame Spread Classification (ASTM E 84, CAN/ULC-S102M) Class A
13. Manufacturer, subject to compliance with requirements of this specification, CertainTeed Ceilings
14. Product Name Sand Micro™

Distributed by:

Characteristics, properties or performance of materials or systems manufactured by CertainTeed herein described are derived from data obtained under controlled test conditions. CertainTeed makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. CertainTeed assumes no responsibility for the effects of structural movement.

NOTICE: The information in this document is subject to change without notice. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • WINDOWS • DECKING • RAILING • FENCE
INSULATION • GYPSUM • CEILINGS • FOUNDATIONS • PIPE

CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482

Professional: 800-233-8990
Consumer: 800-782-8777

www.certainteed.com <http://blog.certainteed.com>

© 05/10 CertainTeed Corporation
Code No. CTC-4869