

Specification Sheet

Features & Benefits:

- Up to 25% higher surface hardness than conventional wet-felted ceiling products per ASTM C 367 testing.
- High light reflectance suitable for indirect lighting applications.
- No added formaldehyde.

See reverse for additional product specifications.


Applications:

- Schools
- Dorms
- Day Cares
- Education


Attributes:

ITEM NUMBER	NOMINAL SIZE (Inches)	EDGE DETAIL	UL CLASSIFIED		LR	RECYCLED CONTENT %
			NRC	CAC		
SAFETONE® CLASS A						
FFSB-157	24 x 24 x 5/8	Trim	0.55	35	0.84	45
FFSB-197	24 x 48 x 5/8	Trim	0.55	35	0.84	45
PROTECTONE® (For specific UL fire resistant time-rated assemblies)						
PFFSB-157	24 x 24 x 5/8	Trim	0.55	35	0.84	47
PFFSB-197	24 x 48 x 5/8	Trim	0.55	40	0.84	47

ASTM E 1264 Classification: Type III, Form 2, Pattern C D



Edge Details:



TRIM EDGE
(Square) 15/16" Grid



BioShield™
BioShield™ treatment **included** for added mold and mildew resistance.



Product Specification Details

Acoustical Ceilings

09 51 00

PART 2: PRODUCTS

2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

2.2 MATERIALS

Acoustical Ceiling Units:

1. Type III
2. Form 2
3. Pattern C D
4. Non-directional fissured and perforated wet-felted lay-in panels with impact resistant coating.
5. Size 5/8" thick x [24" x 24"] [24" x 48"]
6. Edge Detail Trim (Square)
7. Noise Reduction Coefficient (NRC) 0.55
8. Ceiling Attenuation Class (CAC) [35] [40]
9. Light Reflectance Coefficient (LR) 0.84
10. Recycled Content [45] [47]
11. Color White
12. Flame Spread Classification (ASTM E 84, CAN/ULC-S102M) Class A
13. Underwriters Laboratories Inc. Fire-Resistance (ASTM E 119, CAN/ULC-S101M) Time-Rated Assembly* [D203] [D205] [G208] [G218] [G248] [G255] [L201] [P204] [P259] [P260] [P261] [P262] [P264]
14. Manufacturer, subject to compliance with requirements of this specification, CertainTeed Ceilings
15. Product Name [School Board®] [Protectone® School Board®]

* Relevant to Protectone® only. Refer to UL Fire Resistant Directory for specific design information.

Distributed by:

Characteristics, properties or performance of materials or systems manufactured by CertainTeed herein described are derived from data obtained under controlled test conditions. CertainTeed makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. CertainTeed assumes no responsibility for the effects of structural movement.

NOTICE: The information in this document is subject to change without notice. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • WINDOWS • DECKING • RAILING • FENCE
INSULATION • GYPSUM • CEILINGS • FOUNDATIONS • PIPE

CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482

Professional: 800-233-8990
Consumer: 800-782-8777

www.certainteed.com <http://blog.certainteed.com>

© 05/10 CertainTeed Corporation
Code No. CTC-4785

