

CertainTeed

ProRoc[®] BRAND

Finishing Products



CertainTeed 

Quality made certain. Satisfaction guaranteed.™

Finishing Products

Professional Grade Ready-Mixed Joint Compounds, Setting Compounds, Wall and Ceiling Spray Textures, Joint Reinforcement Products, Industrial Coatings (Paints) and Plasters.

ProRoc® Brand is a complete system of finishing products, specially developed to meet the demands of finishing professionals. The result is professional-grade performance that eases application, minimizes callbacks and improves profitability.

ProRoc® Brand packages are color-coded and come labelled in English and Spanish to make it easy to pick the right ProRoc® Brand product for every application.

Ready-Mixed Joint Compounds

ProRoc® Brand Joint Compounds are pre-mixed high performance products designed for professional applicators. These products meet ASTM C 475 Standard.

Lightweight



ProRoc® Lite Taping
Code: 308245
3.5 gal / 13.3 L

- Ready-Mixed Joint Compound
- For embedding wallboard tape and trims
- Excellent adhesion



ProRoc® Lite All-Purpose
Code: 308614
3.5 gal / 13.3 L

- Ready-Mixed Joint Compound
- Tape / Fill / Finish - Designed for all phases of drywall finishing
- Low shrinkage



ProRoc® Lite Finishing
Code: 308246
3.5 gal / 13.3 L

- Ready-Mixed Joint Compound
- Designed for finish coats
- Low shrinkage



ProRoc® EXTRA All-Purpose
Code: 308229
3.5 gal / 13.3 L

- Ready-Mixed Joint Compound
- Designed for all phases of drywall finishing
- Low shrinkage
- Not available in all regions



ProRoc® Lite All-Purpose
Code: 308244
4.5 gal / 17.0 L

- Ready-Mixed Joint Compound
- Tape / Fill / Finish - Designed for all phases of drywall finishing
- Low shrinkage



ProRoc® Mold Resistant Lite All-Purpose
Code: 312910
3.5 gal / 13.3 L

- Ready-Mixed Joint Compound
- Formulated to resist mold
- Designed for machine and hand taping
- Low shrinkage

Heavyweight



ProRoc® Taping
Code: 308223
45 lbs / 20.4 kg

- Ready-Mixed Joint Compound
- For embedding wallboard tape and trims
- Superior adhesion



ProRoc® All-Purpose
Code: 308224
48 lbs / 21.8 kg

- Ready-Mixed Joint Compound
- Tape / Fill / Finish - Designed for all phases of drywall finishing



ProRoc® Finishing
Code: 308222
48 lbs / 21.8 kg

- Ready-Mixed Joint Compound
- Designed for finish coats
- Excellent for skim coating



ProRoc® All-Purpose
Code: 308226
62 lbs / 21.8 kg

- Ready-Mixed Joint Compound
- Tape / Fill / Finish - Designed for all phases of drywall finishing



ProRoc® Finishing
Code: 309169
62 lbs / 28.1 kg

- Ready-Mixed Joint Compound
- Designed for finish coats
- Excellent for skim coating

Midweight



ProRoc® ONE All-Purpose
Code: 308247
3.5 gal / 13.3 L

- Ready-Mixed Joint Compound
- Tape / Fill / Finish - Designed for all phases of drywall finishing
- Can be used for skim coating and simple texturing

Small Retail Pails — 1 Gal.



ProRoc® Lite All-Purpose
Code: 308615
1 gal / 3.8 L

- Ready-Mixed Joint Compound
- Tape / Fill / Finish - Designed for all phases of drywall finishing
- Low shrinkage



ProRoc® All-Purpose
Code: 308225
12 lbs / 5.4 kg

- Ready-Mixed Joint Compound
- Tape / Fill / Finish - Designed for all phases of drywall finishing

The ProRoc® M2Tech® System



ProRoc® Moisture and Mold Resistant Gypsum Board with M2Tech®

ProRoc® Moisture and Mold Resistant 90 with M2Tech®
Code: 312909

FibaTape® Mold X10™ Mold Resistant Mesh Tape
Code: 313384

Sandable Setting Powders

ProRoc® Brand LITE Sand Setting Compounds are lightweight sandable chemically setting powders used to prefill joints, embed joint tape and conceal joints, fasteners and trim accessories on gypsum wallboard. They can also be used for interior patching and repair. They are ideal for heavy fills because they are specially formulated to harden with very little shrinkage in a prescribed time frame. Setting times are available from 5 minutes to 210 minutes.



ProRoc® LITE Sand Setting Compounds

18 lbs / 8.1 kgs

- Lightweight
- Chemical hardening
- Low shrinkage
- Sandable

ProRoc® LITE Sand 5
Code: 308236

ProRoc® LITE Sand 20
Code: 308235

ProRoc® LITE Sand 45
Code: 308234

ProRoc® LITE Sand 90
Code: 308233

ProRoc® LITE Sand 210
Code: 308232



ProRoc® Moisture and Mold Resistant 90

Code: 312909

18 lbs / 8.1 kgs

- Moisture and mold resistant
- Lightweight
- Chemical hardening
- Low shrinkage
- Sandable

Wall and Ceiling Spray Textures

ProRoc® Brand Wall & Ceiling Spray Textures provide a decorative appearance over gypsum panels and most other interior wall and ceiling surfaces. They are formulated to provide for a variety of decorative options including splatter, knockdown and orange peel designs.



ProRoc® Wall & Ceiling Texture (Red)

Code: 308242

50 lbs / 22.6 kgs

- Suitable for all texture patterns
- Tough, durable finish
- Excellent mileage
- Unaggregated



ProRoc® Wall & Ceiling Texture (Blue)

Code: 308240

50 lbs / 22.6 kgs

- Easy mixing
- Good mileage
- Light to medium texture patterns
- Unaggregated



ProRoc® Easi-Tex Spray Texture

Code: 308241

48 lbs / 21.8 kgs

- Dust free pre-mixed product
- Harder and more durable finish
- Suitable for all spray patterns and equipment
- Unaggregated

Level V Wall and Ceiling Primer / Surfer

Level V Wall and Ceiling Primer / Surfer is a PVA product applied with a roller or airless sprayer to create a smooth wall finish. It takes a level 4 finish to level 5 without the need to putty coat by hand. Eliminates the intensive labor necessary with the traditional skim coat method and can be lightly sanded if needed. This product has exceptional hide and a self-leveling characteristic. Meets ASTM specifications for a Level V finish.



ProRoc® Level V Roll-On Wall and Ceiling Primer / Surfer

Code: 310096

5 gal / 18.9 L

- Takes a level 4 finish to level 5
- Designed for easy applied roller application, can be spray applied is desired
- Eliminates putty coating by hand
- Can be sanded but not necessary

ProRoc® Marco Joint Reinforcement

ProRoc® Marco Spark-Perf™ Joint Reinforcement Tape – delivers superior bond and tensile strength to joints.



ProRoc® Marco Spark-Perf™ Paper Tape

500' x 10 rolls Code: 161512

250' x 20 rolls Code: 163332

75' x 20 rolls Code: 165589

- Spark-perforated for easy pass-through of joint compound (mud) and elimination of air bubbles
- Manufactured from fibered-paper with added tensile strength to help prevent tearing, wrinkling or stretching
- Machine roughed for superior bonding



ProRoc® Marco Spark-Perf™ 94 Heavy Weight Paper Tape

500' x 10 rolls Code: 309631

- Heavy weight drywall tape
- Spark-perforated



FibaTape Mold-X-10™ Mold-Resistant Mesh Tape

300' x 12 rolls Code: 313384

- Compatible with mold resistant wallboard
- Self-adhesive for easy installation
- Perfect "10" rating on ASTM D3273 mold test
- To be used with setting compounds

Technical References

For additional information on the application and finishing of ProRoc® Brand Joint Compounds please consult:

- ASTM C 475: Standard specification for Joint Compound and Joint Tape for Finishing Gypsum Board.
- GA-214: Gypsum Association publication "Levels of Gypsum Board Finish."
- GA-216: Gypsum Association publication "Recommended Specifications for the Application and Finishing of Gypsum Board."
- ASTM C 840: Standard Specification for Application and Finishing of Gypsum Board.

Site Conditions

The room temperature should be maintained at 50°F (10°C) for 48 hours prior to application and continuously thereafter until completely dry. Gypsum wallboard should be dry for at least 48 hours before the application of joint compounds. Continuous ventilation must be provided to ensure proper drying. When using temporary heating, care should be taken to avoid overheating and high humidity.

Warranty

Since methods and condition of application such as temperature, humidity and over thinning are beyond our control, CertainTeed Gypsum, Inc. (CertainTeed) will not be responsible for the failure of this product when not used according to directions and specifications and accepted standards of procedure inherent in drywall application; or when reasonable allowance is not made by the user for adverse weather and job conditions. However, if this product proves to be defective, maximum liability shall be limited to replacement of the material only or refund of the purchase price. This shall be the full limit whatsoever of CertainTeed's liability. All claims shall be submitted in writing to CertainTeed within thirty days from the date of discovery. State or Federal laws may provide rights in addition to this warranty that cannot be modified or excluded.

ASK ABOUT OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

EXTERIOR: ROOFING • SIDING • WINDOWS • FENCE • RAILING • TRIM • DECKING • FOUNDATIONS • PIPE
INTERIOR: INSULATION • GYPSUM • CEILINGS

CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482

Professional: 800-233-8990
Consumer: 800-782-8777
www.certainteed.com

CertainTeed