

CertainTeed

ProRoc[®] BRAND

Western Canada Finishing Products



CertainTeed
SAINT-GOBAIN

ProRoc[®] Finishing Products

Professional Grade Ready-Mixed Joint Compounds, Setting Compounds, Wall and Ceiling Spray Textures, Joint Reinforcement Products, Industrial Coatings and Plasters.

ProRoc[®] Brand is a complete system of finishing products, specially developed to meet the demands of finishing professionals. The result is professional-grade performance that increases productivity, minimizes callbacks and delivers a great finish.

Ready-Mixed Joint Compounds

ProRoc[®] Brand Joint Compounds are pre-mixed high performance products designed for professional applicators. These products meet ASTM C 475 Standard.



- ProRoc[®] Lite All-Purpose**
Code: 311670
17 L / 4.5 US Gal.
- Ready-Mixed Joint Compound
 - Designed for fill/finish coats
 - Low shrinkage



- ProRoc[®] Lite Taping**
Code: 311680
17 L / 4.5 US Gal.
- Ready-Mixed Joint Compound
 - For embedding wall-board tape and trims
 - Excellent adhesion



- ProRoc[®] Lite Finishing**
Code: 311789
17 L / 4.5 US Gal.
- Ready-Mixed Joint Compound
 - Designed for finish coats
 - Low shrinkage
 - Easy to sand



- ProRoc[®] Lite All-Purpose**
Code: 313461
13.5 L / 3.5 US Gal.
- Ready-Mixed Joint Compound
 - Designed for fill/finish coats
 - Low shrinkage



- ProRoc[®] Lite Taping**
Code: 313460
13.5 L / 3.5 US Gal.
- Ready-Mixed Joint Compound
 - For embedding wall-board tape and trims
 - Excellent adhesion



- ProRoc[®] Lite Finishing**
Code: 313459
13.5 L / 3.5 US Gal.
- Ready-Mixed Joint Compound
 - Designed for finish coats
 - Low shrinkage
 - Easy to sand



- ProRoc[®] Lite All-Purpose**
Code: 309199
18 L / 4.75 US Gal.
- Ready-Mixed Joint Compound
 - Designed for fill / finish coats
 - Low shrinkage



- ProRoc[®] Lite Taping**
Code: 309200
18 L / 4.75 US Gal.
- Ready-Mixed Joint Compound
 - For embedding wall-board tape and trims
 - Excellent adhesion



- ProRoc[®] Lite Finishing**
Code: 309201
18 L / 4.75 US Gal.
- Ready-Mixed Joint Compound
 - Designed for finish coats
 - Low shrinkage
 - Easy to sand



- ProRoc[®] Dust Away Renovation Mud**
Code: 313382
13.5 L / 3.5 US Gal.
- Sanded dust clumps and falls to the floor
 - General purpose formula for filling, repairing and finishing
 - Ideal for renovations where cleanliness is required



- ProRoc[®] Mould Resistant**
Code: 312910
13.5 L / 3.5 US Gal.
- Use with M2Tech[®] gypsum board
 - Ready-Mixed Joint Compound
 - Designed for tape, fill and finish coats
 - Low shrinkage

The ProRoc® M2Tech® System



ProRoc® Moisture and Mould Resistant Gypsum Board with M2Tech®

ProRoc® Moisture and Mould Resistant 90 with M2Tech®
Code: 312908

FibaTape® Mold X10™ Mould Resistant Mesh Tape
Code: 313384

Sandable Setting Compounds

ProRoc® Brand LITE Sand Setting Compounds are lightweight sandable chemically setting powders used to prefill joints, embed mesh joint tape and conceal joints, fasteners and trim accessories on gypsum wallboard. They can also be used for interior patching and repair. They are ideal for heavy fills because they are specially formulated to harden with very little shrinkage in a prescribed time frame. Setting times are available from 20 minutes to 90 minutes.



ProRoc® Moisture and Mould Resistant 90 with M2Tech®
90 minute - Code: 312908
11 kgs / 24.25 lbs

- Part of the M2Tech® system of products
- Moisture and Mould Resistant
- Lightweight
- Chemical hardening
- Low shrinkage
- Sandable



ProRoc® LITE Sand
20 minute - Code: 309076
45 minute - Code: 309078
90 minute - Code: 309079
11 kgs / 24.25 lbs

- Lightweight formulation
- Chemical hardening
- Low shrinkage
- Sandable

High Density Setting Compounds

ProRoc® Brand High Density Setting Compounds are recommended for heavy fills or when exceptional bond is necessary. Once dry the product is not easily sanded. It is specially formulated to harden with very little shrinkage. Setting times are available from 20 minutes to 90 minutes.



ProRoc® High Density
20 minute - Code: 309055
45 minute - Code: 309083
90 minute - Code: 309084
15 kgs / 33 lbs

- High Strength Setting Compound
- Non-sandable
- Low shrinkage
- Use for embedding tape, heavy fills and repairs
- Exceptional strength

Dry Joint Compound

ProRoc® Brand Satin Coat All-Purpose Powder Compound provides a high quality drywall joint finish from a powder ready-to-mix product. Storage of product in cold conditions will not affect performance. Use to embed paper tape, conceal and finish joints, fasteners, and trim accessories on gypsum wallboard when the convenience of a single finishing product is desired. May be applied with either hand or mechanical tools.



ProRoc® Satin Coat All-Purpose Compound
Code: 309074
10 kgs / 22 lbs

- Air drying compound
- For embedding paper tape, finishing joints, fasteners and trim on gypsum wallboard
- Easy to mix and sand

Wall and Ceiling Spray Textures

ProRoc® Brand Wall and Ceiling Spray Textures provide a decorative appearance over gypsum panels and most other interior wall and ceiling surfaces. They are formulated to provide for a variety of decorative options including splatter, knockdown and orange peel designs.



- ProRoc® Medium -Tex
Spray Texture**
Code: 309089
15 kgs / 33 lbs
- Perlite aggregate based
 - Bright white medium texture finish
 - Good hide



- ProRoc® Coarse-Tex
Spray Texture**
Code: 309090
15 kgs / 33 lbs
- Polystyrene aggregate based
 - Bright white medium texture finish
 - Good hide



- ProRoc® Spanish-Tex
Spray Texture**
Code: 309092
10 kgs / 22 lbs
- Dust free pre-mixed product
 - Harder and more durable finish
 - Suitable for all spray patterns and equipment



- ProRoc® High Hiding
Spray Texture**
Code: 309091
15 kgs / 33 lbs
- Bright white one step finish
 - Polystyrene aggregate based
 - Easy to spray



- ProRoc Spray-Lite
Ready-Mixed Texture**
Code: 313130
17 L / 4.5 US Gal.
- Dust free pre-mixed product
 - Suitable for both hand and machine applications

Level V Wall and Ceiling Primer / Surfacer

ProRoc® Brand Level V Wall and Ceiling Primer / Surfacer is a PVA product applied with a roller or an airless sprayer to create a smooth wall finish. It takes a level 4 finish to level 5 without the need to skim coat by hand. Eliminates the intensive labour necessary with the traditional method and can be lightly sanded if needed. This product has exceptional hide and a self-leveling characteristic. Meets ASTM specifications for a level 5 finish.



- ProRoc® Level V Wall and Ceiling Primer / Surfacer**
Code: 310096
18.9 L / 5 US Gal.
- Takes a level 4 finish to level 5
 - Airless sprayer or roller application
 - Eliminates skim coating by hand
 - Can be sanded but not necessary

Easi-Fil™ Retail Compounds

Easi-Fil™ Brand All-Purpose Joint Compounds are premixed, air drying, easy-to-use products for any drywall job. Use them to embed paper tape, conceal and finish joints, fasteners and trim accessories. Easi-Fil™ compounds come in varying sizes for any job.



Easi-Fil™ All-Purpose

2 L / 0.5 US Gal – Code: 309068

4.5 L / 1.19 US Gal – Code: 309070

12 L / 3.17 US Gal – Code: 309072

- Ready-mixed Drywall Compound
- Embedding paper tape
- Filling and finishing drywall joints, trims and fasteners



Easi-Fil™ Dust Away

2 L / 0.5 US Gal – Code: 313378

4.5 L / 1.19 US Gal – Code: 313380

12 L / 3.17 US Gal – Code: 313394

- Reduces airborne dust by 70%
- When sanded, dust clumps and falls directly to the floor
- General purpose formula for filling, repairing and finishing
- Ideal for areas where cleanliness is required

Easi-Fil™ Brand Setting Powders are chemically setting compounds that set in a prescribed time for fast fills and repairs. They have a higher bond strength than air drying compound.



Easi-Fil™ Light Repair 20

Code: 309077

1.25 kg / 2.76 lbs.

- Setting Compound
- Embedding mesh tape
- Filling and finishing drywall joints, trims and fasteners
- Easy to sand
- Sets in 20 minutes



Easi-Fil™ Light Repair 90

Code: 309080

1.25 kg / 2.76 lbs.

- Setting Compound
- Embedding mesh tape
- Filling and finishing drywall joints, trims and fasteners
- Easy to sand
- Sets in 90 minutes



Easi-Fil™ Heavy Repair 90

Code: 309085

2 kg / 4.4 US Gal.

- Setting Compound
- Heavy fills and repairs
- Embedding mesh tape prior to finishing coat
- Hard to sand
- Sets in 90 minutes

Joint Reinforcement Tape

ProRoc® Marco™ Spark-Perf® Joint Reinforcement Tape is a spark perforated paper tape designed for use with ready-mix joint compound to reinforce gypsum board joints and corners.



163332

ProRoc® Marco™ Spark-Perf® Paper Tape

500' x 10 rolls – Code: 161512

250' x 20 rolls – Code: 163332

75' x 20 rolls – Code: 165589

- Spark-perforated for elimination of air bubbles without loss of tape strength.
- Manufactured from fibred-paper with added tensile strength to help prevent tearing, wrinkling or stretching
- Machine roughed for superior bonding
- For use with ready-mixed compounds

165589

161512



FibaTape® Mold-X-10™ Mould-Resistant Mesh Tape

Code: 313384

1-7/8" x 300'

- Compatible with mold resistant wallboard
- Self-adhesive for easy installation
- Perfect "10" rating on ASTM D3273 mold test
- For use with setting compounds

Gypsum Cove, Cornice and Steps

ProRoc® Decorative Moulding from CertainTeed is practical, as well as beautiful. It greatly reduces callbacks because ProRoc® eliminates the need to tape and finish wall/ceiling joints — where cracking most often occurs. It can also be used to conceal surface wiring or indirect lighting installations.



ProRoc® Decorative Moulding - Cove and Cornice

3/8" COVE 4-1/2" x 8' – Code: 163401

3/8" COVE 4-1/2" x 12' – Code: 163404

3/4" CORNICE 4-7/16" x 8' – Code: 163420

- Interior gypsum board moulding in Cove and Cornice profiles for installation at wall/ceiling intersection.
- Easy to Install using joint compound or caulking adhesive. No screws. No nails. No warping. No splitting.
- Easy to Decorate using the same paint as you do on gypsum board walls and ceilings



ProRoc® Decorative Moulding - Steps

Code: 309561

1/2" STEP 6" x 8'

- Square edge gypsum board used as base steps for the installation of ProRoc® Decorative Moulding.

Corner Beads

ProRoc® corner beads offer a high performance corner reinforcement system that delivers increased productivity, impact resistance and crack resistance, for a clean crisp corner.



ProRoc® Flexible Corner Bead

Code: 313722

100' x 12 rolls

- Flexible corner bead flexes to any inside or outside corner angle.
- Formulated surface paper accepts any finish and resists abrasion
- Perfect for off-angles, tray ceilings and bay windows



ProRoc® AquaBead™ Corner Reinforcement


Outside 90° - 8' – Code: 313724

Outside 90° - 9' – Code: 313723

Outside 90° - 10' – Code: 313725

L-Trim 1/2" - 10' – Code: 313726

- Quick and Easy — just spray on water and press
- No messy compound or spray adhesive required
- Can be coated in 30 minutes for quicker finishing
- Impact resistant



Technical References

For additional information on the application and finishing of ProRoc® Brand Joint Compounds please consult:

- ASTM C 840: Standard Specification for Application and Finishing of Gypsum Board.
- GA-214: Gypsum Association publication "Levels of Gypsum Board Finish."
- GA-216: Gypsum Association publication "Recommended Specifications for the Application and Finishing of Gypsum Board."
- ASTM C 475: Standard specification for Joint Compound and Joint Tape for Finishing Gypsum Board.

Site Conditions

The room temperature should be maintained at 13°C (55°F) for 48 hours prior to application and continuously thereafter until completely dry. Gypsum wallboard should be at room temperature for at least 48 hours before the application of joint compounds. Continuous ventilation must be provided to ensure proper drying. When using temporary heating, care should be taken to avoid overheating and high humidity.

Warranty

Since methods and conditions of application such as temperature, humidity and over thinning are beyond our control, CertainTeed Gypsum Inc. (CertainTeed) will not be responsible for the failure of this Product when the Product

is not used according to directions and specifications and accepted standards of procedure inherent in drywall application; or when reasonable allowance is not made by the user for adverse weather and job conditions. However, if this Product proves to be defective, maximum liability shall be limited to replacement of the material only or refund of the purchase price. This shall be the full limit whatsoever of CertainTeed's liability. All claims shall be submitted in writing to CertainTeed within thirty days from the date of discovery. State/Provincial or Federal laws may provide rights in addition to this warranty that cannot be modified or excluded.

ASK ABOUT OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

EXTERIOR: ROOFING • SIDING • TRIM • WINDOWS • RAILING • DECKING • FENCE

INTERIOR: INSULATION • GYPSUM • CEILINGS • FOUNDATIONS • PIPE

www.certainteed.com <http://blog.certainteed.com>

CertainTeed Corporation

P.O. Box 860

Valley Forge, PA 19482

Professional: 800-233-8990

Consumer: 800-782-8777

© 04/10 CertainTeed Gypsum Canada, Inc. Printed in Canada.
April 2010 Rev. 1 Code No. CTG-4029