

CertainTeed ProRoc[®] BRAND

Plaster of Paris – Quick Setting

Data and Submittal Sheet

DESCRIPTION

ProRoc[®] Plaster of Paris is a top quality, quick setting plaster normally used in combination with gauged lime putty when a shorter set time is desired. It can also be used, mixed with lime putty, for forming plaster mouldings where required. Can be used in a variety of applications.

PRODUCT DATA

MATERIAL: Plaster

COLOUR: Off white

PACKAGING: 25 kg (55 lbs) bag

COVERAGE: Varies depending on application.

SHELF LIFE: 6 months from production code date when stored properly.

STORAGE: Rotate stock to avoid aging problems. Use within 60 days of delivery. Abnormal storage conditions (e.g., high humidity), aged product, and improper proportioning can adversely affect hardness and working properties of the material. Store in a dry location.

WORKING WITH THE PRODUCT

PREPARATION:

To shorten the set time of gauged plaster:

Pour approximately 30 litres of clean water into the centre of a ring formed from approximately 50 kg of lime putty. Slowly add the amount of ProRoc[®] Plaster of Paris that will give the desired setting time, along with the gauging plaster, into the water without allowing the plasters to come into contact with the lime putty. Add 1 part dry gauging plaster by volume to 3 parts lime putty by volume. After the dry plasters have soaked up the water, mix the plasters with the water and then thoroughly blend the plaster with the lime putty. Avoid scraping the gauging board while mixing.

To use for forming plaster mouldings: Use approximately 7 parts water

to 10 parts plaster by weight. Sprinkle plaster into water and allow plaster to soak for 1/2 to 1 minute. Stir until uniform in consistency, then pour into mold.

PRECAUTIONS:

- For interior use only.
- This product generates heat as it hardens. Keep the compound away from exposed skin during the hardening process to prevent burns.
- Store in a dry place.
- Keep away from moisture.
- When mixing, wear safety glasses and dust mask approved by NIOSH/MSHA.
- Use clean water, tools and equipment.
- Do not use in areas subject to continuous high levels of humidity.
- Do not apply or re-mix after it has started to set.
- Do not apply to standard drywall, nor to exterior sheathing.
- Keep out of reach of children.

MSDS:

MSDS Material Safety Data Sheets are available on our web site, www.certainteed.com.

WARNING:

Dust generated from sanding product may cause eye, skin, nose, throat or respiratory irritation. Use wet-sanding to avoid creating dust. Avoid inhalation of dust and eye contact. Product contains silica. Inhalation of respirable silica dust can cause silicosis, a potentially disabling lung disease, known to cause lung cancer.

When sanding, drilling or abrading product during installation or handling: (1) Ensure adequate ventilation. (2) Wear a dust mask or, if dust may exceed PEL, use NIOSH/MSHA approved respirator. (3) Warn others in area. (4) Wear eye protection.

If eye contact occurs, flush thoroughly with water for 15 minutes. For further information, refer to Material Safety Data Sheet or consult manufacturer by calling 1-866-427-2872.

KEEP OUT OF REACH OF CHILDREN.

SUBMITTAL APPROVAL STAMPS/SIGNATURES

Please check the appropriate products above which are being submitted for approval

Date:

Project:



Plaster of Paris – Quick Setting

Data and Submittal Sheet

WARRANTY:

Since methods and condition of application such as temperature, humidity and over thinning are beyond our control, CertainTeed Gypsum (CertainTeed) will not be responsible for the failure of this product when not used according to directions and specifications and accepted standards of procedure inherent in drywall application; or when reasonable allowance is not made by the user for adverse weather and job conditions. However, if this product proves to be defective, maximum liability shall be limited to replacement of the material only or refund of the purchase price. This shall be the full limit whatsoever of CertainTeed's liability. All claims shall be submitted in writing to CertainTeed within thirty days from the date of discovery. Provincial or Federal laws may provide rights in addition to this warranty that cannot be modified or excluded.

ASK ABOUT OUR OTHER CERTAINTEED PRODUCTS AND SYSTEMS:

EXTERIOR: ROOFING • SIDING • WINDOWS • FENCE • RAILING • TRIM • DECKING • FOUNDATIONS • PIPE
INTERIOR: INSULATION • GYPSUM • CEILINGS

CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482

Professional: 800-233-8990
Consumer: 800-782-8777
www.certainteed.com



Characteristics, properties or performance of materials or systems manufactured by CertainTeed herein described are derived from data obtained under controlled test conditions. CertainTeed makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. CertainTeed assumes no responsibility for the effects of structural movement.

™& © CertainTeed and the tag line "Quality made certain. Satisfaction guaranteed." are trademarks of CertainTeed Corporation. All other trademarks are the property of its affiliates and related companies.

NOTICE: The information in this document is subject to change without notice. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

©03/08 CertainTeed Corporation. Printed in Canada on recycled paper. ♻️ March 2008 Rev. 1 Form #: L-SD-005-E