

CertainTeed

# ProRoc<sup>®</sup> BRAND

## Wall & Ceiling Spray Textures

### Product Data and Submittal

#### Product Description

ProRoc<sup>®</sup> Brand Wall and Ceiling Spray Textures provide a decorative appearance over gypsum panels and most other interior wall and ceiling surfaces. They are formulated to provide for a variety of decorative options including splatter, knockdown and orange peel designs.

#### ProRoc<sup>®</sup> Brand Wall & Ceiling Texture - RED (powder)

- Unaggregated interior wall and ceiling spray texture
- Suitable for all texture patterns
- Harder and more durable finish
- Excellent coverage

#### ProRoc<sup>®</sup> Brand Wall & Ceiling Texture - BLUE (powder)

- Unaggregated interior wall and ceiling spray texture
- Light to medium texture patterns
- Easy lump free mixing
- Good mileage

#### ProRoc<sup>®</sup> Brand Wall & Ceiling Texture - GREEN (powder)

- Unaggregated interior wall and ceiling spray texture
- Light to medium texture patterns
- Fast and easy mixing
- Excellent coverage

#### ProRoc<sup>®</sup> Brand Easi-tex<sup>™</sup> (ready-mixed)

- Pre-mixed unaggregated interior wall and ceiling spray texture
- Suitable for all spray patterns and equipment
- Dust free pre-mixed product
- Harder and more durable finish

#### Product Data

**Material:** Powder or Ready-Mixed

**Color:** Off white

**Packaging:** Powder 50 lb. (22.7kg) Bag,

Ready-Mix 48 lb. (21.8kg) Carton

**Coverage:** Approximately 500 ft<sup>2</sup> per package, depending upon the type of pattern, the condition of the substrate, and the application technique.

**Shelf Life:** Ready-Mixed – 6 months from production code date when stored properly.

Powders – 12 months from production code date when stored properly.

**Drying Time:** 8 hours in normal conditions.

**Storage:** ProRoc<sup>®</sup> Wall and Ceiling Textures should be stored in a dry, temperate location where there can be no contact with wet surfaces. Opened bags should be closed tightly before storage. Protect Ready-Mixed texture from freezing.

**Technical References:** For additional information on the application of ProRoc<sup>®</sup> Brand Spray

- ASTM C 475: Standard specification for Joint Compound and Joint Tape for Finishing Gypsum Board.
- ASTM C 840: Standard specification for Application and Finishing of Gypsum Board.
- GA-214: Gypsum Association publication “Levels of Gypsum Board Finish.”
- GA-216: Gypsum Association publication “Recommended Specifications for the Application and Finishing of Gypsum Board.”

#### Working with the Product

##### Site Conditions:

The room temperature should be maintained at 50°F (10°C) for 48 hours prior to application and continuously thereafter until completely dry. Gypsum wallboard should be dry for at least 48 hours before the application of texture products. Continuous ventilation must be provided to ensure proper drying. When using temporary heating, care should be taken to avoid overheating and high humidity.

(Continued on back)

Job Name

Contractor

Date

Products Specified:

Submittal Approvals  
(Stamps or Signatures)

**CertainTeed**   
Quality made certain. Satisfaction guaranteed.™

## Preparation and Use:

### Surface Preparations:

Ensure that surfaces to be decorated are thoroughly dry and free of dirt, oils, mildew and other contaminants.

### Priming:

All surfaces to be textured should be primed prior to application with a good quality interior primer-sealer specified for drywall applications to ensure uniform porosity and texture. Primer should be dry prior to applying texture. Adhere to all manufacturers' specific directions for painting and decorating materials.

### Mixing:

Use a clean vessel equipped with powder agitator. For initial mix, stir powder into recommended amount of water agitating during powder addition. Allow to soak for at least 15 minutes. Remix until creamy, lump-free mix is obtained. Adjust spray consistency by adding small amounts of water, if necessary. Over thinning can create an undesirable finish, "soft wall" or chalky condition. Over dilution can also entrain excessive air and foam. *Note that the air and mix temperature will affect viscosity.*

### Application:

Texture should not be applied until the primer coat is thoroughly dry. Products are specifically designed for spray application. The desired pattern can be achieved by varying the viscosity of the mix, the orifice opening at the spray tip, or the air supply pressure.

### Decorating

It is recommended that this product be painted after drying. Adhere to all manufacturers' specific directions for painting and decorating materials.

## Limitations:

- Application below grade or in high humidity areas is not recommended.
- May contribute to sagging of gypsum board ceilings in humid conditions. The potential for sagging can be minimized by taking the following precautions:
- Gypsum board should be applied perpendicular to the framing at the proper spacing recommendation for the board thickness (see GA-216, Tables 1 and 4).
- Excessive amounts of insulation should not be added without additional support (GA-216, Table 2).
- The relative humidity should be controlled by providing adequate ventilation before, during and after gypsum board and finish application.
- Temperatures should be maintained between 50°F and 70°F, (10°C and 21.1°C).
- Gypsum board should be thoroughly dry and at ambient temperature before application.
- Joint treatment should be thoroughly dry before applying any decoration.
- Individual coats of primer and paint shall be dry before the application of successive coats.
- Where the gypsum board supports ceiling insulation and is finished with a water-based texture material, either spray or hand applied, only 5/8" gypsum board or 1/2" gypsum ceiling board, application perpendicular to the framing members shall be used.
- Texture is not washable unless painted.

## Warning:

Dust generated from sanding product may cause eye, skin, nose, throat or respiratory irritation. Use wet-sanding to avoid creating dust. Avoid inhalation of dust and eye

contact. Product contains silica. Inhalation of respirable silica dust can cause silicosis, a potentially disabling lung disease, and is known to the State of California to cause lung cancer. When sanding, drilling or abrading product during installation or handling:

(1) Ensure adequate ventilation. (2) Wear a dust mask or, if dust may exceed PEL, use NIOSH/ MSHA approved respirator. (3) Warn others in area. (4) Wear eye protection. If eye contact occurs, flush thoroughly with water for 15 minutes. For further information, refer to Material Safety Data Sheet or consult manufacturer by calling 1-800-327-7455.

**KEEP OUT OF REACH OF CHILDREN.**

## Warranty:

Since methods and condition of application such as temperature, humidity and over thinning are beyond our control, CertainTeed Corporation (CertainTeed) will not be responsible for the failure of this product when not used according to directions and specifications and accepted standards of procedure inherent in drywall application; or when reasonable allowance is not made by the user for adverse weather and job conditions. However, if this product proves to be defective, maximum liability shall be limited to replacement of the material only or refund of the purchase price. This shall be the full limit whatsoever of CertainTeed's liability. All claims shall be submitted in writing to CertainTeed within thirty days from the date of discovery. State or Federal laws may provide rights in addition to this warranty that cannot be modified or excluded.

## ASK ABOUT OUR OTHER CERTAINTEED PRODUCTS AND SYSTEMS:

**EXTERIOR:** ROOFING • SIDING • WINDOWS • FENCE • DECKING • RAILING • MILLWORK • FOUNDATIONS • PIPE  
**INTERIOR:** INSULATION • WALLS • CEILINGS

CertainTeed Corporation  
P.O. Box 860  
Valley Forge, PA 19482

Professional: 800-233-8990  
Consumer: 800-782-8777  
[www.certainteed.com](http://www.certainteed.com)

**CertainTeed** 

Characteristics, properties or performance of materials or systems manufactured by CertainTeed herein described are derived from data obtained under controlled test conditions. CertainTeed makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. CertainTeed assumes no responsibility for the effects of structural movement.

™ © CertainTeed and the tag line "Quality made certain. Satisfaction guaranteed." are trademarks of CertainTeed Corporation. All other trademarks are the property of its affiliates and related companies.

NOTICE: The information in this document is subject to change without notice. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

©09/07 CertainTeed Corporation. Printed in U.S.A. CTG-4005/3M/9-2007