


Landmark® PRO Shingles

PRODUCT INFORMATION

Landmark® PRO shingles reflect the same high manufacturing standards and superior warranty protection as the rest of CertainTeed's line of roofing products. Landmark PRO (and Algae Resistant-AR) are built with the industry's toughest fiber glass mat base, and their strict dimensional tolerance assures consistency. Complex granule color blends and subtle shadow lines produce a distinctive color selection. Landmark PRO is produced with the unique NailTrak® nailing feature.



Landmark PRO algae-resistant (AR) shingles are algae-resistant and help protect against dark or black discoloration, sometimes called staining or streaking, caused by blue-green algae (*gloeocapsa magma*). AR shingles are not available in all regions.

Colors: Please refer to the product brochure or CertainTeed website for the colors available in your region.

Limitations: Use on roofs with slopes greater than 2" per foot. Low-slope applications (2:12 to < 4:12) require additional underlayment. In areas where icing along eaves can cause the back-up of water, apply CertainTeed WinterGuard® Waterproofing Shingle Underlayment, or its equivalent, according to application instructions provided with the product and on the shingle package.

Product Composition: Landmark PRO shingles are composed of a fiber glass mat base. Ceramic-coated mineral granules are tightly embedded in carefully refined, water-resistant asphalt. Two pieces of the shingle are firmly laminated together in a special, tough asphaltic cement. All Landmark shingles have self-sealing adhesive strips.

Applicable Standards

ASTM D3018 Type I

ASTM D3462

ASTM E108 Class A Fire Resistance

ASTM D3161 Class F Wind Resistance

ASTM D7158 Class H Wind Resistance

UL 790 Class A Fire Resistance

ICC-ES ESR-1389 and ESR-3537

CSA Standard A123.5 (Regional)

Miami-Dade Product Control Approved (Regional)

Florida Product Approval # FL5444

Meets TDI Windstorm Requirements

UL 2218 Class 3 Impact Resistance

(at time of manufacture)

Technical Data:

	Landmark PRO (and AR)
Weight/Square (approx.)	231 to 240 lb *
Dimensions (overall)	13 1/4" x 38 3/4"
Weather Exposure	5 5/8"
Shingles/Square (approx.)	66
Bundles per square	3
Coverage per square	100 square feet

*Dependent on manufacturing location. Weight per 100 square feet.

INSTALLATION

Detailed installation instructions are supplied on each bundle of Landmark PRO shingles and must be followed. Separate application sheets may also be obtained from CertainTeed.

Hips and Ridges: For capping hip and ridge apply CertainTeed Shadow Ridge®, Cedar Crest® or Mountain Ridge® shingles of a like color.

MAINTENANCE

These shingles do not require maintenance when installed according to manufacturer's application instructions. However, to protect the investment, any roof should be routinely inspected at least once a year. Older roofs should be looked at more frequently.

WARRANTY

Landmark PRO (and AR) shingles carry a lifetime limited, transferable warranty to the consumer against manufacturing defects when applied to stated CertainTeed application instructions for this product. In addition, Landmark PRO (and AR) shingles carry up to 10-years of SureStart™ Protection. Landmark PRO AR shingles carry a 30-year algae resistance warranty if installed with CertainTeed Hip and Ridge Accessories mentioned above. For specific warranty details and limitations, refer to the warranty itself (available from the local supplier, roofing contractor or on-line at www.certainteed.com).

TECHNICAL SUPPORT

Technical Service Department: 800-345-1145

e-mail: RPG.T.Services@saint-gobain.com

FOR MORE INFORMATION

Customer Experience Team: 800-233-8990

e-mail: gethelp@saint-gobain.com

Web site: www.certainteed.com

CertainTeed

20 Moores Road
Malvern, PA 19355

© 10/23 CertainTeed

