



Volu-Matic® 300

BLOWING MACHINE

The Industry Workhorse

Designed to operate in tough environments, the Volu-Matic 300 provides years of dependable service with superior performance. The Volu-Matic 300 is easily adjustable, making it the ideal machine for attic and netted-cavity insulation. It's also available in an electric version for in-plant applications such as fiber testing labs or manufactured housing.

Features & Benefits

- Single point grease bank for ease of maintenance
- Quick change seal system
- Heavy-duty idler assembly
- Protected emergency stop assemblies
- Wired remote control with cord plugin guard
- Solid heavy-duty drop gate with reinforced hinges
- Knife holder box with optional long blade holder

Optional PLC Digital Display Technology Package



- Preventative maintenance notifications
- Support screens with troubleshooting tips
- Bag counter by job
- Real-time parts replacement alert timers with part numbers

MACHINE SPECIFICATIONS

| | |
|-------------------------|---|
| Insulation | Fiberglass, Stone Wool, Cellulose |
| Power Options Available | Power Take-Off (PTO) 23.5 Horsepower Carburated Gasoline Engine 26.5 Horsepower EFI Gasoline Engine 23.7 Horsepower Diesel Engine Electric Power Available At 240 Volt, 480 Volt, or 600 Volt |
| Typical Feed Rate* | Fiberglass 25-35 lbs./min. Stone Wool 35-55 lbs./min. Cellulose 70-80 lbs./min. |
| Load Height | 63.5" |
| Height | 72" |
| Width | 75" |
| Depth | 56.5" |
| Weight: Approx | 2,000 lbs. |

* Rates apply to material that has been properly conditioned.

ACCESSORY OPTIONS

Hopper Extensions
Air Compressor
Wireless Remote Control
Blowing Hose
Couplings and Clamps
Built-In MP 20 Water Pump

Featured Details

Fully Sealed Blow-Through Air-Lock Feeder – Seals pressurized airflow to provide installer with a consistent flow of conditioned fiber.

Air Volume Control System – Adjustable air pressure and air flow control with panel mounted display gauge.

Four-Speed Transmission – Operator-selected speed control for various materials and applications. Allows additional control of air-to-material ratio.

Material Control Slide – Secondary volume and conditioning control. Allows operator adjustment of fiber flow to the shredder.

Mechanical Overload Protection – protects the internal hopper components and air-lock feeder from foreign objects.

EZ Single Point Grease Bank – Simple scheduled bearing lubrication through one color-coated grease bank.


Powder-Coat Finish – Durable, long-life protection for your investment.

Integrated Safety Features – Emergency stop switches; electrical interlock; front, rear and side guards.

Self-Aligning Sealed Bearings – High-quality bearings are used throughout the certainteed machine works product line. They are sealed to keep out dust and equipped with zerk fittings for proper maintenance.

Adjustable Drive Belts – Flexibility to adjust belt tension as belts wear to maximize belt life.

Visit us at www.ctmachineworks.com or call us at 800-237-7841 for more information.



CertainTeed Machine Works offers a comprehensive line of commercial and residential insulation and fireproofing application equipment, including blowing machines, vacuums and accessories. We provide equipment installation, troubleshooting and repair, custom machine design services, and same-day shipping of spare parts.