

TL-0006 — In-Place Performance Temperatures

The GRACE VYCOR™ portfolio of underlayments (GRACE VYCOR™ ICE & WATER SHIELD®, GRACE VYCOR™ ICE & WATER SHIELD® HT, GRACE VYCOR™ ULTRA™, GRACE VYCOR™ SELECT™, and ROOF DETAIL MEMBRANE) are formulated to withstand rooftop temperatures. The temperature that a roof assembly reaches can vary significantly depending on the time of year, the local climate, the color and composition of the roof covering material, and the construction of the roof assembly. Based on actual in-place temperature measurements and mathematical models using climatic data from the National Oceanic and Atmospheric Agency, CertainTeed understands the temperatures that roofs are likely to experience. Based on these measured and calculated roof temperatures, these underlayments are formulated for performance for the life of the roof.

GRACE VYCOR™ ULTRA™ and GRACE VYCOR™ ICE & WATER SHIELD® HT have been formulated to provide the highest factor of safety when used under extreme climatic and roof construction conditions. An example of extreme roof construction temperature conditions may be a black metal roof installed over the underlayment applied to rigid insulation boards with no roof ventilation. Extreme climatic conditions may be defined as the 30 year hourly extreme temperature, and on the summer solstice when solar radiation is maximum.

While GRACE VYCOR™ ULTRA™ and GRACE VYCOR™ ICE & WATER SHIELD® HT are formulated to provide the highest factor of safety under extreme temperatures, in many roof constructions temperature of the underlayment would be less than the case above. Lighter roof colors, an air space or insulation over the underlayment, and roof ventilation will all significantly mitigate the temperature the membrane will experience. Also, the roof may be subjected to extreme climatic conditions for only a small fraction of its useful life. Therefore, in most cases GRACE VYCOR™ ICE & WATER SHIELD®, GRACE VYCOR™ SELECT™, and ROOF DETAIL MEMBRANE exceed the in-place performance temperature requirements and provide an appropriate factor of safety.

Not all self-adhered membrane materials are designed and manufactured to work in hot climates or in high temperature roof constructions. GRACE VYCOR™ ULTRA™, GRACE VYCOR™ ICE & WATER SHIELD®, GRACE VYCOR™ ICE & WATER SHIELD® HT, GRACE VYCOR™ SELECT™, and ROOF DETAIL MEMBRANE have been formulated specifically for performance at rooftop temperatures.

Certainteed.com | Customer Service: 800-233-8990

This document is only current as of the last updated date stated below and is valid only for use in North America. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on [certainteed.com](https://www.certainteed.com). Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact CertainTeed Customer Service.