

## TL-0009 — Fastener Sealability

The GRACE VYCOR™ portfolio of underlayments (GRACE VYCOR™ ICE & WATER SHIELD®, GRACE VYCOR™ ICE & WATER SHIELD® HT, GRACE VYCOR™ ULTRA™, GRACE VYCOR™ SELECT™, and ROOF DETAIL MEMBRANE) are formulated to provide a quality seal around fastener penetrations. However, the quality of that seal can be significantly affected by the type of fastener used and the manner in which they are installed.

For best results, use smooth shank electroplated galvanized fasteners. Hand nailing generally provides a better seal than power activated nailing. Do not install the fasteners through the underlayment over unsupported areas of the structural deck, such as over the joints between adjacent structural panels. In addition, the fasteners should be installed as straight as possible, so the membrane is not torn. It is important that the temperature at the time the fasteners are installed through membrane is 40°F (5°C) or higher for optimum sealability. If fasteners are removed leaving holes in the underlayment, the membrane must be patched with a round piece of membrane extending past the damaged area 6 inches (150 mm) in all directions. Underlayments may not self-seal open fastener penetrations.

### **CertainTeed.com | Customer Service: 800-233-8990**

This document is only current as of the last updated date stated below and is valid only for use in North America. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on [certainteed.com](https://www.certainteed.com). Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact CertainTeed Customer Service.