

SUBMITTAL SHEET 150F

Project Name _____

Specification Section _____

Ceiling Type _____

SUBSTRATE: .025" Aluminum

COLOR/FINISH

- Luxacote Lighthouse White - #0401
- Luxacote Natural - #7080
- Other _____

PERFORATION PATTERN

- Non-Perforated
- #124 _____ % Vent Panels (Max 10% of ceiling)

TRIM

- Wall Angle
- Other _____

Color/Finish: # _____

EXPOSURE Exterior Only - Design Wind Pressure (required) _____ PSF

Shop Drawings required on all Exterior projects.


To Contact Us:
5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.366.4327
fax: 770.806.0214
www.CertainTeed.com/Architectural

ARCHITECTURAL

CertainTeed
SAINT-GOBAIN

PERFORATIONS

Perforated panels improve acoustical performance as well as create aesthetic effects.

#124

Perforation diam: .078 in.
Open Area: 15%

Miami-Dade County, Florida
NOA No. 20-0203.01
(expires March 19, 2025)

Exterior Application Vent Panels

PHYSICAL DATA

Substrate: Aluminum

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread: ≤ 25 , Smoke ≤ 50

Weight: 0.75 lbs./sq.ft.

Wind load: Per code

Designed and tested in accordance with the requirements of the Florida Building Code 6th edition (2017), including the High Velocity Hurricane Zone (HVHZ) provisions and Miami-Dade requirements.

Miami-Dade County, Florida NOA No. 20-0203.01 (expires March 19, 2025)

Exterior Application Non-Perforated Panels and perforation #124 exterior vent panels

Recycled content: Up to 92%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81