

SUBMITTAL SHEET

150F

Project Name _____

Specification Section _____

Ceiling Type _____

SUBSTRATE: .025" Aluminum

COLOR/FINISH Luxacote Lighthouse White – #0401
 Luxacote Natural – #7080
 Other _____

PERFORATION PATTERN Non-Perforated #160 _____ % Vent Panels (Max 10% of ceiling)

TRIM Wall Angle Other _____
Color/Finish: # _____

EXPOSURE Exterior – Design Wind Pressure (required) _____ PSF


Shop Drawings required on all Exterior projects.

To Contact Us:
5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.366.4327
fax: 770.806.0214
CTSpecialtyCeilings.com

HunterDouglas 
Ceiling & Wall Products
exclusively from CertainTeed

PERFORATIONS – VENT PANELS

#160



Perforation diam: .060 in.
Open Area: 23%

PHYSICAL DATA

Substrate: Aluminum

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread: ≤ 25 , Smoke ≤ 50

Weight: 0.75 lbs./sq.ft.

Wind load: Per code

Designed and tested in accordance with the requirements of the Florida Building Code 5th edition (2014), including the High Velocity Hurricane Zone (HVHZ) provisions and Miami-Dade requirements.

Miami-Dade County, Florida NOA No. 17-0807.10 (expires March 19, 2020)

Exterior Application Non-Perforated Panels

Recycled content: Up to 92%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81