Safety Data Sheet



Section 1: Identification

Product identifier

Product Name

 Residential Building Insulation - Sustainable Insulation™ CT10144-8

Synonyms

 Basement Wall Insulation; Building Insulation (Unfaced & Kraft Faced); Commercial Blanket; Commercial Board Insulation; EasyTouch™ Encapsulated Insulation; Flame-Resistant Class A (PSK-25); Flame-Resistant Class A (PSK-25) Fiber Glass Building Insulation; Foil-Faced Building Insulation; Masonry Wall Batts; Noise Reducer™ Sound Batts; SMARTBATT™; SpeedyR™; UltraTherm® Blowing Insulation

Product Literature Code: 30-45-002.

Relevant identified uses of the substance or mixture and uses advised against

Recommended use

· Acoustical & Thermal Insulation

Details of the supplier of the safety data sheet

Manufacturer

CertainTeed Corporation

20 Moores Road Malvern, PA 19355 United States www.certainteed.com

CertainTeed-EHS@saint-gobain.com

Telephone (General) • 610-893-6000

Emergency telephone number

Manufacturer 800-424-9300 - CHEMTREC

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012

· Not classified

Label elements **OSHA HCS 2012**

Hazard statements • No label element(s) required

Other hazards

OSHA HCS 2012

This product is not considered hazardous under the U.S. OSHA 29 CFR 1910.1200 Hazard Communication Standard.

Canada

According to: WHMIS

Preparation Date: 22/June/2012 Revision Date: 27/April/2016 OSHA HCS 2012 Page 1 of 13

Classification of the substance or mixture

WHMISNot classified

Label elements

WHMISNo label element(s) required.

Other hazards

• In Canada, the product mentioned above is not considered hazardous under the

Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

Substances

• Material does not meet the criteria of a substance.

Mixtures

			Composit	tion	
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Glass, oxide, chemicals	CAS :65997 -17-3	78% TO 97%	NDA	OSHA HCS 2012: Not Classified	NDA
Petroleum asphalt, oxidized	CAS :64742 -93-4	0% TO 17%	NDA	OSHA HCS 2012: Not Classified	The oxidized asphalt contained in our finished product is a solid form and therefore poses no similar exposure to the heated liquid form during roofing which resulted in IARC classification for this material.
Acetic acid, vinyl ester, polymer	CAS :9003- 20-7	< 11%	Ingestion/Oral- Rat LD50 • >25 g/kg	OSHA HCS 2012: Not Classified	NDA
Proprietary	NDA	3% TO 9%	NDA	OSHA HCS 2012: Not Classified	NDA
Acetic acid ethenyl ester, polymer with ethene	CAS :24937 -78-8	< 7%	Ingestion/Oral- Rat LD50 • >2500 mg/kg	OSHA HCS 2012: Not Classified	NDA
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	CAS :64742 -65-0	0.5% TO 1.5%	NDA	OSHA HCS 2012: Not Classified	NDA
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	CAS :64742 -54-7	0.5% TO 1.5%	NDA	OSHA HCS 2012: Asp. Tox. 1	NDA

Section 4: First-Aid Measures

Description of first aid measures

Inhalation

· Move victim to fresh air. Get medical attention immediately if symptoms occur.

Skin

 Immediately flush skin with soap and plenty of water. Take off contaminated clothing and wash before reuse. If skin irritaion occurs: Get medical advice/attention.

Eve

• Do not rub or scratch your eyes. Flush eyes with water for at least 15 minutes while holding eyelids open. Get medical attention immediately if symptoms occur.

Ingestion

• Unlikely. Consult physician if unusual reaction is noted.

Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

All treatments should be based on observed signs and symptoms of distress in the
patient. Consideration should be given to the possibility that overexposure to materials
other than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media • Use that which is applicable to surrounding fire.

Unsuitable Extinguishing Media

· None known.

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

 Does not support combustion. These products contain a cured binder and various facings which contain retardant systems to reduce the possibility of fire. Use of plasma or other type of cutting tool may cause the release of toxic fumes and smoke. Facings on these products may burn. Do not leave facing exposed when working close to an open flame. If burned, the materials could release toxic fumes.

Hazardous Combustion Products

 If burned, the materials could release toxic fumes and smoke. The binder and kraft facings combustion products include carbon-dioxide, hydrogen chloride, carbon monoxide and molecular fragments of hydrocarbon particles, carbon-hyrdogen-nitrogen and nitrogen-oxygen compounds. Comparative animal inhalation toxicity studies of combustion products on a number of CertainTeed fiber glass insulation products found the insulation products to be no more toxic than wood based on incapacitation and mortality.

Advice for firefighters

 Fire fighters should wear complete protective clothing including self-contained breathingapparatus.

Fire fighters should avoid inhaling any combustion products. Firefighters should wear full-face, self contained breathing apparatus and impervious protective clothing.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions

 Avoid contact with skin and eyes during clean-up. Wear appropriate protective equipment.

Emergency Procedures

 Persons not wearing appropriate protective equipment should be excluded from area of spill until clean-up has been completed. Ventilate the contaminated area.

Environmental precautions

No special precautions necessary.

Methods and material for containment and cleaning up

Containment/Clean-up Measures

Avoid generating dust.

Vacuum dust deposits. Do not use compressed air for clean-up.

Preparation Date: 22/June/2012 Revision Date: 27/April/2016 Format: GHS Language: English (US)
OSHA HCS 2012

Section 7 - Handling and Storage

Precautions for safe handling

Handling

Do not breathe dust from this material. Keep this product from heat, sparks, or open flame. Use this product with adequate ventilation. Always wash work clothes separately from other clothing. Wipe out the washer or sink to prevent loose glass fibers from getting on other clothing. Wash thoroughly after handling. Use personal protective equipment as described in Section 8.

Conditions for safe storage, including any incompatibilities

Storage

Store in a dry place and under cover to protect product.

Section 8 - Exposure Controls/Personal Protection

Control parameters

	Exposure Limits/Guidelines				
	Result	ACGIH	NIOSH		
Glass, oxide, chemicals	TWAs	1 fiber/cm3 TWA (respirable fibers: length >5 µm, aspect ratio >=3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination, listed under Synthetic vitreous fibers) as Glass wool fiber	3 fiber/cm3 TWA (fibers <= 3.5 μm in diameter and >= 10 μm in length); 5 mg/m3 TWA (total) as Glass wool fiber		

Exposure Control Notations ACGIH

•Glass, oxide, chemicals as Glass wool fiber: Carcinogens; (A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans (listed under Synthetic vitreous fibers))

Exposure controls

Engineering Measures/Controls

Personal Protective Equipment

Respiratory

Eve/Face

Skin/Body

Considerations

Hands

 Avoid spread of fiber glass dust. Provide general and/or local exhaust ventilation to control airborne dust levels below exposure limits.

A properly fitted NIOSH (American National Institute For Occupational Safety And Health) approved disposable N 95 series dust respirator such as type 3M 8210 (formerly 8710) or 3M 8271 (formerly 9900) respirators should be used under any dust environment or during a process that generates dusts. Use respiratory protection in accordance with the respiratory protection program of your company, local regulations and OSHA regulations under 29 CFR 1910.134.

Safety glasses with side shields should be worn at a minimum. In dusty environments chemical goggles should be worn.

Work clothing sufficient to prevent all skin contact should be worn, such as overalls, long sleeves and cap.

No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

General Industrial Hygiene

Wash hands, face and other potentially exposed areas immediately after handling material (especially before eating, drinking, or smoking). Decontaminate all protective equipment after use.

Environmental Exposure Controls

 Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways. Follow best practice for site management and disposal of waste.

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Solid	Appearance/Description	Tan solid with faint sweet odor.
Color	Tan	Odor	Faint sweet odor.
Odor Threshold	No data available		
General Properties		-	-
Boiling Point	No data available	Melting Point/Freezing Point	2200 °F(1204.4444 °C)
Decomposition Temperature	No data available	рН	No data available
Specific Gravity/Relative Density	= 2.5 Water=1	Density	0.51 to 1.34 lb(s)/ft ³
Water Solubility	Slightly Soluble	Viscosity	No data available
Volatility	•	-	•
Vapor Pressure	No data available	Vapor Density	No data available
Evaporation Rate	No data available		
Flammability			
Flash Point	No data available	UEL	No data available
LEL	No data available	Autoignition	No data available
Flammability (solid, gas)	No data available		
Environmental			
Octanol/Water Partition coefficient	No data available		

Section 10: Stability and Reactivity

Reactivity

No dangerous reaction known under conditions of normal use.

Chemical stability

· Stable under normal conditions of use.

Possibility of hazardous reactions

Hazardous polymerization will not occur.

Conditions to avoid

Keep away from heat, ignition sources and incompatible materials.

Incompatible materials

Hydrofluoric acid.

Hazardous decomposition products

 Hazardous decomposition may occur generating toxic fumes/vapors, oxides of carbon (COx), oxides of nitrogen (NOx).

Section 11 - Toxicological Information

Information on toxicological effects

Other Material Information

Temporary irritation may be observed in the upper respiratory system, eyes, and skin. This product has not been tested as a separate entity. Therefore, the hazards must be evaluated on the basis of the individual ingredients, and those hazards must be assumed to be additive in the absence of complete information. A properly fitted NIOSH (American National Institute For Occupational Safety And Health) approved disposable N 95 series dust respirator such as type 3M 8210 (formerly 8710) or 3M

8271 (formerly 9900) respirators should be used under any dust environment or during a process that generates dusts. Use respiratory protection in accordance with the respiratory protection program of your company, local regulations and OSHA regulations under 29 CFR 1910.134.

	Components			
Glass, oxide, chemicals (78% TO 97%)	65997- 17-3	Tumorigen / Carcinogen: Inhalation-Rat TCLo • 5 mg/m³ 7 Hour(s) 90 Week(s)-Intermittent; <i>Tumorigenic</i> : Carcinogenic by RTECS criteria ; <i>Blood</i> : Leukemia		
Hydrotreated heavy paraffinic petroleum distillate (highly refined) (0.5% TO 1.5%)	64742- 54-7	Acute Toxicity: Ingestion/Oral-Rat LD50 • >15 g/kg; Skin-Rabbit LD50 • >5 g/kg; Multi-dose Toxicity: Inhalation-Rat TCLo • 1000 mg/m³ 4 Week(s)-Intermittent; Lungs, Thorax, or Respiration:Changes in lung weight		
Mineral oil, petroleum distillates, solvent- dewaxed heavy paraffinic (severe solvent- refiningand/or hydrotreatment) (0.5% TO 1.5%)	64742- 65-0	Acute Toxicity: Ingestion/Oral-Rat LD50 • >5000 mg/kg; Skin-Rabbit LD50 • >5000 mg/kg; Tumorigen / Carcinogen: Skin-Mouse • 389 g/kg 78 Week(s)-Intermittent; Tumorigenic:Equivocal tumorigenic agent by RTECS criteria; Skin and Appendages:Other:Tumors; Tumorigenic:Tumors at site of application		
Acetic acid, vinyl ester, polymer (< 11%)	9003- 20-7	Acute Toxicity: Ingestion/Oral-Rat LD50 • >25 g/kg		

GHS Properties	Classification
Germ Cell Mutagenicity	OSHA HCS 2012 • No data available
Carcinogenicity	OSHA HCS 2012 • No data available
Respiratory sensitization	OSHA HCS 2012 • No data available
STOT-RE	OSHA HCS 2012 • No data available
STOT-SE	OSHA HCS 2012 • No data available
Toxicity for Reproduction	OSHA HCS 2012 • No data available
Aspiration Hazard	OSHA HCS 2012 • No data available
Skin sensitization	OSHA HCS 2012 • No data available
Serious eye damage/Irritation	OSHA HCS 2012 • No data available
Skin corrosion/Irritation	OSHA HCS 2012 • No data available
Acute toxicity	OSHA HCS 2012 • No data available

Potential Health Effects

Inhalation

Acute (Immediate)

• Exposure to dust may cause irritation.

Chronic (Delayed)

• Fiber glass wool is a possible cancer hazard. Fiber glass wool has caused cancer in animals but has not produced cancer by inhalation in humans. Use of these products has not been shown to cause cancer in humans.

Skin

Acute (Immediate)

May cause irritation.

Chronic (Delayed)

No data available

Eye

Acute (Immediate)

Contact with the eyes may cause irritation due to the abrasive action of the dust. Not
expected to cause prolonged or significant eye irritation. Material is dusty and may
scratch the surface of the eye.

Chronic (Delayed)

No data available

Ingestion

Acute (Immediate)

Unlikely. Contact physician if unusual reaction is noted.

Chronic (Delayed) Carcinogenic Effects

- No data available
- This product contains glass wool insulation fibers. Following a thorough review of all the medical-scientific data available at a meeting in October 2001, the IARC panel lowered the classification for glass wool insulation fibers from a Group 2B classification ("possibly carcinogenic to humans") to a Group 3 classification ("not classifiable as to carcinogenicity to humans"). According to IARC, there is "no evidence of increased risks of lung cancer or of mesothelioma from occupational exposures during manufacturing of these materials, and inadequate evidence overall of any cancer risk." This product contains petroleum asphalt. Asphalt fumes arise from hot asphalt. Asphalt fumes (CAS # 8052-42-4): In 1985/87, IARC (International Agency for Research on Cancer) concluded the following: (a) Bitumens are not classifiable as to their carcinogenicity to humans (Group 3). (b) Extracts of steam- and air-refined bitumens are possibly carcinogenic to humans (Group 2B). IARC found that evidence for carcinogenicity from animal studies was: inadequate for undiluted air-refined bitumens; limited for steam-refined and cracking residue bitumens; sufficient for extracts of steam-refined and air-refined bitumen. IARC found that human evidence for carcinogenicity of asphalt fumes was inadequate. Studies of roofers indicated an excess of cancers; however, IARC concluded that, since roofers may be exposed also to coal-tar pitches and other materials, "the excess cancer risk cannot be attributed specifically to bitumens." In 1994, a published review of 20 epidemiology studies of asphalt workers and roofers agreed with IARC, that current human evidence is inadequate for the carcinogenicity of asphalt fumes in humans. Trace amounts of polynuclear aromatic hydrocarbons (PAHs) may be present in some asphalts and can be released upon excessive heating, which results in thermal cracking of the asphalt compounds. Some of these PAHs have been identified as having the potential to induce carcinogenic and reproductive health effects. The oxidized asphalt contained in our finished product is a solid form and therefore poses no similar exposure to the heated liquid form during roofing which resulted in IARC classification for this material.

Carcinogenic Effects				
	CAS	IARC	NTP	
Petroleum asphalt, oxidized	64742-93-4	Group 2A-Probable Carcinogen	Not Listed	
Glass, oxide, chemicals as Glass wool fiber	NDA	Not Listed	Reasonably Anticipated to be Human Carcinogen	

Other information

Following a thorough review of all of the medical-scientific data available at a meeting
in October 2001, the IARC panel lowered the classification for glass wool insulation
fibers from a Group 2B classification ("possibly carcinogenic to humans") to a Group 3
classification ("not classifiable as to carcinogenicity to humans"). According to IARC,
there is "no evidence of increased risks of lung cancer or of mesothelioma...from
occupational exposures during the manufacture of these materials, and inadequate
evidence overall of any cancer risk."

Key to abbreviations

LD = Lethal Dose

TC = Toxic Concentration

Section 12 - Ecological Information

Toxicity

No data available

Persistence and degradability

 Binder-coated fiber glass is hydrophobic, therefore, no adverse environmental effects would be expected if this product were accidentally released in the water or soil. No harm to fish or wildlife would be caused by this product.

Bioaccumulative potential

· No data available

Mobility in Soil

Binder-coated fiber glass is hydrophobic, therefore, no adverse environmental effects would be expected if this product were accidentally released in the water or soil. No harm to fish or wildlife would be caused by this product.

Other adverse effects

· No studies have been found.

Other Information

 This product is not manufactured with, nor does it contain any Class I Ozone depleting chemicals as defined by EPA in Title VI of the Clean Air Act Amendments of 1990 40 CFR Part 82, Protection of Stratospheric Ozone. This product is not classified as a hazardous air pollutant in Title III Clean Air Act of 1990. Certain Teed's residential fiber glass insulation batts meet GREENGUARD Emission Standards.CertainTeed's certification confirms compliance with GREENGUARD Emission Standards, which are basedon criteria used by the State of Washington, the U.S. Environmental Protection Agency (EPA), OSHA and the World Health Organization for total particulate and Volatile Organic Compounds (VOC) emissions, including formaldehyde. Additionally, CertainTeed's residential fiber glass insulation products meet the following emission criteria: California Section CA1350 material specification for schools and offices; OSHA Purchase Specification; State of Washington; EPA; and Proposed State of California. CertainTeed's residential fiber glass insulations also meet the EPA Recovered Material Guideline for recycled content.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

 Dispose of waste material in an approved landfill in accordance with federal, state, and local regulations. If you are unsure of the regulations, contact your Public Health Department, or the local office of the Environmental Protection Agency (EPA). See Section 7 for Handling Procedures; see Section 8 for Personal Protective Equipment recommendations.

Packaging waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class(es)	Packing group	Environmental hazards
DOT	Not Applicable	Not Regulated	Not Applicable	Not Applicable	NDA
TDG	Not Applicable	Not Regulated	Not Applicable	Not Applicable	NDA

Special precautions for user • None specified.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

· No data available

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Hazard Classifications • None

Preparation Date: 22/June/2012 Format: GHS Language: English (US) Revision Date: 27/April/2016 Page 8 of 13

		State Right To Know
Component	CAS	PA
Acetic acid ethenyl ester, polymer with ethene	24937-78-8	No
Acetic acid, vinyl ester, polymer	9003-20-7	No
Glass, oxide, chemicals	65997-17-3	No
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	No
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent- refiningand/or hydrotreatment)	64742-65-0	No
Petroleum asphalt, oxidized	64742-93-4	No

	Inventory					
Component	CAS	Canada DSL	Canada NDSL	TSCA		
Acetic acid ethenyl ester, polymer with ethene	24937-78-8	Yes	No	Yes		
Acetic acid, vinyl ester, polymer	9003-20-7	Yes	No	Yes		
Glass, oxide, chemicals	65997-17-3	Yes	No	Yes		
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	Yes	No	Yes		
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent- refiningand/or hydrotreatment)	64742-65-0	Yes	No	Yes		
Petroleum asphalt, oxidized	64742-93-4	Yes	No	Yes		

Canada

ı	2	h	^	r
L	_a	IJ	u	•

Canada - WHMIS - Classifications of Substances	
Petroleum asphalt, oxidized	64742-93-4 Not Listed
Acetic acid ethenyl ester, polymer with ethene	24937-78-8 Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7 Not Listed
Acetic acid, vinyl ester, polymer	9003-20-7 Not Listed

Not Listed	
Not Listed	
Not Listed	
Not Listed	
Not Listed	
Not Listed	
Not Listed	
	Not Listed

Petroleum asphalt, oxidized	64742-93-4	Not Listed
Acetic acid ethenyl ester, polymer with ethene	24937-78-8	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	Not Listed
Acetic acid, vinyl ester, polymer	9003-20-7	Not Listed
Glass, oxide, chemicals	65997-17-3	Not Listed
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-	64742-65-0	Not Listed
refiningand/or hydrotreatment)	04742 00 0	Not Elsted
U.S CERCLA/SARA - Radionuclides and Their Reportable Quantities	64740.00.4	Not Listed
Petroleum asphalt, oxidized	64742-93-4	Not Listed
Acetic acid ethenyl ester, polymer with ethene Acetic acid ethenyl ester, polymer with ethene	24937-78-8	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	Not Listed
Acetic acid, vinyl ester, polymer	9003-20-7	Not Listed
Glass, oxide, chemicals	65997-17-3	Not Listed
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs		
Petroleum asphalt, oxidized	64742-93-4	Not Listed
Acetic acid ethenyl ester, polymer with ethene	24937-78-8	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	Not Listed
Acetic acid, vinyl ester, polymer	9003-20-7	Not Listed
Glass, oxide, chemicals	65997-17-3	Not Listed
 Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment) 	64742-65-0	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs	64742-93-4	Not Listed
Petroleum asphalt, oxidized		
Acetic acid ethenyl ester, polymer with ethene All udretreeted began perefficie petrology additional distillate (highly refined)	24937-78-8	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	Not Listed
Acetic acid, vinyl ester, polymer Class syids shamisels	9003-20-7	Not Listed Not Listed
Glass, oxide, chemicals Minaral ail, patralayer distillator, as heart dayloyed because are fining (acycles as heart).	65997-17-3	Not Listed
 Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment) 	64742-65-0	Not Listed
H.O. OFPOLATOARA Ocation 040. Engineiro Remontino		
U.S CERCLA/SARA - Section 313 - Emission Reporting	64740.00.4	Not Listed
Petroleum asphalt, oxidized	64742-93-4	Not Listed Not Listed
Acetic acid ethenyl ester, polymer with ethene All udretreeted began perefficie petrology additional distillate (highly refined)	24937-78-8 64742-54-7	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)		
Acetic acid, vinyl ester, polymer	9003-20-7	Not Listed
Glass, oxide, chemicals Minaral ail, patralayer distillator, as heart daylored has a reffinic (access solvent).	65997-17-3	Not Listed
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-refiningand/or hydrotreatment)	64742-65-0	Not Listed
U.S CERCLA/SARA - Section 313 - PBT Chemical Listing		
Petroleum asphalt, oxidized	64742-93-4	Not Listed
Acetic acid ethenyl ester, polymer with ethene	24937-78-8	Not Listed
Hydrotreated heavy paraffinic petroleum distillate (highly refined)	64742-54-7	Not Listed
Acetic acid, vinyl ester, polymer	9003-20-7	Not Listed
Glass, oxide, chemicals	65997-17-3	Not Listed
Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-	04740.05.0	
refiningand/or hydrotreatment)	64742-65-0	Not Listed

United States - California

Environment U.S. - California - Proposition 65 - Carcinogens List 64742-93-4 Not Listed · Petroleum asphalt, oxidized Not Listed Acetic acid ethenyl ester, polymer with ethene 24937-78-8 Hydrotreated heavy paraffinic petroleum distillate (highly refined) 64742-54-7 Not Listed · Acetic acid, vinyl ester, polymer 9003-20-7 Not Listed · Glass, oxide, chemicals 65997-17-3 Not Listed · Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-64742-65-0 Not Listed refiningand/or hydrotreatment) U.S. - California - Proposition 65 - Developmental Toxicity 64742-93-4 Not Listed · Petroleum asphalt, oxidized · Acetic acid ethenyl ester, polymer with ethene 24937-78-8 Not Listed Hydrotreated heavy paraffinic petroleum distillate (highly refined) 64742-54-7 Not Listed · Acetic acid, vinyl ester, polymer 9003-20-7 Not Listed · Glass, oxide, chemicals 65997-17-3 Not Listed · Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-64742-65-0 Not Listed refiningand/or hydrotreatment) U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL) · Petroleum asphalt, oxidized 64742-93-4 Not Listed · Acetic acid ethenyl ester, polymer with ethene 24937-78-8 Not Listed Hydrotreated heavy paraffinic petroleum distillate (highly refined) 64742-54-7 Not Listed · Acetic acid, vinyl ester, polymer 9003-20-7 Not Listed · Glass, oxide, chemicals 65997-17-3 Not Listed Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-64742-65-0 Not Listed refiningand/or hydrotreatment) U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL) 64742-93-4 Not Listed · Petroleum asphalt, oxidized Not Listed · Acetic acid ethenyl ester, polymer with ethene 24937-78-8 Hydrotreated heavy paraffinic petroleum distillate (highly refined) 64742-54-7 Not Listed · Acetic acid, vinyl ester, polymer Not Listed 9003-20-7 · Glass, oxide, chemicals 65997-17-3 Not Listed · Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-Not Listed 64742-65-0 refiningand/or hydrotreatment) U.S. - California - Proposition 65 - Reproductive Toxicity - Female 64742-93-4 Not Listed Petroleum asphalt, oxidized · Acetic acid ethenyl ester, polymer with ethene 24937-78-8 Not Listed Hydrotreated heavy paraffinic petroleum distillate (highly refined) 64742-54-7 Not Listed · Acetic acid, vinyl ester, polymer 9003-20-7 Not Listed · Glass, oxide, chemicals 65997-17-3 Not Listed · Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-64742-65-0 Not Listed refiningand/or hydrotreatment) U.S. - California - Proposition 65 - Reproductive Toxicity - Male Not Listed Petroleum asphalt, oxidized 64742-93-4 · Acetic acid ethenyl ester, polymer with ethene 24937-78-8 Not Listed Hydrotreated heavy paraffinic petroleum distillate (highly refined) 64742-54-7 Not Listed · Acetic acid, vinyl ester, polymer 9003-20-7 Not Listed · Glass, oxide, chemicals 65997-17-3 Not Listed · Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic (severe solvent-64742-65-0 Not Listed refiningand/or hydrotreatment)

United States - Pennsylvania

64742-93-4	Not Listed
24937-78-8	Not Listed
64742-54-7	Not Listed
9003-20-7	Not Listed
65997-17-3	Not Listed
64742-65-0	Not Listed
64742-93-4	Not Listed
24937-78-8	Not Listed
64742-54-7	Not Listed
9003-20-7	Not Listed
65997-17-3	Not Listed
64742-65-0	Not Listed
	24937-78-8 64742-54-7 9003-20-7 65997-17-3 64742-65-0 64742-93-4 24937-78-8 64742-54-7 9003-20-7 65997-17-3

Section 16 - Other Information

Revision Date Preparation Date Other Information

27/April/201622/June/2012

Disclaimer/Statement of

 For reference to the acronyms/definitions used in this SDS please visit www.certainteed.com.

Disclaimer/Statement o Liability

Reasonable care has been taken in the preparation of this information, but the supplier
gives no warranty of merchantability or of fitness for a particular purpose. Any product
purchased is sold on the assumption the purchaser will make his own tests to
determine the quality and suitability of the product. Supplier expressly disclaims any
and all liability for incidental and/or consequential property damage arising out of the
use of this product. No information provided shall be deemed to be a recommendation
to use any product in conflict with any existing patent rights. Read the Safety Data
Sheet before handling product.

Key to abbreviations NDA = No Data Available