

Non-directional, sound-absorbing and sound blocking utilitarian panel with exceptional value.

FEATURES AND BENEFITS

- Non-directional fissured pattern
- Three-dimensional face scoring available in 3 geometric designs with Customline options
- Environmental Product Declaration (EPD) available for this product
- Available in (Protectone) version suited for fire assemblies
- Health Product Declaration (HPD) available for this product

ATTRIBUTES



LR 0.83



EPD
AVAILABLE



HPD
AVAILABLE



EMISSION
COMPLIANT
CERTIFIED



RECYCLED
CONTENT
33-44%

LEED® v4

RECYCLED CONTENT				
CLASS A PROTECTONE®	33%		44%	
	Pre: 23%	Post: 3%	Pre: 42%	Post: 2%
✓	MR: PBT Source Reduction (Healthcare)			
✓	EQ: Low-Emitting Materials			
✓	EQ: Daylight			
✓	MR: Material Ingredients (HPDs)			
✓	MR: Sourcing Raw Materials			
✓	MR: Environmental Product Declarations (EPDs)			
✓	MR: Construction and Demolition Waste Management Planning			

LEED® is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS




EPD AVAILABLE




HPD AVAILABLE


SUSPENSION SYSTEM OPTIONS




Trim
15/16 Grid



Reveal
Beveled
15/16 Grid



Narrow Reveal
Corner Bevel
9/16 Grid




Narrow Reveal
Beveled
9/16 Grid
(Customline)


CUSTOMLINE SCORING OPTIONS



24 x 48
(BQCL-224 / PBQCL-224)




24 x 48
(BQCL-448)




24 x 48
(BQCL-812)


BAROQUE

	Format	Dimensions (in.)
TRIM		
	BET-157	Panels 24 x 24 x 5/8
	PBT-157	Panels 24 x 24 x 5/8
	BET-197	Panels 24 x 48 x 5/8
	PBT-197	Panels 24 x 48 x 5/8
	BET-2067	Panels 20 x 60 x 5/8

NRC	CAC	Recycled Content	UL Fire-Rated	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet
0.55	33	33%	—	16	64	45	20
0.55	35	44%	Yes*	16	64	70	20
0.55	35	33%	—	8	64	45	20
0.55	40	44%	Yes*	8	64	70	20
0.55	35	33%	—	8	67	52	20


	Format	Dimensions (in.)
REVEAL		
	BET-154	Panels 24 x 24 x 5/8
	PBT-154	Panels 24 x 24 x 5/8
	BET-194	Panels 24 x 48 x 5/8

0.55	33	33%	—	16	64	45	20
0.55	35	44%	Yes*	16	64	70	20
0.55	35	33%	—	8	64	45	20

	Format	Dimensions (in.)
NARROW REVEAL		
	BET-150	Panels 24 x 24 x 5/8


0.55	33	33%	—	16	64	46	20
------	----	-----	---	----	----	----	----

BAROQUE METRIC


	Format	Dimensions (mm)
METRIC TRIM		
	BET-2067M	Panels 500 x 1500 x 15

NRC	CAC	Recycled Content	UL Fire-Rated	Pieces/carton	Sq. m/carton	Lbs./carton	Cartons/pallet
0.55	35	33%	—	8	6	52	20

BAROQUE CUSTOMLINE

	Format	Dimensions (in.)
REVEAL		
	BQCL-224	Panels 24 x 48 x 3/4
	BQCL-448	Panels 24 x 48 x 3/4
	BQCL-812	Panels 24 x 48 x 3/4
	PBQCL-224	Panels 24 x 48 x 3/4

NRC	CAC	Recycled Content	UL Fire-Rated	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet
0.55	35	33%	—	8	64	55	16
0.50	35	33%	—	8	64	55	16
0.50	35	33%	—	8	64	55	16
0.50	40	44%	Yes*	8	64	75	16

	Format	Dimensions (in.)
NARROW REVEAL		
	BQCLN-224	Panels 24 x 48 x 3/4
	BQCLN-448	Panels 24 x 48 x 3/4
	BQCLN-812	Panels 24 x 48 x 3/4

0.55	35	33%	—	8	64	55	16
0.50	35	33%	—	8	64	55	16
0.50	35	33%	—	8	64	55	16

* Protectone®: A fire-resistive ceiling when used in applicable UL/ULC assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column.

PHYSICAL DATA

MATERIAL

Mineral Fiber

ASTM E1264 CLASSIFICATION

Type III, Form 2, Pattern C D - Baroque

Type III, Form 2, Pattern C D K - Customline

FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

BAROQUE CUSTOMLINE WARRANTY

10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/ceilings.

BAROQUE WARRANTY

1-year Limited Warranty