

Blowing Machine Comparison

| Machine Works Feature | <i>Volu-Matic V</i> | <i>Volu-Matic III</i> | <i>Volu-Matic SE</i> | <i>Volu-Matic MS</i> | <i>Multi-Matic</i> |
|---------------------------------|---------------------|-----------------------|----------------------|----------------------|--------------------|
| Positive Displacement Blower | Std | Std | Std | Std | Std |
| 4-Speed Transmission | Std | Std | Std | N/A | N/A |
| Material Control Slide | Std | Std | Std | Std | Std |
| Self-Aligning Bearings | Std | Std | Std | Std | Std |
| Heavy Duty Gearboxes | Std | Std | N/A | N/A | Std |
| Heavy Duty Electric Clutches | Std | Std | N/A | N/A | N/A |
| Automatic Back Flow Check Valve | Std | Std | Std | Std | Std |
| Electrical Overload Protection | Std | Std | Std | Std | Std |
| Mechanical Overload Protection | Std | Std | Std | N/A | Std |
| Automatic Pressure Relief Valve | Std | Std | N/A | N/A | N/A |
| Quick Change Seal System | Opt | Opt | N/A | N/A | N/A |
| Integrated Safety Features | Std | Std | Std | Std | Std |
| Adjustable Drive Belts | Std | Std | Std | Std | Std |
| Expended Hopper | Std | Opt | Opt | N/A | Std |
| Built-In Water Pump | Std | Opt | N/A | N/A | * |
| Integrated Vacuum System | Std | N/A | N/A | N/A | Std |
| Fully Hydraulic Drive System | N/A | N/A | N/A | N/A | Std |
| Wired Remote Control | Std | Std | Std | Std | Std |
| Wireless Remote Control | Opt | Opt | Opt | Opt | Opt |
| Power Sources | | | | | |
| PTO Driven | Std | Opt | Opt | N/A | Std |
| Engine Driven | N/A | Opt | Opt | Std | N/A |
| Electric | N/A | Opt | N/A | N/A | N/A |

Blowing Machine Comparison

| Machine Works Feature | <i>Volu-Matic V</i> | <i>Volu-Matic III</i> | <i>Volu-Matic SE</i> | <i>Volu-Matic MS</i> | <i>Multi-Matic</i> |
|----------------------------|---------------------|-----------------------|----------------------|----------------------|--------------------|
| Physical Dimensions | | | | | |
| Height - Inches | 88 | 74 | 69 | 62 | 95 |
| Width | 80 | 75 | 72 | 60 | 84.5 |
| Depth | 88.5 | 56.5 | 48 | 47 | 80 |
| Weight - lbs | 2,500 | 2,000 | 1,300 | 850 | 3,100 |
| Open Blow Output (lbs/min) | | | | | |
| Fiberglass | 25-35 | 25-35 | 25-35 | 11-15 | N/A |
| Rockwool | 35-55 | 35-55 | 35-55 | 16-22 | N/A |
| Cellulose | 70-80 | 70-80 | 70-80 | 20-30 | 14-20** |
| Applications | | | | | |
| Open Blow | Yes | Yes | Yes | Yes | N/A |
| Side Wall Spray | Yes | Yes | No | No | Yes |
| Dense Pack / Cavity Fill | Yes | Yes | Yes | Yes | Yes |

Std - Standard feature

Opt - Optional Feature

N/A - Feature not available on this model

* Water pump is an integral part of the Multi-Tank water system required for this model

** Machine specifically designed for cellulose Side Wall Spray and Dense Pack / Cavity Fill applications