

PERFORMA®

Sereno™ Fine Fissured
VOC Compliant



LOW
VOC

\$\$\$



LEED® v4

- MR: Environmental Product Declarations (EPDs)
- MR: Sourcing Raw Materials
- MR: Material Ingredients (HPDs)
- IEQ: Daylight
- IEQ: Low-Emitting Materials
- IEQ: Prereq. Min. Acoustic Performance (Schools)
- IEQ: Acoustic Performance
- MR: PBT Source Reduction (Healthcare)
- IEQ: Interior Lighting
- EA: Prereq. Min. Energy Performance
- EA: Optimize Energy Performance
- Recycled Content
Pre: **70%** | Post: **0%**

TOOLS

Visit CertainTeed.com/Ceilings
Download HPDs and EPDs
LEED® Information / BIM Objects
3-Part Specs / Data Pages



Carbon Footprint Reduction
Rapidly Renewable Resource Content
Recycled Content



EPD Available



HPD Available

FEATURES & BENEFITS

- Superior acoustical combination provides high in-room sound absorption with room-to-room sound blocking capabilities for privacy
- Cuts quickly and cleanly with minimal dust for cost-efficient installation
- Attractive 100% non-directional fissured pattern to aid in quick installation
- Complies with LEED® v4 for Schools classroom acoustics prerequisite
- Meets ANSI S12.60 classroom acoustic guidelines
- Third-party verified Environmental Product Declaration (EPD) available
- Health Product Declaration (HPD) available

APPLICATIONS

- Universities
- Public Schools
- Healthcare Spaces
- Open Plan Offices
- Corridors
- Areas with HVAC Noise Concerns
- Libraries/Media Centers
- Computer Rooms
- Other Commercial Buildings / Space Applications

AVAILABLE EDGE DETAILS



Trim
15/16 Grid



Reveal Beveled
15/16 Grid



Narrow Reveal Corner Bevel
9/16 Grid



Narrow Reveal Corner Bevel
9/16 Grid Bolt Slot



Narrow Reveal Corner Bevel
9/16 Grid Tier Drop



Sereno™ Fine Fissured (SFF-457 HNRC/HCAC)

ATTRIBUTES

DIMENSIONS (INCHES)	EDGE DETAIL	 NRC	 CAC	 EPD AVAILABLE	 HPD AVAILABLE	 SAG RESISTANT	 MOLD RESISTANT	 LR	 WASHABLE	 WASHABLE WITH SANITIZING CHEMICALS	 FIRE CLASS (ASTM E1264)	 EMISSION COMPLIANT	 RECYCLED CONTENT
---------------------	-------------	---	---	---	---	---	--	--	---	--	---	--	--

SERENO™ FINE FISSURED

SFF-457 HNRC/HCAC	24 x 24 x 3/4	Trim	0.75	40	Yes	Yes	Yes	BioShield	0.83	—	—	Class A	Certified	70%
SFF-454 HNRC/HCAC	24 x 24 x 3/4	Reveal	0.70	40	Yes	Yes	Yes	BioShield	0.83	—	—	Class A	Certified	70%
SFF-450 HNRC/HCAC	24 x 24 x 3/4	Narrow Reveal	0.75	38	Yes	Yes	Yes	BioShield	0.83	—	—	Class A	Certified	70%
SFF-497 HNRC/HCAC	24 x 48 x 3/4	Trim	0.75	42	Yes	Yes	Yes	BioShield	0.83	—	—	Class A	Certified	70%
SFF-494 HNRC/HCAC	24 x 48 x 3/4	Reveal	0.70	42	Yes	Yes	Yes	BioShield	0.83	—	—	Class A	Certified	70%
SFF-490 HNRC/HCAC	24 x 48 x 3/4	Narrow Reveal	0.75	40	Yes	Yes	Yes	BioShield	0.83	—	—	Class A	Certified	70%

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

PHYSICAL DATA

MATERIAL

Mineral Fiber

ASTM E1264 CLASSIFICATION

Type III, Form 1, Pattern C D

FIRE CLASS (ASTM E1264)

Tested according to ASTM E84 & CAN S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010.

MOLD/MILDEW RESISTANCE

BioShield® treatment included for added mold and mildew resistance.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY

10-year 104/90 Limited Warranty

Technical Support | certaineed.com/ceilings 800-233-8990

© 05/17 CertainTeed Corporation

CertainTeed
SAINT-GOBAIN
Ceilings