

ECOPHON® FOCUS™ A, E

Smooth
Fiberglass

Easily demountable smooth panel with glass tissue backing provides superior sound absorption.



APPLICATIONS


- Open Plan Offices
- Classrooms
- Conference Rooms
- Private Offices
- Healthcare
- Libraries
- Doctor's Offices / Patient Rooms
- Other Commercial Buildings / Space Applications



FEATURES AND BENEFITS

- Smooth panel offering superior sound absorption (0.90-0.95 NRC)
- Extremely low particle emissions
- Easy-to-clean Akutex™ FT surface in white finish has perfect light diffusion (+99%)
- Durable edges resist damage from handling
- Fully encapsulated with tissue backing for maximum performance
- Reveal edges painted; trim edges primed
- Available in 16 standard colors

SUSPENSION SYSTEM OPTIONS



LEED® v4	
RECYCLED CONTENT	71%
<input checked="" type="checkbox"/>	EA: Optimize Energy Performance
<input checked="" type="checkbox"/>	EA: Prereq. Min. Energy Performance
<input checked="" type="checkbox"/>	EQ: Interior Lighting
<input checked="" type="checkbox"/>	MR: PBT Source Reduction (Healthcare)
<input checked="" type="checkbox"/>	EQ: Acoustic Performance
<input checked="" type="checkbox"/>	EQ: Prereq. Min. Acoustic Performance (Schools)
<input checked="" type="checkbox"/>	EQ: Low-Emitting Materials
<input checked="" type="checkbox"/>	EQ: Daylight
<input type="checkbox"/>	MR: Material Ingredients (HPDs)
<input checked="" type="checkbox"/>	MR: Sourcing Raw Materials
<input checked="" type="checkbox"/>	MR: Environmental Product Declarations (EPDs)
<input checked="" type="checkbox"/>	MR: Construction and Demolition Waste Management Planning



EPD Available


ECOPHON® FOCUS™ A, E

Smooth
Fiberglass


All products in this line
feature these attributes:




FOCUS A

	Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
TRIM											
	NRC 95	3540 4607	Panels	24 x 24 x 3/4	0.95	21	71%	28	112	29	—
		3540 4608	Panels	24 x 48 x 3/4	0.95	21	71%	14	112	29	—
		3540 4609	Panels	48 x 48 x 3/4	0.95	21	71%	8	128	34	—
		3542 5067	Planks	24 x 60 x 3/4	0.95	21	71%	12	120	31	—
		3542 5068	Planks	24 x 72 x 3/4	0.95	21	71%	12	144	37	—
		3542 5069	Planks	24 x 96 x 3/4	0.95	21	71%	12	192	47	—

FOCUS E

	Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
REVEAL (E24)											
	NRC 90	3542 2263	Panels	24 x 24 x 3/4	0.90	23	71%	20	80	40	—
		3542 2264	Panels	24 x 48 x 3/4	0.90	23	71%	10	80	38	—
		3542 2265	Panels	48 x 48 x 3/4	0.90	23	71%	6	96	50	—
		3542 5070	Planks	24 x 60 x 3/4	0.90	23	71%	6	60	28	—
		3542 5071	Planks	24 x 72 x 3/4	0.90	23	71%	6	72	35	—
		3542 5073	Planks	24 x 96 x 3/4	0.90	23	71%	6	96	46	—


NARROW REVEAL (E15)

	NRC 90	3542 5929	Panels	24 x 24 x 3/4	0.90	23	71%	20	80	30	—
		3542 5932	Panels	24 x 48 x 3/4	0.90	23	71%	10	80	30	—
		3542 2287	Panels	48 x 48 x 3/4	0.90	23	71%	6	96	50	—
		3542 5103	Planks	24 x 60 x 3/4	0.90	23	71%	6	60	28	—
		3542 5104	Planks	24 x 72 x 3/4	0.90	23	71%	6	72	35	—
		3541 5816	Planks	24 x 96 x 3/4	0.90	23	71%	6	96	34	—

All Focus A, E products listed above are white. To order colors please contact your local Sales Representative.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

ACCESSORIES



FOCUS A & E ACCESSORIES	Product Name	Pieces/carton	Use
	2630 0691 Connect Edge Sealant White*	1	For re-sealing cut edges (typically 100-150 lf/container); 1 liter container

*Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative or call 800-233-8990.

ECOPHON® FOCUS™ A, E

Smooth
Fiberglass

ACCESSORIES

FOCUS E ACCESSORIES	Product Name	Pieces/carton	Use
	STBAR-2 CTC 2' Stabilizer Bar	40	For all 2x6, 2x8 reveal and narrow reveal applications; typically 1 pc./panel for 2x6, 2 pc./panel for 2x8 (not needed for trim panels)
	STBAR-4 CTC 4' Stabilizer Bar	40	For all 2x6, 2x8 reveal and narrow reveal applications; typically 1 pc./panel for 2x6, 2 pc./panel for 2x8 (not needed for trim panels)

PHYSICAL DATA

MATERIAL
Fiberglass

ASTM E1264 CLASSIFICATION
Type XII, Form 2, Pattern G

FIRE CLASS (ASTM E1264)
All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

VOC EMISSIONS
Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE
Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE
Wipe with a soft cloth or vacuum with brush attachment. Cleanable with mild detergent.

WARRANTY
10-year Ecophon® Warranty increases to 15 years when installed with CertainTeed Suspension Systems. Full warranty information can be found at certainteed.com/ceilings.



Customer Support | certainteed.com/ceilings | 800-233-8990

LEED® is a registered trademark of the U.S. Green Building Council. © 2/19 CertainTeed Corporation.