

PERFORMA®

Open Plan™



White



White Nubby



Black Nubby

FEATURES & BENEFITS

- Excellent sound absorption for speech privacy
- Higher R-Value can reduce energy costs
- Humidity resistant
- Foil backing for increased CAC available as an option
- Completely painted edge available as an option

APPLICATIONS

- Open Plan Office
- Theaters
- Classrooms
- Houses of Worship
- Libraries
- Other Commercial Buildings / Space Applications

AVAILABLE EDGE DETAILS



Trim
15/16 Grid



\$\$\$

LEED® v4

- MR: Environmental Product Declarations (EPDs)
- MR: Sourcing Raw Materials
- MR: Material Ingredients (HPDs)
- IEQ: Daylight
- IEQ: Low-Emitting Materials
- IEQ: Prereq. Min. Acoustic Performance (Schools)
- IEQ: Acoustic Performance
- MR: PBT Source Reduction (Healthcare)
- IEQ: Interior Lighting
- EA: Prereq. Min. Energy Performance
- EA: Optimize Energy Performance
- Recycled Content
Pre: **0%** | Post: **31-46%**

TOOLS

Visit CertainTeed.com/Ceilings
Download HPDs and EPDs
LEED® Information / BIM Objects
3-Part Specs / Data Pages












Recycled Content



Open Plan™ White Elite Perforated Trim (1492-ELTP-1)

ATTRIBUTES

	DIMENSIONS (INCHES)	EDGE DETAIL	 NRC	 CAC+	 SAG RESISTANT	 MOLD RESISTANT	 LR	 WASHABLE	 FIRE CLASS (ASTM E1264)	 EMISSION COMPLIANT	 RECYCLED CONTENT
WHITE NUBBY											
1440-NBY-1	24 x 48 x 1	Trim	0.95	25	Yes	Inherent	0.84	—	Class A	—	31%
1442-NBY-1	24 x 24 x 1	Trim	0.95	25	Yes	Inherent	0.84	—	Class A	—	31%
1444-NBY-1	48 x 48 x 1	Trim	0.95	25	Yes	Inherent	0.84	—	Class A	—	31%
1446-NBY-1	24 x 96 x 1	Trim	0.95	25	Yes	Inherent	0.84	—	Class A	—	31%
1460-NBY-1	24 x 48 x 1-1/2	Trim	1.00	26	Yes	Inherent	0.84	—	Class A	—	36%
1462-NBY-1	24 x 24 x 1-1/2	Trim	1.00	26	Yes	Inherent	0.84	—	Class A	—	36%
1466-NBY-1	24 x 96 x 1-1/2	Trim	1.00	26	Yes	Inherent	0.84	—	Class A	—	36%
1469-NBY-1	30 x 60 x 1-1/2	Trim	1.00	26	Yes	Inherent	0.84	—	Class A	—	36%
1470-NBY-1	60 x 60 x 1-1/2	Trim	1.00	26	Yes	Inherent	0.84	—	Class A	—	36%
BLACK NUBBY											
1440-NBY-5	24 x 48 x 1	Trim	0.95	25	Yes	Inherent	0.03	—	Class A	—	31%
1442-NBY-5	24 x 24 x 1	Trim	0.95	25	Yes	Inherent	0.03	—	Class A	—	31%
1444-NBY-5	48 x 48 x 1	Trim	0.95	25	Yes	Inherent	0.03	—	Class A	—	31%
1446-NBY-5	24 x 96 x 1	Trim	0.95	25	Yes	Inherent	0.03	—	Class A	—	31%
WHITE ELITE PERFORATED											
1490-ELTP-1	24 x 48 x 3	Trim	1.05	30	Yes	Inherent	0.82	—	Class A	—	46%
1492-ELTP-1	24 x 24 x 3	Trim	1.05	30	Yes	Inherent	0.82	—	Class A	—	46%
WHITE ELITE UNPERFORATED											
1490-ELT-1	24 x 48 x 3	Trim	0.95	26	Yes	Inherent	0.82	—	Class A	—	46%
1492-ELT-1	24 x 24 x 3	Trim	0.95	26	Yes	Inherent	0.82	—	Class A	—	46%

+CAC values with foil backing

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

PHYSICAL DATA

MATERIAL

Fiberglass

R-VALUE

3-inch offers 13.60 / 1.5-inch offers 6.50

ASTM E1264 CLASSIFICATION

White Elite Finish: Type XII, Form 1, Pattern C E (perforated), E (unperforated); Nubby Finishes: Type XII, Form 2, Pattern E

FIRE CLASS (ASTM E1264)

Tested according to ASTM E84 & CAN S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY

10-year 104/95 Limited Warranty