

## SUSPENSION SYSTEMS


### 15/16" Cleanroom Stab System



\$\$\$\$

#### TOOLS

Visit [CertainTeed.com/Ceilings](http://CertainTeed.com/Ceilings)  
Download Technical Brochures  
LEED® Information / BIM Objects  
3-Part Specs / Data Pages



#### MAIN RUNNER



Main Runner



Cross Tee



15/16" Wall Angle

#### CROSS TEE




The Cleanroom Stab System is designed for controlled environment rooms and provides a clean, particulate free, sealed ceiling system.


#### FEATURES & BENEFITS

- Tested as a component in clean room design to Class 3 (as defined by ISO Standard 14644-1)
- Combine with Aquarock, Ecophon Hygiene Advance A, Ecophon Hygiene Meditec A, Ecophon Hygiene Performance A, Ecophon Hygiene Protec A, Envirogard, Rx Symphony m, Rx Symphony f, Symphony f, Symphony m, Vinylrock, Vinylshield A, VinylShield C to achieve product-specific clean room performance
- Satisfies FGI Healthcare Guidelines for ceilings systems in semi-restricted spaces
- CertainTeed Classic Stab-style main runners and cross tees for fast and sturdy installation
- G60 hot-dipped galvanized body with closed-cell gasketed flanges and white aluminum capping (for superior corrosion resistance)
- Seismic compliant per ICC ESR-3336
- High recycled content - 3rd party certified

#### 15/16" WALL ANGLE




#### AVAILABLE EDGE DETAILS



Trim  
(Square)  
15/16 Grid

#### MAIN RUNNERS









## ATTRIBUTES

	DESCRIPTION	GRID FACE (INCHES)	DIMENSIONS (INCHES)	SLOT/ROUTE SPACING (INCHES)	STRUCTURAL CLASSIFICATION (ASTM C635)	SEISMIC DESIGN CATEGORY	RECYCLED CONTENT TOTAL	RECYCLED CONTENT PRE	RECYCLED CONTENT POST	PIECES PER CARTON	FEET PER CARTON
<b>15/16" CLEANROOM STAB SYSTEM</b>											
<b>CRS12-12-20 WHT</b>	Main Runner	15/16	144 x 1-1/2 x 15/16	6 O.C.	HD	A-F	55%	24%	31%	20	240
<b>CRS2-12-12 WHT</b>	Cross Tee	15/16	24 x 1-1/2 x 15/16	—	—	—	55%	24%	31%	60	120
<b>CRS4-12-12 WHT</b>	Cross Tee	15/16	48 x 1-1/2 x 15/16	12 O.C.	—	—	55%	24%	31%	60	240
<b>CRS4-12-20 WHT</b>	Cross Tee	15/16	48 x 1-1/2 x 15/16	12 O.C.	HD	—	54%	24%	30%	60	240
<b>CRWA15-15</b>	Wall Angle	15/16	144 x 15/16 x 15/16	—	—	—	88%	19%	69%	40	480

## ACCESSORIES

	ITEM NUMBER	DESCRIPTION	DIMENSIONS L' X W' X H' (MM)
	AHD	Adjustable Hold Down Clip	1-1/8 x 1/2 x 1-11/16 (29 x 13 x 43)
	2630 0172	Connect Hygiene Clip 20	1-31/32 x 1-37/64 x 1-13/16 (50 x 40 x 46)
	CTSPC	Seismic Perimeter Clip	3-1/16 x 2-1/4 x 1-1/16 (78 x 58 x 27)
	CTSTJ	Seismic Transition Joint Clip	3-1/2 x 3-1/2 x 1-3/16 (89 x 89 x 31)

## PHYSICAL DATA

**Material** — Hot dipped galvanized steel (G60)

**Face Dimension** — 15/16"

**Cross Tee/Main Runner Interface** — Stepped-end/Override

**Duty Classification** — Heavy-duty or Intermediate duty

**Surface Finish** — Painted Aluminum Cap

**Profile Height** — 1-1/2"

**End Detail** — Main Runner: Integral Stab  
Cross Tee: Staked-on Stab Clip

**Seismic Rating** — Cat. A, B, C, D, E, F

**Gasket Type** — Closed-Cell Foam (gasket tape must be removed prior to installation)

### ICC EVALUATION SERVICE, INC., REPORT COMPLIANCE

Suspension systems manufactured by CertainTeed Ceilings have been reviewed and are approved by listing in ICC-ES Evaluation Report ESR-3336. CertainTeed Ceilings suspension systems have been reviewed and are approved by listing in L.A. Research Report number 25978. Evaluation Reports are subject to reexamination, revision and possible cancellation. Refer to [CertainTeed.com/Ceilings](http://CertainTeed.com/Ceilings) for current reports.