



Whether you're a home owner, contractor, builder or architect looking for ways to keep the noise out, or you're a home theater enthusiast or sound engineering professional trying to keep the sound in, Green Glue has the solution to noise-proof your life.

For more information and Green Glue's technical data, please visit www.CertainTeed.com/GreenGlue
1-800-233-8990

We're happy to help you **noiseproof your life.**



Caulkings and Sealants	44XU
Surface Burning Characteristics	
Green Glue Noiseproofing Compound Applied to Inorganic Reinforced Cement Board	
Flame Spread	10
Smoke Developed	5
Tested as applied in three 3/8 in. beads 5 in. OC, Covering 6.3% of the exposed test sample area.	



Adhesives	44XU
Listed in accordance with CAN/ULC-S102	
Flame Spread	25
Smoke Developed	5
Green Glue tested as applied in three 11.1 mm diameter beads, 127 mm OC covering 7.4% of the exposed test sample area.	

A GLOBAL LEADER

Founded in 1665 to manufacture glass for the Hall of Mirrors at the Palace of Versailles, Saint-Gobain is a world leader in construction markets, developing a new generation of building products to help meet the global challenges of energy efficiency and sustainability. Our vision is to offer a wide range of solutions and services to make buildings more energy efficient, while enhancing comfort and quality of life.

Saint-Gobain, parent company of CertainTeed and Green Glue, is a global manufacturer and distributor of building products, high-performance materials, glass, and containers. Based in Paris, France, Saint-Gobain has operations in 64 countries with over 190,000 employees. In North America, the company has headquarters in Valley Forge, Pennsylvania, with over 330 locations and approximately 19,000 employees across the U.S. and Canada. www.saint-gobain-northamerica.com

A SAINT-GOBAIN COMPANY

GREEN GLUE
noiseproof your life

1 Sealants Park • Granville, NY 12832
www.greengluecompany.com

©07/11 Green Glue Company.
 Printed in the U.S.A. on recycled paper.
 CTG-1220/3M/07-2011

GREEN GLUE
noiseproof your life



Distributed by

CertainTeed
SAINT-GOBAIN

GREEN GLUE

noiseproof your life

Noiseproofing Compound



Use between two sheets of drywall for walls and ceilings or plywood for subfloors to significantly reduce the amount of sound transferring from one room to another.

Green Glue Noiseproofing Compound works by remaining tacky and never drying out or becoming rigid like conventional adhesives.

- Available in 28 oz. tubes (cases of 12)
- Recommended coverage is 2 tubes per 4' x 8' panel of drywall or plywood

Noiseproofing Sealant

Use to seal gaps between walls and ceilings and floors, as well as spaces around electrical boxes, light fixtures, or additional potential sound leaks.

Green Glue Noiseproofing Sealant is specially formulated to never dry out and crack. It can be mudded and painted over 48 hours after application.

- Available in 28 oz. tubes (cases of 12)
- One tube covers 40 linear feet using a 3/8" bead



Because it outperforms the competition.

Sound Isolation Excellence

Greatly reduces noise between rooms when used in walls and ceilings

Eliminates up to 90% of sound transmission

Outperforms other soundproofing solutions – verified by 3rd party testing

Best acoustic solution for renovation or new construction



Because it's easy to use.

Easy to Use

Installing Green Glue is fast and simple

Extremely low viscosity – dispenses easily using a standard 32 oz. quart size caulk gun

No specific application pattern necessary

View product installation videos at www.youtube.com/GreenGlueCompany



Distributed by
CertainTeed
SAINT-GOBAIN

Because it's cost-effective.

Cost Effective

Faster installation equals less time commitment for homeowners and lower labor costs for contractors

Use only what you need – no more, no less, no waste

Cost-effective solution with most reliable results



Because it's safe.

Safe for You and the Environment

No formaldehyde emissions detected – meets the requirements of CA Section 01350

Mold Resistant per ASTM D 3273



GREEN GLUE NOISEPROOFING IS AS EASY AS 1-2-3!



1 Cut the tip, attach the nozzle and Green Glue is ready to dispense using any standard quart-size caulk gun.



2 Apply Green Glue beads evenly over the entire back of the second layer of gypsum or subflooring. Leave 3 inches on the edge for handling. **No troweling required.**



3 Install the second layer of gypsum or subflooring within 15 minutes, using proper screws and screw spacing.

For installation details, visit www.CertainTeed.com/GreenGlue Remember to get your CertainTeed drywall.