

CertainTeed

Vapor Prime

Vapor Barrier



- Class II vapor barrier
- Meets ASTM E96 and E96-16
- Seals the wall surface with a perm rating of less than 1.0 @ 2mils
- VOC compliant
- Non-breathing latex primer sealer
- For use on interior walls and ceilings

CertainTeed Vapor Prime is a vapor barrier coating designed for use on interior walls. Vapor Prime is a non-breathing latex primer which seals the wall with a perm rating of less than 1.0 in one coat. CertainTeed Vapor Prime is a low VOC product and is compatible with any waterborne latex paint coating applied for the topcoat.

Product Data

CERTAINTEED CODE:	UPC CODE:	COLOR:	PACKAGE SIZE:	PACKAGE TYPE:
408186	800805156113	White	5 US Gal. / 18.9L	Pail

COVERAGE:

Apply at 320 square feet per gallon yielding 5 wet mils.

APPLICATION:

Apply product at can consistency. No thinning is necessary. Brush, roll, or spray application.

DRY TIME:

Vapor Prime is dry to the touch in 1 hour and ready for recoat in 4 - 6 hours at 70°F and 50% relative humidity.

CLEANUP:

Wipe up drips and spills immediately with a wet cloth. Clean tools with soap and water.

Distributed by:

CertainTeed
SAINT-GOBAIN

CertainTeed Corporation

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM

20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 certainteed.com

© 05-2013 CertainTeed Gypsum, Inc. Rev 10-2018 CTG-4091