



# QuietPutty™ Acoustical Putty



---

**Please Check**

QuietPutty 380

---

**Submittal Approvals**

**Job Name:**

---

**Contractor/Engineer:**

**Date:**

---

**Description**

Acoustical putty for residential and commercial construction. QuietPutty is a fire-rated, mouldable putty designed to maintain the performance of acoustically rated walls with penetrations such as electrical outlets, HVAC ducts, and water hookups.

QuietPutty is conveniently sold in 178 mm (7") square pads for easy application onto most common outlet boxes. Each package contains ten individually wrapped QuietPutty pads.

---

**Benefits**

- One hour fire-rated to UL 1479
- Maintains high STC values
- Easy to use - requires no special tools and is applied manually
- Adheres to most construction materials for a high integrity seal
- Material is noncorrosive to metal and plastics
- Provides a draft and cold smoke seal in the installed condition

---

**Storage and Handling**

1. Service temperature limits: -17.8° C to 37.8° C (0° F to 100° F)
2. Shelf life: One year in sealed container
3. Clean up: Wash with soap and water

---

Over >>>

---

**Limitations**

1. QuietPutty is designed strictly for interior use.
  2. Design all wall penetrations per the fire resistance requirements of your provincial or local fire code. QuietPutty is to be used as an addition to such a design.
- 

**Product & Test Data**

QuietPutty is lab tested and non-toxic.

<b>Approx. Weight per unit</b>	170.1 g (6oz) / Pad
<b>Approx. Density per unit</b>	28.4 g/16.4cm <sup>3</sup> (1oz / in <sup>3</sup> )
<b>Drying time</b>	Non-skinning, remains permanently soft.
<b>Thickness</b>	3 mm (1/8 in)
<b>Color</b>	Blue/green
<b>Odor</b>	no odour
<b>Unit Size</b>	10 pads per box
<b>Size</b>	178 mm x 178 mm (7 in x 7 in) pad
<b>STC-rated</b>	47-63 (ASTM E90)
<b>Fire-rated</b>	One hour to UL 1479

**Additional Information**

This document is intended as a product submittal only. For complete information regarding QuietPutty Brand modable putty, please refer to QuietPutty data sheet, application notes and MSDS.

**Trademarks**

©2002-2008 Serious Materials, Inc. All rights reserved. QuietRock, QuietWood, QuietSeal, QuietGlue, QuietCoat, QuietTile, QuietPutty and QuietFoam are registered trademarks of Serious Materials, Inc.

**Note**

Products described here may not be available in all geographic markets. Consult your Quiet Solution sales office or representative for information.

**Notice**

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

**Safety First**

Follow good safety and industrial hygiene practices during handling and installing all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or usage. Product safety information: (800) 797-8159. KEEP OUT OF REACH OF CHILDREN.