

CertainTeed

Marco® Spark-Perf®

Drywall Joint Tape

Product Data and Submittal

Product Description

Marco® Spark-Perf® Drywall Joint Tape is a paper tape designed for use with joint compound to reinforce gypsum board joints and corners prior to painting, texturing or wallpapering.

Features and Benefits

- Tape is manufactured from a special fibred paper with added tensile strength to help prevent tearing, wrinkling or stretching
- Joint tape is available in three styles: No Spark (no perforations), Spark-Perf or Slot perforations, which helps to prevent blistering
- Tape is roughened on both sides for superior bonding and holding power
- Tape has precision-matched centre crease for easy and accurate corner applications
- Designed for use with all quality joint and taping compounds available on the market today

Product Data

Material: Fibred Paper

Colour: White

Packaging: See chart on back.

Storage: Tape should always be stored in closed cartons at normal room temperatures in an enclosed dry area.

Environmental Limitations: When applying drywall joint tape, follow the printed recommendations of the compound manufacturer. Apply tape only within their recommended minimum and maximum temperature range. Adequate ventilation is required to avoid any excess moisture.

Technical References: For additional information on the application and finishing of Finishing Products please consult:

- ASTM C 475: Standard specification for Joint Compound and Joint Tape for Finishing Gypsum Board.
- ASTM C 840: Standard Specification for Application and Finishing of Gypsum Board.
- GA-214: Gypsum Association publication “Levels of Gypsum Board Finish.”
- GA-216: Gypsum Association publication “Recommended Specifications for the Application and Finishing of Gypsum Board.”

Working with the Product

Application

Designed to be used by both hand and automatic tool applications.

Install gypsum board by following the published Installation Guide. Follow the printed instructions on the joint compound container for mixing and use of compound prior to and during the tape application.

For hand taping, apply a first coat of joint compound over the joint with a four-inch knife. Press the joint tape firmly into the compound by pressing the knife over the tape. Squeeze out excess compound, making sure that there is enough joint compound under the tape to ensure a good bond. Allow each coat to dry thoroughly before applying the next coat. If the tape does lift along the edges after drying, simply cut out the affected area in the shape of a canoe before applying the next coat. If the tape lifts in the centre, tear out the affected area and re-tape. Apply a second and third coat, ensuring that all joints and fasteners are completely concealed by feathering each subsequent coat beyond the last. Sand between coats where necessary and finish until a smooth surface is achieved.

Continued on back

Job Name

Contractor

Date

Products Specified:

Submittal Approvals
(Stamps or Signatures)

CertainTeed
SAINT-GOBAIN

Once primed, the finished interior walls and ceilings can be painted, wallpapered or textured as desired. Follow all manufacturers' instructions.

Warranty

Since methods and condition of application such as temperature, humidity and over thinning are beyond our control, CertainTeed Gypsum, Inc. (CertainTeed) will not be responsible for the failure of

this Product when the Product is not used according to directions and specifications and accepted standards of procedure inherent in drywall application; or when reasonable allowance is not made by the user for adverse weather and job conditions. However, if this product proves to be defective, maximum liability shall be limited to replacement of the material only or refund of the purchase price.

This shall be the full limit whatsoever of CertainTeed's liability. All claims shall be submitted in writing to CertainTeed within thirty days from the date of discovery. Provincial or Federal laws may provide rights in addition to this warranty that cannot be modified or excluded.

2-1/16" Wide (52.38 mm)	Style	Rolls Per Carton	Weight Per Carton	Cartons Per Pallet	Pallet Weight
75' (23 m)	NO SPARK	20	9 lb (4.1 kg)	140	1,260 lb (574 kg)
250' (76 m)	NO SPARK	20	26 lb (11.8 kg)	72	1,872 lb (849.1 kg)
500' (153 m)	NO SPARK	10	26 lb (11.8 kg)	80	2,080 lb (943.3 kg)
75' (23 m)	SPARK	20	9 lb (4.1 kg)	140	1,260 lb (574 kg)
250' (76 m)	SPARK	20	26 lb (11.8 kg)	72	1,872 lb (849.1 kg)
500' (153 m)	SPARK	10	26 lb (11.8 kg)	80	2,080 lb (943.3 kg)
75' (23 m)	SLOT	20	9 lb (4.1 kg)	140	1,260 lb (574 kg)
250' (76 m)	SLOT	20	26 lb (11.8 kg)	72	1,872 lb (849.1 kg)
500' (153 m)	SLOT	10	26 lb (11.8 kg)	80	2,080 lb (943.3 kg)

Drywall Joint Tape is 2-1/16" (52.38 mm) wide and available in 75' (23 m), 250' (76 m) and 500' (153 m) lengths.



ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE • FOUNDATIONS
 GYPSUM • CEILINGS • INSULATION • PIPE

www.certainteed.com <http://blog.certainteed.com>

CertainTeed Corporation
 P.O. Box 860
 Valley Forge, PA 19482

Professional: 800-233-8990
 Consumer: 800-782-8777

© 6-2008 CertainTeed Gypsum, Inc. Rev 4-2012
 Printed in Canada on recycled paper. CTG-5001

