


Technical Data Sheet

CedarCrest® IR (Impact Resistant) Shingle
(Hip and Ridge Accessory)



PRODUCT DESCRIPTION

CedarCrest IR (Impact Resistant) is a self-sealing shingle of multiple-layered construction that combines enhanced thickness, algae resistance, and durability with flexibility and good looks. Available in 12" x 36" overall, with perforations for easy separation and yielding three 12" x 12" caps with an 8" exposure. Availability depends on sales region.



Color: Please refer to the product brochure or CertainTeed website for the colors available in your region. CedarCrest shingles are designed to blend with all of CertainTeed Landmark Series and Presidential Series shingles. CedarCrest accessory shingles will also blend closely with several competitive colors. Please review CertainTeed's CedarCrest Color Chart for specific recommendations. Available in Algae Resistant (AR) colors only.

Limitations: Use on hips and ridges of roofs only after application of primary roofing shingles to both intersecting roof decks. These shingles are designed to be used with CertainTeed's shingles that reference the use of CedarCrest or High Profile Shingles. Use CedarCrest product colors that complement the shingle colors applied to the main roof. Special hand-sealed application is required for 110-mph wind resistance. Contact CertainTeed's Technical Service Department at 800-345-1145 for details or refer to this information on the wrapper.

Product Composition: CedarCrest shingles are composed of a fiber glass mat base. Ceramic coated mineral granules are tightly embedded in specially refined, water-resistant asphalt. This is a three-piece shingle that must be separated into individual pieces, each 12" x 12", by folding along the perforated lines.

Applicable Standards:

ASTM D3018 Type I	CSA Standard A123.5
ASTM D3462	ICC-ES ESR-1389 and ESR-3537
ASTM E108 Class A Fire Resistance	Florida Product Approval # FL5444
UL 790 Class A Fire Resistance	UL 2218 Impact Resistance Class 3
ASTM D3161 Class F* Wind Resistance	

*Special hand-sealed application required (see manufacturer's installation instructions or contact CertainTeed's Technical Service Department at 1-800-345-1145 for details).

TECHNICAL DATA

Weight/Bundle (approx.):	53 lb.
Dimensions (overall):	12" x 36"
Separated into individual pieces:	12" x 12"
Weather Exposure:	8"
Coverage/bundle:	20 lin. ft.

INSTALLATION

Each bundle of CedarCrest shingles has detailed installation instructions including diagrams.

AVAILABILITY AND COST

Availability: For the names of local distributors and dealers, please write Architectural Support, 20 Moores Road, Malvern, PA 19355; or call (800) 233-8990.

Cost: Contact a local distributor or dealer for current price information.

MAINTENANCE

CedarCrest shingles do not require maintenance when installed according to manufacturer's application instructions. However, to protect the investment, any roof should be routinely inspected at least once a year. Older roofs should be looked at more frequently.

WARRANTY

This product has a limited warranty against manufacturing defects concurrent with the warranty of the field shingle with which it is installed.

TECHNICAL SERVICE

Complete technical support and assistance is available through CertainTeed's Technical Service Department at 1-800-345-1145, Territory Managers, and the fully staffed and equipped Research and Development facility in Malvern, PA.

FOR MORE INFORMATION

Sales Support Group: 800-233-8990

Web site: www.certainteed.com

CertainTeed Roofing
20 Moores Road
Malvern, PA 19355