

ECOPHON® AKUSTO™ WALL C SUPER G

Wall Panels
Fiberglass

Akusto Wall C Super G fiberglass wall panel features an impact resistant surface.



APPLICATIONS

- Classrooms
- Gymnasiums
- Multi-purpose Rooms
- Libraries
- Public Lobbies
- Other Commercial Buildings / Space Applications



White


Gray

Blue

FEATURES AND BENEFITS

- High impact resistance
- Use as a complement and/or alternative to acoustical ceiling panels for excellent acoustical performance within a space
- Moisture resistant
- Available in 3 standard colors

EDGE DETAILS



Kerfed Edge

LEED® v4

RECYCLED CONTENT 71%

<input type="checkbox"/>	EA: Optimize Energy Performance
<input type="checkbox"/>	EA: Prereq. Min. Energy Performance
<input type="checkbox"/>	EQ: Interior Lighting
<input checked="" type="checkbox"/>	MR: PBT Source Reduction (Healthcare)
<input checked="" type="checkbox"/>	EQ: Acoustic Performance
<input checked="" type="checkbox"/>	EQ: Prereq. Min. Acoustic Performance (Schools)
<input type="checkbox"/>	EQ: Daylight
<input type="checkbox"/>	MR: Material Ingredients (HPDs)
<input checked="" type="checkbox"/>	MR: Sourcing Raw Materials
<input checked="" type="checkbox"/>	MR: Environmental Product Declarations (EPDs)
<input checked="" type="checkbox"/>	MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

EPD®

EPD Available

ECOPHON® AKUSTO™ WALL C SUPER G

Wall Panels
Fiberglass

All products in this line feature these attributes:



MOLD RESISTANT INHERENT



LR 0.37-0.78*



WASHABLE




EPD AVAILABLE



RECYCLED CONTENT 71%

AKUSTO WALL C SUPER G

	Color	Dimensions mm (in.)	NRC	LR	Recycled Content	Pieces/carton	Sq. m (Ft.) / carton	Lbs. / carton		
WALL PANEL										
	NRC 95	3557 7729	White	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.78	71%	4	21.3 (≈ 70)	71
		3557 7028	Gray	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.38	71%	4	21.3 (≈ 70)	71
		3557 7027	Blue	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.37	71%	4	21.3 (≈ 70)	71

*Does not apply to gray.

PHYSICAL DATA

MATERIAL

Fiberglass

FIRE CLASS (ASTM E1264)

Tested according to ASTM E84 & CAN S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment. Washable with mild detergent

WARRANTY

10-year Ecophon Warranty. Full warranty information can be found at certainteed.com/ceilings.



CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM
20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 certainteed.com