

ECOPHON® FOCUS™ A, E

Smooth
Fiberglass

Easily demountable smooth panel with glass tissue backing provides superior sound absorption.



APPLICATIONS

- Open Plan Offices
- Classrooms
- Conference Rooms
- Private Offices
- Healthcare
- Libraries
- Doctor's Offices / Patient Rooms
- Other Commercial Buildings / Space Applications




Dark Diamond Silk Slate Silver Stone Cloudy Day Golden Field Highland Fog Moonlight Sky Morning Drizzle
Ocean Storm Pale Pearl Ruby Rock Silent Steam Summer Breeze Sunset Heat Volcanic Ash White

FEATURES AND BENEFITS

- Smooth panel offering superior sound absorption (0.90-0.95 NRC)
- Extremely low particle emissions
- Easy-to-clean Akutex™ FT surface in white finish has perfect light diffusion (+99%)
- Durable edges resist damage from handling
- Fully encapsulated with tissue backing for maximum performance
- Reveal edges painted; trim edges primed
- Available in 16 standard colors

SUSPENSION SYSTEM OPTIONS



Trim 15/16 Grid (A)

Reveal 15/16 Grid (E24)

Narrow Reveal 9/16 Grid (E15)

LEED® v4

RECYCLED CONTENT 71%

- ✓ EA: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Daylight
- MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

EPD®

EPD Available

ECOPHON® FOCUS™ A, E

Smooth
Fiberglass

All products in this line
feature these attributes:



FOCUS A

		Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet	
TRIM											
	NRC 95	3542 4607	Panels	24 x 24 x 3/4	0.95	21	71%	28	112	29	—
		3542 4608	Panels	24 x 48 x 3/4	0.95	21	71%	14	112	29	—
		3542 4609	Panels	48 x 48 x 3/4	0.95	21	71%	8	128	34	—
		3542 5067	Planks	24 x 60 x 3/4	0.95	21	71%	12	120	31	—
		3542 5068	Planks	24 x 72 x 3/4	0.95	21	71%	12	144	37	—
		3542 5069	Planks	24 x 96 x 3/4	0.95	21	71%	12	192	47	—

FOCUS E

		Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet	
REVEAL (E24)											
	NRC 90	3542 2263	Panels	24 x 24 x 3/4	0.90	23	71%	20	80	40	—
		3542 2264	Panels	24 x 48 x 3/4	0.90	23	71%	10	80	38	—
		3542 2265	Panels	48 x 48 x 3/4	0.90	23	71%	6	96	50	—
		3542 5070	Planks	24 x 60 x 3/4	0.90	23	71%	6	60	28	—
		3542 5071	Planks	24 x 72 x 3/4	0.90	23	71%	6	72	35	—
		3542 5073	Planks	24 x 96 x 3/4	0.90	23	71%	6	96	46	—

NARROW REVEAL (E15)

	NRC 90	3542 5929	Panels	24 x 24 x 3/4	0.90	23	71%	20	80	30	—
		3542 5932	Panels	24 x 48 x 3/4	0.90	23	71%	10	80	30	—
		3542 2287	Panels	48 x 48 x 3/4	0.90	23	71%	6	96	50	—
		3542 5103	Planks	24 x 60 x 3/4	0.90	23	71%	6	60	28	—
		3542 5104	Planks	24 x 72 x 3/4	0.90	23	71%	6	72	35	—
		3541 5816	Planks	24 x 96 x 3/4	0.90	23	71%	6	96	34	—

All Focus A, E products listed above are white. To order colors please contact your local Sales Representative.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

ACCESSORIES



FOCUS A & E ACCESSORIES	Product Name	Pieces/carton	Use
	2630 0691 Connect Edge Sealant White*	1	For re-sealing cut edges (typically 100-150 lf/container); 1 liter container

*Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative or call 800-233-8990.

ECOPHON® FOCUS™ A, E

Smooth
Fiberglass

ACCESSORIES

FOCUS ACCESSORIES	Product Name	Pieces/carton	Use
	STBAR-2 CTC 2' Stabilizer Bar	40	For all 2x6, 2x8 reveal and narrow reveal applications; typically 1 pc./panel for 2x6, 2 pc./panel for 2x8 (not needed for trim panels)
	STBAR-4 CTC 4' Stabilizer Bar	40	For all 2x6, 2x8 reveal and narrow reveal applications; typically 1 pc./panel for 2x6, 2 pc./panel for 2x8 (not needed for trim panels)

PHYSICAL DATA

MATERIAL
Fiberglass

ASTM E1264 CLASSIFICATION
Type XII, Form 2, Pattern G

FIRE CLASS (ASTM E1264)
All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

MOLD/MILDEW RESISTANCE
Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE
Wipe with a soft cloth or vacuum with brush attachment. Cleanable with mild detergent.

WARRANTY
10-year Ecophon® Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at [certainteed.com/ceilings](https://www.certainteed.com/ceilings).



CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM
20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 [certainteed.com](https://www.certainteed.com)

ECOPHON® FOCUS™ A, E

Smooth
Fiberglass

