

ECOPHON® FOCUS™ Ds

Smooth
Fiberglass

Fully concealed suspension system coupled with superior sound absorption in a wide selection of sizes and colors.



APPLICATIONS


- Public Lobbies
- Conference Rooms / Offices
- Galleries
- Healthcare
- Classrooms
- Other Commercial Buildings / Space Applications



FEATURES AND BENEFITS

- Fully concealed, easy downward access
- Monolithic surface simulates drywall finished appearance
- Focus Wing accessory available for finishing of cloud perimeter
- Easy-to-clean Akutex™ FT surface in white finish has perfect light diffusion (+99%)
- Fully encapsulated with tissue backing for maximum performance
- Painted, damage-resistant concealed edges
- Available in 16 standard colors

SUSPENSION SYSTEM OPTIONS



Fully-concealed
15/16 Grid

LEED® v4	
RECYCLED CONTENT	71%
<input checked="" type="checkbox"/>	EA: Optimize Energy Performance
<input checked="" type="checkbox"/>	EA: Prereq. Min. Energy Performance
<input checked="" type="checkbox"/>	EQ: Interior Lighting
<input checked="" type="checkbox"/>	MR: PBT Source Reduction (Healthcare)
<input checked="" type="checkbox"/>	EQ: Acoustic Performance
<input checked="" type="checkbox"/>	EQ: Prereq. Min. Acoustic Performance (Schools)
<input checked="" type="checkbox"/>	EQ: Daylight
<input type="checkbox"/>	MR: Material Ingredients (HPDs)
<input checked="" type="checkbox"/>	MR: Sourcing Raw Materials
<input checked="" type="checkbox"/>	MR: Environmental Product Declarations (EPDs)
<input checked="" type="checkbox"/>	MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

EPD®

EPD Available

All products in this line
feature these attributes:



FOCUS Ds

	Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
FULLY-CONCEALED											
	NRC 85	3542 1511	Panels	24 x 24 x 3/4	0.85	25	71%	20	80	44	n/a
		3542 1512	Panels	24 x 48 x 3/4	0.85	25	71%	10	80	44	n/a
		3542 1516	Panels	48 x 48 x 3/4	0.85	25	71%	6	96	50	n/a
		3542 1513	Planks	24 x 60 x 3/4	0.85	25	71%	6	60	33	n/a
		3542 1514	Planks	24 x 72 x 3/4	0.85	25	71%	6	72	45	n/a
		3542 1515	Planks	24 x 96 x 3/4	0.85	25	71%	6	96	50	n/a

All Focus Ds products listed above are white. To order colors please contact your local Sales Representative.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

ACCESSORIES











FOCUS Ds ACCESSORIES	Product Name	Pieces/carton	Use
	2630 0547 Connect Dg20 Support Clip	50	For support of any cut supporting edge on 3/4" Dg or Ds (typically 1 pc. every 12 - 18 inches)
	2630 0691 Connect Edge Sealant White*	1	For re-sealing cut edges (typically 100-150 lf/container); 1 liter container
	2630 0991 Connect Dg Cutting Tool	1	For rabbeting field-cut edges
	STBAR-2 CTC 2' Stabilizer Bar	40	For all 2x5, 2x6, 2x8 applications; typically 1 pc./panel for 2x5, 2x6, 2 pc./panel for 2x8
	STBAR-4 CTC 4' Stabilizer Bar	40	For all 2x6, 2x8 applications; typically 1 pc./panel for 2x6, 2 pc./panel for 2x8
	CS12-12-20 15/16" Classic Stab HD Main Runner		For use only with Connect Space Bar 0577
	2630 0577 Ecophon® Connect Space Bar	10	For use only with CTC HD CS12-12-20, spaced every 48" on center, max 24" away from the wall
	2630 0524 Connect Wall Bracket T-Profile	50	For main runner attachment to wall (typically 2/run of main runner)
	2630 0525 Connect Space Bar Wall Bracket	10	For attachment of space bar to wall (typically 2/run of space bar)
	2630 0553 Connect Space Bar Winch	200	For attachment of space bar to main runner (one pc. for each intersection)

*Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative or call 800-233-8990.

ECOPHON® FOCUS™ Ds

Smooth
Fiberglass

ACCESSORIES

FOCUS Ds ACCESSORIES (continued)		Product Name	Pieces/carton	Use
	2630 0381	Connect Edge Stiffener	12	Required for Focus™ Ds 4x4 systems (2 pc./panel)
	2631 1080	Connect Perimeter Tile Clip	100	For attaching and securing panels at the perimeter
	2630 0196	Connect Hold Down Clip Ds	100	For use as a hold down clip with Focus Dg and Focus Ds (typically 1 pc./sf for 2x2 and 0.65 pc./sf for 2x4)
FOCUS WING & WING ACCESSORIES		Product Name	Pieces/carton	Use
	3549 1060	Focus Wing DS Straight Kit	3	Perimeter treatment for clouds or peninsulas; straight 48 x 8 x 2 full-concealed panel
	3549 1061	Focus Wing DS External Corner Kit	1	Perimeter treatment for clouds or peninsulas; kit for external corners containing 56 x 8 x 2 panel with mitered corner
	3549 1062	Focus Wing DS Internal Corner Kit	1	Perimeter treatment for clouds or peninsulas; kit for internal corners containing 56 x 8 x 2 panel with mitered corner
	2630 0650	Connect Wing Distance	2	For connection of Wing to Wing (typically 1 pc./Wing intersection)
	2630 0666	Connect Hook	1	For connection between Wing Corner pieces (typically 1 pc./corner)
	2630 0197	Connect Wall Spring Spacer	24	For use when trim cutting panels at the perimeter
	2631 1040	Connect L-coupling	50	For use every time a field grid member intersects with the perimeter main runners

PHYSICAL DATA

MATERIAL
Fiberglass

ASTM E1264 CLASSIFICATION
Type XII, Form 2, Pattern G

FIRE CLASS (ASTM E1264)
All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

MOLD/MILDEW RESISTANCE
Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE
Wipe with a soft cloth or vacuum with brush attachment. Cleanable with mild detergent.

WARRANTY
10-year Ecophon Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/ceilings.



CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM
20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 certainteed.com

ECOPHON® FOCUS™ Ds

Smooth
Fiberglass

