



# LOW-SLOPE RESIDENTIAL SOLUTIONS

Self-Adhered, Torch or Hot-Mopped Application

Products shown:

- Steep Slope - Landmark® PRO Max Def Heather Blend
- Low Slope - Flintlastic® SA Heather Blend

**CertainTeed**  
SAINT-GOBAIN

# Low-Slope Membranes Manufactured with Colors that Complement the Most Popular Shingles and Tiles on the Market

Flintlastic membrane colors are true-blends to shingle colors, not just a single color granule. Now you can coordinate a low-slope roof to an adjacent shingle or tile roof with any low-slope application method using these Flintlastic membranes:



## Flintlastic SA Cap (Self-Adhered)

- Pair with Flintlastic SA NailBase for a 12-year warranty
- Pair with Flintlastic SA NailBase and Flintlastic SA PlyBase for a 15-year warranty<sup>1</sup>
- Pair with Flintlastic SA NailBase and Flintlastic SA MidPly for a 20-year warranty<sup>1</sup>
- Upgrade to **Flintlastic SA Cap FR** for increased fire<sup>2</sup> and impact resistance



## Flintlastic GTA (Torch)

- Pair with Glasbase™ Base Sheet or All Weather/Empire® Base Sheet for a 12-year warranty
- Pair with All Weather/Empire Base Sheet and Black Diamond® Base Sheet for a 15-year warranty<sup>1</sup>
- Pair with All Weather/Empire Base Sheet and Ultra Glass SA for a 20-year warranty<sup>1</sup>
- Upgrade to **Flintlastic GTA-FR** for increased fire<sup>2</sup> resistance



## Flintlastic GMS (Hot Asphalt or Cold Adhesive)

- Pair with Glasbase Base Sheet or All Weather/Empire Base Sheet for a 12-year warranty
- Pair with All Weather/Empire Base Sheet and Black Diamond Base Sheet for a 15-year warranty<sup>1</sup>
- Pair with All Weather/Empire Base Sheet and Ultra Glass SA for a 20-year warranty<sup>1</sup>
- Upgrade to **Flintlastic Premium FR-P** for increased fire<sup>2</sup> resistance

Product	Material	Reinforcement	Coverage	Weight	Thickness	ASTM	Rolls/Pallet
Flintlastic GTA	APP	Polyester	100 sq. ft.	103 lbs.	4.0 mm (160 mils)	D6222 Grade G, Type 1	20
Flintlastic GMS	SBS			93 lbs.	3.7 mm (145 mils)	D6164, Grade G, Type 1	
Flintlastic SA Cap	SBS			95 lbs.	4.0 mm (160 mils)	D6164, Grade G, Type 1, D7505, D1970	
Flintlastic SA Cap FR	SBS	Fiberglass		88 lbs.	3.2 mm (125 mils)	ASTM D6163, Grade G Type 1, D7530, UL2218 Class 4	

<sup>1</sup> Direct adhesion to wood, without the inclusion of the anchor sheet, is permitted; roof systems self-adhered to wood decks are limited to Asphalt Shingle Limited Warranties and Integrity Roof System Limited Warranties; Sure Start Plus 5-Star Warranties require the use of Flintlastic SA NailBase as an anchor sheet; direct adhesion to wood is not permitted by code in Miami-Dade County (check your local building code); at the end of the roofing membrane's life, roofing membranes directly adhered to wood roof decks will require replacement of the deck; self-adhering to wood plank decks constructed of resinous woods, such as pine, is prohibited

<sup>2</sup> Refer to your local building code for fire rating requirements; refer to [iq.ulprospector.com](http://iq.ulprospector.com), CertainTeed's Roof Systems TGFU.R11656 for CertainTeed roof system fire ratings

# Flintlastic® Complementary Colors For Steep Slope with Low-Slope Elements

Flintlastic SA	CertainTeed Landmark	CertainTeed Landmark PRO	GAF Timberline HD	GAF Natural Shadow	IKO Cambridge
Burnt Sienna	Burnt Sienna	Max Def Burnt Sienna	Hickory	Hickory	Dual Brown
Buff	—			N/A	
Colonial Slate*	**	***	Williamsburg Slate	N/A	Charcoal Grey, Harvard Slate
CoolStar	Mist White	N/A	White	Artic White	N/A
Heather Blend	Heather Blend	Max Def Heather Blend	Barkwood	N/A	Driftwood
Hunter Green	Hunter Green	Max Def Hunter Green	Hunter Green	N/A	N/A
Moiré Black	Moiré Black	Max Def Moiré Black	Charcoal	Charcoal	Dual Black
Mojave Tan	Mojave Tan	Max Def Mojave Tan	Driftwood	N/A	N/A
Red	Cottage Red	N/A	Patriot Red	N/A	Aged Redwood
Resawn Shake	Resawn Shake	Max Def Resawn Shake	Shakewood	Shakewood	Earthtone Cedar
Terra Cotta	Terra Cotta	N/A	N/A	N/A	N/A
Weathered Wood	Weathered Wood	Max Def Weathered Wood	Weathered Wood	Weathered Wood	Weathered Wood
White	Silver Birch	N/A	Fox Hollow Gray	N/A	Super White, Dual Grey

Flintlastic SA	OC Duration	OC Oakridge	TAMKO Heritage	Atlas Pinnacle	Malarkey Vista
Burnt Sienna	Brownwood	Brownwood	Rustic Slate	Pristine Hickory	Antique Brown
Buff	N/A		N/A		N/A
Colonial Slate*	Colonial Slate	Peppermill Gray	Virginia Slate, Oxford Grey	Coastal Granite	Storm Grey
CoolStar	Shasta White	Shasta White	N/A	Pristine Pearl	N/A
Heather Blend	Teak	Teak	Timberwood	Pristine Heather	Heather
Hunter Green	Chateau Green	Chateau Green	Rustic Evergreen	Pristine Green	Rainforest
Moiré Black	Onyx Black	Onyx Black	Rustic Black	Pristine Black	Midnight Black
Mojave Tan	Amber	Sand Castle	Rustic Cedar	Pristine Desert	N/A
Red	Terra Cotta	N/A	Rustic Redwood	Pristine Sunset	N/A
Resawn Shake	Desert Tan	Desert Tan, Aged Cedar	Natural Timber	Morning Harvest	Sienna Blend
Terra Cotta	N/A	N/A	Autumn Brown	Pristine Sienna	N/A
Weathered Wood	Driftwood	Driftwood	Weatherwood	Pristine Weathered Wood	Weathered Wood
White	Sierra Gray	Sierra Gray	Olde English Pewter	Pristine Oyster	Silverwood

\* Does not contain red granules

\*\* Colonial Slate, Pewter, Georgetown Gray and Driftwood

\*\*\* Max Def Colonial Slate, Max Def Pewter, Max Def Georgetown Gray and Max Def Driftwood

# Flintlastic® SA Complementary Colors for Steep Slope Projects with Low-Slope Elements

Available in thirteen colors designed and engineered to match our most popular shingle blends

Colors	Flintlastic GTA	Flintlastic SA Cap	Flintlastic GMS	Flintlastic SA Cap FR
Burnt Sienna	S	S		S
Buff		S		
Colonial Slate	S	S		S
CoolStar	S	S	S	S
Heather Blend	S	S		S
Hunter Green		S		
Moiré Black	S	S	S	S
Mojave Tan		S		
Red		S		
Resawn Shake	S	S	S	S
Terra Cotta		S		
Weathered Wood	S	S	S	S
White	S	S	S	S

S = Stock

**For more information on CertainTeed Commercial Roofing Products, go to [www.certainteed.com](http://www.certainteed.com).**

CertainTeed Flintlastic® roofing products are intended for use by professional roofing contractors only. It is the responsibility of the installer to follow all appropriate and required safety precautions in conjunction with the installation of any CertainTeed roofing product.

Meets or exceeds ASTM D6164 (SA MidPly and SA Cap), ASTM D6163 (SA Cap FR) and ASTM D4601 (SA NailBase and PlyBase).



UL 2218 Class 4 Impact Resistance - Certain systems are UL classified as to impact resistance as described in the UL Roofing Materials and Systems Directory.



ICC-ES ESR-1388



**CertainTeed**

CEILING • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM

20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 [certainteed.com](http://certainteed.com)

©1/21 CertainTeed, Printed in the USA, Code No. COMM-086