



# FLINTLASTIC® SA

## SELF-ADHERED MODIFIED BITUMEN ROOF SYSTEM

Flintlastic SA delivers the reliable protection of traditional modified bitumen roofing for a fraction of the labor, plus:

- **No kettle, fumes, or burn risk**
- **No torch or risk of fire**
- **Reduced training requirement**
- **No building occupant disturbance**
- **No mess or side lap bleed out**
- **Reduced insurance requirement**

### Meet the family

Select the Flintlastic SA base, interply (optional) and cap sheet combination that meets your building, performance and warranty needs:

#### **Flintlastic SA NailBase**

Nailable base sheet for plywood/OSB or lightweight insulating concrete

#### **Flintlastic SA PlyBase**

Self-adhered base ply or interply

#### **Flintlastic SA MidPly**

Premium self-adhered base ply or interply, for extended warranties

#### **Flintlastic SA Cap**

Workhorse cap sheet

#### **Flintlastic SA Cap FR\*\***

Fire and impact resistant cap sheet




\*\*UL 2218 Class 4 Impact Resistance - Certain systems are UL classified as to impact resistance as described in the UL Roofing Materials and Systems Directory.

**CertainTeed**  
SAINT-GOBAIN

# Aesthetic Selection

Flintlastic SA Cap is available in thirteen colors designed and engineered to match our most popular shingle blends:



## Don't forget the tools and accessories!

- 70 lb. roller, for field application
- FlintPrime® SA & FlintPrime Aerosol, primer for applicable substrates and metal details
- FlintBond® SBS-Modified Adhesive
  - Trowel Grade, for endlaps and details
  - Caulk Grade, for details



## Popular Systems

MF = Mechanically Fastened, SA = Self-Adhered

Warranty Duration	Insulation/Coverboard	Base	Cap (SA)
12 Years	Optional	SA NailBase (MF)	SA Cap/
15 Years	Optional	SA PlyBase <sup>1</sup> (SA)	SA Cap (FR)
20 Years	Optional	SA MidPly <sup>1</sup> (SA)	SA Cap CoolStar®/
25 Years	Double layer, 2nd layer adhered	SA MidPly (SA)	SA Cap (FR) CoolStar

<sup>1</sup>Wood deck? CertainTeed recommends the use of Flintlastic SA NailBase as a base sheet and SA PlyBase and SA MidPly as interplies, however, when self-adhering a base layer over wood decks, priming is required; self-adhering over wood decks is not permitted by code in Miami-Dade County; check your local building code; at the end of the roofing membrane's life, roofing membranes self-adhered over wood decks will require replacement of the deck; self-adhering to resinous wood, such as pine, is prohibited; roof systems with base sheets self-adhered directly to wood roof decks qualify for Integrity Roof System Limited Warranties only; Integrity Roof System NDL Limited Warranties and Sure Start™ Plus 5-STAR Warranties require the use of Flintlastic SA NailBase as a base sheet.



**CertainTeed**  
 CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM  
 20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 [certainteed.com](http://certainteed.com)