



## EXTERIOR CLADDING

There are numerous exterior claddings available today, from shingles to shakes to a multitude of siding alternatives. GlasRoc® Sheathing is an excellent choice for any of these applications. Simply install GlasRoc Sheathing and apply the preferred exterior cladding, per the manufacturer's recommendations. Depending on local building codes, a joint treatment, building felt, or building wrap may be necessary.

### REFERENCED STANDARDS

- ASTM C514: Specification for Nails for the Application of Gypsum Board
- ASTM C954: Specification for Steel Drill Screws for the Application of Gypsum Panel Products or Metal Plaster Bases to Steel Studs from 0.33" (0.84 mm) to 0.112" (2.84 mm) in Thickness
- ASTM C1002: Standard Specification for Steel Drill Screws for the Application of Gypsum Panel Products or Metal Plaster Bases
- ASTM C1177: Standard Specification for Glass Mat Gypsum Substrate for Use as Sheathing
- ASTM C1280: Standard Specification for Application of Gypsum Sheathing
- CAN/ULC-S102 (ASTM E84): Test Method for Surface Burning Characteristics of Building Materials
- ASTM E96: Test Methods for Water Vapour Transmission of Materials
- CAN/ULC-S101 (ASTM E119): Test Method for Fire Tests of Building Construction and Materials