

GYPTONE® ACOUSTICAL PANELS


Perforated
Gypsum

Unique gypsum panels with easy plenum access.



APPLICATIONS

- Stores
- Airports
- Offices
- Schools
- Atriums
- Corridors
- Other Commercial Buildings / Space Applications



LINE 4




POINT 11



QUATTRO 20



SIXTO 60




BASE 31


FEATURES AND BENEFITS

- Perforated, sound absorbent gypsum panel available in 4 unique patterns
- Fully finished white surface is capable of being post-painted to suit design
- Durable lay-in panel provides easy plenum access
- Proprietary Saint-Gobain formaldehyde scavenging performance (inherent to all Gypstone products)
- Health Product Declaration (HPD) available
- Environmental Product Declaration (EPD) Available

SUSPENSION SYSTEM OPTIONS



Trim
15/16 Grid



Narrow Reveal
Corner Bevel
9/16 Grid

LEED® v4

RECYCLED CONTENT 85%

<input type="checkbox"/>	EA: Optimize Energy Performance
<input type="checkbox"/>	EA: Prereq. Min. Energy Performance
<input checked="" type="checkbox"/>	EQ: Interior Lighting
<input checked="" type="checkbox"/>	MR: PBT Source Reduction (Healthcare)
<input checked="" type="checkbox"/>	EQ: Acoustic Performance
<input checked="" type="checkbox"/>	EQ: Prereq. Min. Acoustic Performance (Schools)
<input checked="" type="checkbox"/>	EQ: Low-Emitting Materials
<input type="checkbox"/>	EQ: Daylight
<input checked="" type="checkbox"/>	MR: Material Ingredients (HPDs)
<input checked="" type="checkbox"/>	MR: Sourcing Raw Materials
<input checked="" type="checkbox"/>	MR: Environmental Product Declarations (EPDs)
<input type="checkbox"/>	MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

EPD®

EPD Available



HPD Available



GYPTONE® ACOUSTICAL PANELS

Perforated
Gypsum

All products in this line
feature these attributes:





LINE 4™

	Format	Dimensions (in.)	NRC*	CAC*	LR	Hole Size (mm)	Perforated Area	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
TRIM														
	NRC 70	5200410258	Panels	24 x 24 x 1/2	0.70	35	0.70	6 x 95	17%	85%	6	24	39	32
NARROW REVEAL														
	NRC 70	5200410261	Panels	24 x 24 x 1/2	0.70	35	0.70	6 x 95	17%	85%	6	24	39	32



*NRC and CAC values when used with CertainTeed Sustainable™ Insulation in unfaced 3-1/2" (R-11) as an overlay above the installed panel
(Without insulation NRC=0.60, CAC=17)

POINT 11™

	Format	Dimensions (in.)	NRC*	CAC*	LR	Hole Size (mm)	Perforated Area	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
TRIM														
	NRC 80	5200410316	Panels	24 x 24 x 1/2	0.80	35	0.71	6.5	12%	85%	6	24	39	32
NARROW REVEAL														
	NRC 80	5200410320	Panels	24 x 24 x 1/2	0.80	35	0.71	6.5	12%	85%	6	24	39	32

*NRC and CAC values when used with CertainTeed Sustainable Insulation in unfaced 2-1/2" (R-8) as an overlay above the installed panel
(Without insulation overlay: NRC=0.60, CAC=17)

QUATTRO 20™

	Format	Dimensions (in.)	NRC*	CAC*	LR	Hole Size (mm)	Perforated Area	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
TRIM														
	NRC 75	5200410417	Panels	24 x 24 x 1/2	0.75	35	0.71	9	18%	85%	6	24	39	32
NARROW REVEAL														
	NRC 75	5200410422	Panels	24 x 24 x 1/2	0.75	35	0.71	9	18%	85%	6	24	39	32

*NRC and CAC values when used with CertainTeed Sustainable Insulation in unfaced 2-1/2" (R-8) as an overlay above the installed panel
(Without insulation overlay: NRC=0.65, CAC=17)

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

GYPTONE® ACOUSTICAL PANELS

Perforated
Gypsum

All products in this line
feature these attributes:



LR
0.71-0.82



EPD
AVAILABLE



HPD
AVAILABLE



EMISSION
COMPLIANT
CERTIFIED



RECYCLED
CONTENT
85%

SIXTO 60™		Format	Dimensions (in.)	NRC*	CAC*	LR	Hole Size (mm)	Perforated Area	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet	
TRIM														
	NRC 80	5200609848	Panels	24 x 24 x 1/2	0.80	35	0.71	11	17%	85%	6	24	39	16
NARROW REVEAL														
	NRC 80	5200609840	Panels	24 x 24 x 1/2	0.80	35	0.71	11	17%	85%	6	24	39	16

*NRC and CAC values when used with CertainTeed Sustainable Insulation in unfaced 2-1/2" (R-8) as an overlay above the installed panel
(Without insulation NRC=0.70, CAC=17)

BASE 31™		Format	Dimensions (in.)	NRC	CAC*	LR	Hole Size (mm)	Perforated Area	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet	
TRIM														
		5200410489	Panels	24 x 24 x 1/2	—	35	0.82	—	—	85%	6	24	44	32
NARROW REVEAL														
		5200410494	Panels	24 x 24 x 1/2	—	35	0.82	—	—	85%	6	24	44	32

*CAC values when used with CertainTeed Sustainable Insulation in unfaced 3-1/2" (R-11) as an overlay above the installed panel

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

PHYSICAL DATA

MATERIAL
Gypsum

ASTM E1264 CLASSIFICATION
Type XX, Pattern A G

FIRE CLASS (ASTM E1264)
All are Class A ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

VOC EMISSIONS
Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MAINTENANCE
Wipe with a soft cloth or vacuum with brush attachment. Painted surfaces can be cleaned with a damp cloth and mild detergent.



CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM
20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 certainteed.com

GYPTONE® ACOUSTICAL PANELS

Perforated
Gypsum

