

SUBMITTAL SHEET

HIGH PROFILE SERIES™

STRAIGHT BAFFLE

Project Name _____

Specification Section _____

Ceiling Type _____

SUBSTRATE

Extruded Aluminum

PROFILE

(Width x Height)

Beam

- 1-1/2" x 4-3/8"
- 1-1/2" x 6-3/8"
- 1-1/2" x 8-3/8"
- 2" x 4"
- 2" x 6"
- 2" x 8"
- 4" x 4"

Aero

- 1-5/8" x 6-3/8"

Sweep

- 1-3/4" x 6-3/8"

Open Beam

- 4" x 4"

Taper

- 1-1/2" x 8"

Crescent

- 4" x 6-3/8"

Other - contact manufacturer

- _____

* Length - minimum 4'-0", maximum 20'-0"

BEAM SPACING

- 6"
- 8"
- 12"
- Other _____

COLOR/FINISH

Beam Finish

- Cotton White - #0280
- Natural - #7163
- Other _____

* Veneer finishes (interior only) are profile-specific; please contact manufacturer for more information.

Hanger Bracket Finish

- Black
- White
- Painted to match plenum

END CAPS

- Yes
- No

GRAIN DIRECTION

(For Decorated or Veneer End Caps)

- Horizontal
- Vertical

SPLICES

- Yes
- No

EXPOSURE

- Interior
- Exterior* - Design Wind Pressure (required) _____ PSF

* Exterior applications are project-specific and must be reviewed and approved by manufacturer prior to quote.

Shop Drawings required on all High Profile Exterior projects.

To Contact Us:

5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.366.4327
fax: 770.806.0214
www.CertainTeed.com/Architectural

ARCHITECTURAL

CertainTeed
SAINT-GOBAIN

SUBMITTAL SHEET **HIGH PROFILE SERIES™ STRAIGHT BAFFLE**

PHYSICAL DATA

Substrate: Aluminum

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread: ≤ 25 , Smoke ≤ 50
- Wood veneer on metal: Flame spread: ≤ 25 , Smoke ≤ 55

Weight: Varies 2.0 - 4.0 lbs./sq.ft.

Wind load: Per Code

Recycled content: Minimum of 50%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81

For technical details, go to [CertainTeed.com/Architectural](https://www.CertainTeed.com/Architectural) • 800.366.4327