

SUBMITTAL SHEET

HEARTFELT®

Project Name _____

Specification Section _____

Ceiling Type _____

SUBSTRATE Felt: Non-woven PES fibers

PROFILE

HeartFelt Linear: 4OHL55 1-9/16" x 2-3/16" (40mm x 55mm)
 4OHL80 1-9/16" x 3-1/8" (40mm x 80mm)
 4OHL105 1-9/16" x 4-1/8" (40mm x 105mm)

HeartFelt Round: 4OHR64 1-9/16" x 2-1/2" (40mm x 64mm)

PANEL COLOR/FINISH

HeartFelt - Greys White - #7593F Dark Grey - #7598F
 Light Grey - #7596F Black - #7594F
 Medium Grey - #7597F

HeartFelt - Earth Tones Creme - #7575F Light Brown - #7576F
(4OHL55 only) Medium Brown - #7577F Dark Brown - #7578F
 Umber - #7579F

PANEL DEPTH Depth: 55mm, 64mm, 80mm, 105mm: _____

CARRIERS

Standard Carrier

- 60mm 2-3/8" o.c. module, 13/16" reveal
- 80mm 3-1/8" o.c. module, 1-9/16" reveal
- 100mm 3-15/16" o.c. module, 2-3/8" reveal

Carrier for HeartFelt - Levels

- Wave
- Choppy
- Step
- Scatter
- Custom* _____

* Custom carrier modulations are available upon request. HeartFelt Levels, 50mm (2"), 70mm (2-3/4"), and 90mm (3-1/2") spacings, as well additional configurations and spacings are available. An additional lead time will apply. Please contact your local sales representative for more information.

CARRIERS COLOR/FINISH

- Silver - #7178
- Painted Black - #1863
- Other: _____

EXPOSURE Interior Only

HeartFelt® is a registered trademark of Hunter Douglas, Inc. used with permission.

To Contact Us:
5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.366.4327
fax: 770.806.0214
www.certainteed.com/architectural

ARCHITECTURAL

CertainTeed
SAINT-GOBAIN

SOUND ABSORPTION (NRC) SUMMARY*

Panel Spacing	Open Area	Reveal	Acoustics
2-3/8" (60 mm)	33%	13/16"	NRC 0.60
3-1/8" (80 mm)	50%	1-9/16"	NRC 0.50
3-15/16" (100 mm)	59%	2-3/8"	NRC 0.45

* Acoustical tests performed in accordance with ASTM C423 and ASTM E795, in a type E400 mounting. Test reports available upon request.

PHYSICAL DATA

Substrate: Non-woven PES fibers

Warranty: 1 year limited

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A per ASTM E1264 & CAN/ULC S102

Weight: Varies

Wind load: N/A

Light reflectance (LR): Varies with color selected

Given the unique and special nature of our HeartFelt® ceiling product, steps should be taken (before and during installation, as well as over the lifetime of the ceiling) to avoid or minimize static and the accumulation of dust, lint, dirt or airborne particles on or around the felt. Manufacturer does not warrant against or take responsibility for any such static or accumulation.