

SUBMITTAL SHEET

LINEAR NUVOLA™

BOX 4

Project Name _____

Specification Section _____

Ceiling Type _____

SUBSTRATE: Aluminum

PROFILE Box 4

COLOR/FINISH Cotton White - #0280 Other # _____
 Natural - #7163

FILLER STRIP Box Flat Recessed Closure - Matte Black - #1883 Open Reveal
 Box Flat Recessed Closure - Cotton White - #0280

PERFORATION PATTERN #160 Non-Perforated

ACOUSTICAL BACKER Black Non-Woven
 Black Polywrapped Pad
 None

TRIM Edgeline (Available with longer lead times / Shop drawings required)
 End Caps
 Color/Finish # _____

EXPOSURE Interior Only

LINEAR NUVOLA ROUND

Quantity:	Description:	Item #:
_____	4' Round ○	LNK4RLINEARB4
_____	6' Round ○	LNK6RLINEARB4
_____	8' Round ○	LNK8RLINEARB4

LINEAR NUVOLA SQUARE

Quantity:	Description:	Item #:
_____	2' W x 2' L □	LNK22LINEARB4
_____	4' W x 4' L □	LNK44LINEARB4
_____	6' W x 6' L □	LNK66LINEARB4
_____	8' W x 8' L □	LNK88LINEARB4

LINEAR NUVOLA RECTANGLE

Quantity:	Description:	Item #:
_____	2' W x 4' L □	LNK24LINEARB4
_____	2' W x 6' L □	LNK26LINEARB4
_____	2' W x 8' L □	LNK28LINEARB4
_____	4' W x 2' L □	LNK42LINEARB4
_____	4' W x 6' L □	LNK46LINEARB4
_____	4' W x 8' L □	LNK48LINEARB4

LINEAR NUVOLA RECTANGLE (continued)

Quantity:	Description:	Item #:
_____	6' W x 2' L □	LNK62LINEARB4
_____	6' W x 4' L □	LNK64LINEARB4
_____	6' W x 8' L □	LNK68LINEARB4
_____	8' W x 2' L □	LNK82LINEARB4
_____	8' W x 4' L □	LNK84LINEARB4
_____	8' W x 6' L □	LNK86LINEARB4


To Contact Us:
 5015 Oakbrook Parkway, Suite 100
 Norcross, GA 30093
 phone: 800.366.4327
 fax: 770.806.0214
www.CertainTeed.com/Architectural

SUBMITTAL SHEET **LINEAR NUVOVA™ - BOX 4**

PERFORATIONS

Perforated panels improve acoustical performance as well as create aesthetic effects.

#160



Perforation diam: .060 in.
Open Area: 23%

PHYSICAL DATA

Substrate: Aluminum

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread: ≤ 25 , Smoke ≤ 50
- Film on metal: Flame spread: ≤ 25 , Smoke ≤ 50
- Wood veneer on metal: Flame spread: ≤ 25 , Smoke ≤ 55 (for interior applications)

Weight: Varies 0.5 - 0.75 lbs./sq.ft.

Wind load: N/A

Recycled content: Up to 92%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81

For technical details, go to [CertainTeed.com/Architectural](https://www.certainteed.com/Architectural) • 800.366.4327