

SUBMITTAL SHEET

MULTI-BOX

CONTINUOUS

Project Name _____

Specification Section _____

Ceiling Type _____

PATTERN

- | | | |
|----------------------------------|----------------------------------|---------------------------------------|
| <input type="checkbox"/> Alpha | <input type="checkbox"/> Foxtrot | <input type="checkbox"/> Other: _____ |
| <input type="checkbox"/> Bravo | <input type="checkbox"/> Golf | (Specify pattern and start point) |
| <input type="checkbox"/> Charlie | <input type="checkbox"/> Hotel | |
| <input type="checkbox"/> Delta | <input type="checkbox"/> India | |
| <input type="checkbox"/> Echo | <input type="checkbox"/> Juliet | |

COLOR/FINISH

- | | |
|---|--|
| <input type="checkbox"/> Cotton White - #0280 | <input type="checkbox"/> Other # _____ |
| <input type="checkbox"/> Natural - #7163 | |

FILLER STRIP

- | | |
|---|--------------------------------------|
| <input type="checkbox"/> Box Flat Recessed Closure - Matte Black - #1883 | <input type="checkbox"/> Open Reveal |
| <input type="checkbox"/> Box Flat Recessed Closure - Cotton White - #0280 | |
- * Filler Strip required for all Exterior applications.

PERFORATION PATTERN

- | | |
|---|--|
| Box 2 <input type="checkbox"/> Non-Perforated | Deep Box 2 <input type="checkbox"/> Non-Perforated <input type="checkbox"/> #160 |
| Box 4 <input type="checkbox"/> Non-Perforated <input type="checkbox"/> #160 | Deep Box 4 <input type="checkbox"/> Non-Perforated |
| Box 6 <input type="checkbox"/> Non-Perforated <input type="checkbox"/> #160 | Deep Box 6 <input type="checkbox"/> Non-Perforated |
| Box 8 <input type="checkbox"/> Non-Perforated <input type="checkbox"/> #160 | Deep Box 8 <input type="checkbox"/> Non-Perforated |

ACOUSTICAL BACKER

- | |
|--|
| <input type="checkbox"/> Black Non-Woven |
| <input type="checkbox"/> Black Polywrapped Pad |
| <input type="checkbox"/> None |
- * For use with interior perforated material only.

ACOUSTICAL RATING

_____ (NRC)

TRIM

- | | |
|--|---|
| <input type="checkbox"/> Wall Angle | <input type="checkbox"/> Edgeline (interior only) _____ |
| <input type="checkbox"/> Floating J-Trim | <input type="checkbox"/> End Caps |
- Color/Finish # _____

EXPOSURE

- | |
|---|
| <input type="checkbox"/> Interior |
| <input type="checkbox"/> Exterior - Design Wind Pressure (required) _____ PSF |

Shop Drawings required on all Multi-Box projects.

To Contact Us:

5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.366.4327
fax: 770.806.0214
www.CertainTeed.com/Architectural

ARCHITECTURAL


CertainTeed
SAINT-GOBAIN

SUBMITTAL SHEET **MUTI-BOX CONTINUOUS**

PERFORATIONS

Perforated panels improve acoustical performance as well as create aesthetic effects.

#160



Perforation diam: .060 in.

Open Area: 23%

(Box 4, 6, 8 and Deep Box 2 only)

SOUND ABSORPTION (NRC) SUMMARY*

Product	Acoustical Infill	NRC
Linear Multi-Box "Alpha" Pattern, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.75
Linear Multi-Box "Bravo" Pattern, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.65
Box 2, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.90
Box 4, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.75
Box 4, Perforated #160 (23% open area), open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.90
Box 4, Perforated #160 (23% open area), with Box Flat Closure Strip	Nonwoven	0.70
Box 4, Perforated #160 (23% open area), with Box Flat Closure Strip	1.5" - 1.5 pcf Polywrapped Fiberglass	0.85
Box 6, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.65
Box 6, Perforated #160 (23% open area), open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.90
Box 6, Perforated #160 (23% open area), with Box Flat Closure Strip	Nonwoven	0.70
Box 6, Perforated #160 (23% open area), with Box Flat Closure Strip	1.5" - 1.5 pcf Polywrapped Fiberglass	0.80
Box 8, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.50
Box 8, Perforated #160 (23% open area), open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.90
Box 8, Perforated #160 (23% open area), with Box Flat Closure Strip	Nonwoven	0.70
Box 8, Perforated #160 (23% open area), with Box Flat Closure Strip	1.5" - 1.5 pcf Polywrapped Fiberglass	0.85
Deep Box 2, Perforation #160 (23% Open Area), open reveal	2" Polywrapped acoustical pad	1.05
Deep Box 2, Perforation #160 (23% Open Area), with Box Flat Closure	2" Polywrapped acoustical pad	1.00
Deep Box 2, Perforation #160 (23% Open Area), with Box Flat Closure	Nonwoven Acoustic & 1" polywrapped acoustical pad	1.00
Deep Box 2, Perforation #160 (23% Open Area), with Box Flat Closure	1" Polywrapped acoustical pad	0.95
Deep Box 2, Perforation #160 (23% Open Area), open reveal	1" Polywrapped acoustical pad	0.95
Deep Box 2, Non-perforated, open reveal	2" Polywrapped acoustical pad	0.90
Deep Box 2, Perforation #160 (23% Open Area), with Box Flat Closure	Nonwoven Acoustic	0.80
Deep Box 2, Non-perforated, open reveal	1" Polywrapped acoustical pad	0.65
Deep Box 2, Perforation #160 (23% Open Area), open reveal	Nonwoven Acoustic	0.50

* Acoustical tests performed in accordance with ASTM C423 and ASTM E795, in a type E400 mounting. Test reports available upon request.

PHYSICAL DATA

Substrate: Aluminum

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50
- Film on metal: Flame spread: ≤ 25, Smoke ≤ 50
- Wood veneer on metal: Flame spread: ≤ 25, Smoke ≤ 55 (for interior applications)

Weight: Varies 0.5 - 1.0 lbs./sq.ft.

Wind load: Per code (for exterior applications)

Recycled content: Up to 92%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Varies with finish
- Cotton White: LR = 0.81

For technical details, go to CertainTeed.com/Architectural • 800.366.4327