OPEN CELL




Project: National Center for Aviation Training (NCAT), Wichita, KS; Open Cell

KEY FEATURES

- Two-directional plenum mask
- Patented sliding clip on factory-assembled panels allow install in matching runners
- Monolithic appearance without T-grid
- Waste reduction with factory fabricated dimensional material

- Downweight: reduce dead load with lightweight aluminum
- Easy plenum access downward accessible panels
- Compatible with industry standard lighting, HVAC, speaker, fire safety, and security services

TYPICAL ISOMETRICS



PHYSICAL DATA

Substrate: Aluminum Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50

Weight: Varies 0.5 – 1.25 lbs./sq.ft.

Wind load: N/A

Recycled content: Up to 92%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81

BIN

REVIT files available for BIM contributions, see website for details.

LEED V4 CREDITS

MR: Building Product Disclosure EQ: Low-Emitting Materials EQ: Indoor Air Quality Assessment

CERTIFICATIONS

GREENGUARD Gold Certified EPDs – available upon request

104 CTSpecialtyCeilings.com | 800.366.4327 | CTSpecialtyCeilings.com 105

CELL **OPEN CELL**

COLORS & FINISHES

A wide choice of colors and finishes are available and some carry a premium price over manufacturer's standard colors. Custom color matching is available upon request. Minimum quantities and lead times may apply. See website for the most up to date information and to order samples. Colors are for illustration purposes only.

STANDARD PAINT COLORS







CUSTOM COLORS

Premium custom colors.





106 CTSpecialtyCeilings.com | 800.366.4327 800.366.4327 | CTSpecialtyCeilings.com 107