

# SUBMITTAL SHEET

# FELT CEILINGS - OPEN CELL

Project Name \_\_\_\_\_

Specification Section \_\_\_\_\_

Ceiling Type \_\_\_\_\_

**SUBSTRATE**      PET Recycled Felt

---

**DIMENSIONS**       Open Cell

Height\*: 6" up to 24"  
Length: 1' up to 8' (nominal)  
Thickness: 3/8" (nominal)

*\* Additional heights available, Open Cell spacing varies according to height - contact your local sales rep*

---

**COLORS**

- |   |  |  |
|---|--|--|
| <input type="checkbox"/> Red - #3701    | <input type="checkbox"/> Sky - #3707       | <input type="checkbox"/> Pepper - #3713    |
| <input type="checkbox"/> Orange - #3702 | <input type="checkbox"/> Blue Jean - #3708 | <input type="checkbox"/> Charcoal - #3714  |
| <input type="checkbox"/> Gold - #3703   | <input type="checkbox"/> Wine - #3709      | <input type="checkbox"/> Black - #3715     |
| <input type="checkbox"/> Citrus - #3704 | <input type="checkbox"/> White - #3710     | <input type="checkbox"/> Oat - #3716       |
| <input type="checkbox"/> Pear - #3705   | <input type="checkbox"/> Alabaster - #3711 | <input type="checkbox"/> Violet - #3717    |
| <input type="checkbox"/> Green - #3706  | <input type="checkbox"/> Marble - #3712    | <input type="checkbox"/> Cranberry - #3718 |
- 

**BRACKET  
COLORS**

- Black  
 White  
 Natural
- 

**ATTACHMENT  
TYPE**

- Adjustable wire hanger/Direct hung  
 T-Grid System
- 

**EXPOSURE**

- Interior Only
- 

**To Contact Us:**

5015 Oakbrook Parkway, Suite 100  
Norcross, GA 30093  
phone: 800.366.4327  
fax: 770.806.0214  
[www.CertainTeed.com/Architectural](http://www.CertainTeed.com/Architectural)

ARCHITECTURAL

**CertainTeed**  
SAINT-GOBAIN

## ACOUSTICAL TEST RESULTS

Sound absorption of up to 1.12 Sabins/SF  
Baffle dimensions: 3/8" (nominal) thick x 10" height

## OPEN CELL

Spacing	Apparent NRC	Apparent SAA	Sabins/SF
12" o.c.	0.90	0.90	0.92
6" o.c.	1.10	1.10	1.12

Tests conducted in accordance with ASTM C423 and E795, with mounting type "A".

## PHYSICAL DATA

---

**Substrate:** PET Recycled Felt

**Warranty:** 1 year

**Seismic:** Felt Ceilings - Open Cell are suitable for installation in Seismic areas when installed in accordance with local code requirements.

**Fire rating:** Class A Fire Rated per ASTM E84

- Flame spread:  $\leq 25$ , Smoke  $\leq 250$

**Weight:** Varies

**Wind load:** N/A

**Recycled content:** 60% recycled content - 100% recyclable

**Light reflectance (LR):** Varies with color selected

Given the unique and special nature of our FELT ceiling product, steps should be taken (before and during installation, as well as over the lifetime of the ceiling) to avoid or minimize static and the accumulation of dust, lint, dirt or airborne particles on or around the felt. Manufacturer does not warrant against or take responsibility for any such static or accumulation.