

A humidity resistant fiberglass panel with excellent sound absorption that is available in a variety of finish textures and colors.




### APPLICATIONS

- Open Plan Office
- Theaters
- Classrooms
- Houses of Worship
- Libraries
- Other Commercial Buildings / Space Applications



White Nubby



Black Nubby




White Elite

### FEATURES AND BENEFITS

- Excellent sound absorption for speech privacy
- Higher R-Value can reduce energy costs
- Humidity resistant
- Completely painted edge available as an option
- Available in durable Nubby glass cloth or cost-effective Elite vinyl
- CAC foil backing for increased CAC available as an option

### SUSPENSION SYSTEM OPTIONS



Trim  
15/16 Grid

### LEED® v4

RECYCLED CONTENT

31% - 46%

<input type="checkbox"/>	EA: Optimize Energy Performance
<input type="checkbox"/>	EA: Prereq. Min. Energy Performance
<input type="checkbox"/>	EQ: Interior Lighting
<input checked="" type="checkbox"/>	MR: PBT Source Reduction (Healthcare)
<input checked="" type="checkbox"/>	EQ: Acoustic Performance
<input checked="" type="checkbox"/>	EQ: Prereq. Min. Acoustic Performance (Schools)
<input type="checkbox"/>	EQ: Low-Emitting Materials
<input checked="" type="checkbox"/>	EQ: Daylight
<input type="checkbox"/>	MR: Material Ingredients (HPDs)
<input checked="" type="checkbox"/>	MR: Sourcing Raw Materials
<input type="checkbox"/>	MR: Environmental Product Declarations (EPDs)
<input checked="" type="checkbox"/>	MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.


# OPEN PLAN™

Textured  
Fiberglass


All products in this line  
feature these attributes:



## WHITE NUBBY

	Format	Dimensions (in.)	NRC	CAC	LR	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
<b>TRIM</b>												
	NRC 100	1462-NBY-1	Panels	24 x 24 x 1-1/2	1.00	26	0.84	36%	16	64	34	14
		1460-NBY-1	Panels	24 x 48 x 1-1/2	1.00	26	0.84	36%	8	64	34	14
		1469-NBY-1	Panels	30 x 60 x 1-1/2	1.00	26	0.84	36%	8	100	52	14
		1470-NBY-1	Panels	60 x 60 x 1-1/2	1.00	26	0.84	36%	8	200	104	7
		1466-NBY-1	Planks	24 x 96 x 1-1/2	1.00	26	0.84	36%	8	128	67	10
NRC 95	1442-NBY-1	Panels	24 x 24 x 1	0.95	25	0.84	31%	24	96	34	14	
	1440-NBY-1	Panels	24 x 48 x 1	0.95	25	0.84	31%	12	96	34	14	
	1444-NBY-1	Panels	48 x 48 x 1	0.95	25	0.84	31%	12	192	67	7	
	1446-NBY-1	Planks	24 x 96 x 1	0.95	25	0.84	31%	12	192	67	10	

## BLACK NUBBY

	Format	Dimensions (in.)	NRC	CAC	LR	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
<b>TRIM</b>												
	NRC 95	1442-NBY-5	Panels	24 x 24 x 1	0.95	25	0.03	31%	24	96	34	14
		1440-NBY-5	Panels	24 x 48 x 1	0.95	25	0.03	31%	12	96	34	14
		1444-NBY-5	Panels	48 x 48 x 1	0.95	25	0.03	31%	12	192	67	7
		1446-NBY-5	Planks	24 x 96 x 1	0.95	25	0.03	31%	12	192	67	10

## WHITE ELITE PERFORATED

	Format	Dimensions (in.)	NRC	CAC	LR	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
<b>TRIM</b>												
	NRC 105	1492-ELTP-1	Panels	24 x 24 x 3	1.05	30	0.82	46%	4	32	32	14
		1490-ELTP-1	Panels	24 x 48 x 3	1.05	30	0.82	46%	4	32	32	14

## WHITE ELITE UNPERFORATED

	Format	Dimensions (in.)	NRC	CAC	LR	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
<b>TRIM</b>												
	NRC 95	1492-ELT-1	Panels	24 x 24 x 3	0.95	26	0.82	46%	8	32	32	14
		1490-ELT-1	Panels	24 x 48 x 3	0.95	26	0.82	46%	4	32	32	7

\* CAC foil-backing available at additional charge. Add an F to the end of the item number. Add one additional week to service level. Order product with a completely painted edge by contacting your local Sales Representative or calling 800-233-8990.

**CAN'T FIND A SIZE?** Contact your local Sales Representative or call 800-233-8990

## PHYSICAL DATA

**MATERIAL**  
Fiberglass

**R-VALUE**  
3-inch offers 13.60 / 1.5-inch offers 6.50

**ASTM E1264 CLASSIFICATION**  
White Elite Finish: Type XII, Form 1, Pattern C E (perforated), E (unperforated);  
Nubby Finishes: Type XII, Form 2, Pattern E

**FIRE CLASS (ASTM E1264)**  
All are Class A per ASTM E84 & CAN S102  
Flame Spread: 25 or less  
Smoke Developed: 50 or less

**MOLD/MILDEW RESISTANCE**  
Fiberglass substrate is inherently resistant to the growth of mold and mildew.

**MAINTENANCE**  
Wipe with a soft cloth or vacuum with brush attachment.

**WARRANTY**  
10-year 104/95 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at [certainteed.com/ceilings](http://certainteed.com/ceilings).



## CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM  
20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 [certainteed.com](http://certainteed.com)