

FLINTFAST® SIPLD FASTENERS

Product Information



Technical Data

Description: FlintFast Fasteners from CertainTeed are engineered to provide top quality performance with commercial roofing systems and designed to increase strength and improve application efficiency. SIPLD Fasteners are used in roofing applications for the attachment of nailboard (FlintBoard® ISO NB) and vented nailboard (FlintBoard® CV).

Uses: Light duty, #2 drill point fasteners for steel and wood deck applications. Available in lengths from 3" to 18".

Material: Case hardened and tempered carbon steel
Headstyle/Drive: Pancake head with T-30 internal drive
Head Diameter: 0.062"
Nominal Shank Diameter: 0.190"
Thread Length: 2.750"
Point: #2 (0.135" diameter)
Drill Point Coating: Epoxy e-coat (black)
Withdrawal Value in Wood*: 1067 lb./in.
*Specify Gravity: 0.50
Withdrawal Value in 22 ga. Steel: 510 lbf.
Approvals: Factory Mutual

Packaging

| Screw Length | Pieces per Pail |
|---------------------|------------------------|
| 3"-8" | 500 |
| 8-1/2" to 18" | 250 |

Two T-30 driver bits included in each pail.

For more information, contact CertainTeed Commercial Roofing Technical Services at 800-396-8134 x2.



ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE
GYPSUM • CEILINGS • INSULATION

www.certainteed.com <http://blog.certainteed.com>

CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482

Professional: 800-233-8990
Consumer: 800-782-8777