

WARRANTY DURATION MATRIX

Roll goods listed under Base, Interply or Cap columns and separated by a comma are options for system configurations within each respective warranty duration row; these are not intended to be installed together or additively.

SBS SYSTEMS WITH BASE SHEET ADHERED

Warranty Duration	NDL Warranty Fee (100 Sq Min)	Insulation/Coverboard	Base	Interply	Cap	Applicable Specs	Recover
12 years	\$4.00/Sq	Optional (coverboard required over polyisocyanurate if base is mopped) ¹	Any approved CertainTeed BUR or SBS Base Sheet ⁵	Flintlastic Ultra Poly SMS	Flood coat and gravel	SBS(G)-I-2-A, SBS(G)-C-A	SBS(G)-I-2-A Approved for Recover
12 years	\$4.00/Sq	Optional ¹		Optional		SBS-I-2-A, SBS-I-2-C, SBS-I-2-T	Approved
15 years	\$7.50/Sq	Optional ¹	Flintglas Ply 4	Optional	Any approved CertainTeed SBS Cap Sheet ⁵	SBS-I-2-A, SBS-I-2-C, SBS-I-2-T	Approved
20 years	\$12.50/Sq	Double layer, second layer adhered		Flintglas Ply 4		SBS-I-3-A, SBS-I-3-T	
20 years	\$12.50/Sq	Double layer, second layer adhered	Flintlastic Base 20 ³ , Flintlastic Base 20 T Black Diamond Base Sheet	Optional		SBS-I-2-A, SBS-I-2-C, SBS-I-2-T	Prior approval required by CertainTeed Commercial Roofing Technical Services Department
20 years	\$12.50/Sq	Optional ²	Flintlastic Ultra Poly SMS, Flintlastic Ultra Glass SA	Optional	Flintlastic GMS, Flintlastic FR-P, Flintlastic Premium FR-P, Flintlastic GTS-FR	SBS-C-2-A, SBS-I-2-A, SBS-I-2-T, SBS-C-2-T	
20 years	\$12.50/Sq	Optional ¹	Black Diamond Base Sheet	Optional	Flintlastic GTS-FR CoolStar, Flintlastic Premium FR-P CoolStar	SBS-I-2-A, SBS-I-2-C ⁴	
25 years	\$15.00/Sq	Double layer, second layer adhered	Flintlastic Ultra Poly SMS, Flintlastic Ultra Glass SA	Optional	Flintlastic Premium FR-P, Flintlastic GTS-FR	SBS-I-2-A, SBS-I-2-C, SBS-I-2-T	—
25 years	\$15.00/Sq	Double layer, second layer adhered	Black Diamond Base Sheet, Flintlastic Poly SMS	Flintlastic Poly SMS	Flintlastic Premium FR-P, Flintlastic GTS-FR	SBS-I-3-A, SBS-I-3-C, SBS-I-3-T	—

Note: Unless noted, prior approval required by CT Tech Services for recover.

1. If "Optional" Insulation/Coverboard is utilized, refer to "SBS-I-2-X"^{*}
2. If "Optional" Insulation/Coverboard is utilized, refer to "SBS-I-3-X"^{*}
3. CertainTeed's FlintBond[®] SBS Modified Adhesive must be utilized to obtain 20-year warranty duration.

^{*} Please see the Specification Nomenclature chart on the preceding page to determine the X values.

4. Not applicable for Black Diamond Base Sheet
5. Refer to applicable system specification for approved base and cap sheets.

WARRANTY DURATION MATRIX

Roll goods listed under Base, Interply or Cap columns and separated by a comma are options for system configurations within each respective warranty duration row; these are not intended to be installed together or additively.

SBS SYSTEMS WITH BASE SHEET MECHANICALLY ATTACHED

Warranty Duration	NDL Warranty Fee (100 Sq Min)	Insulation/Coverboard	Base	Interply	Cap	Applicable Specs	Recover
12 years	\$4.00/Sq	Optional ¹	Any approved CertainTeed BUR or SBS Base Sheet ⁵	Flintlastic Ultra Poly SMS	Flood coat and gravel	SBS(G)-IN-2-A, SBS(G)-N-2-A	Approved
12 years	\$4.00/Sq	Optional ¹		Optional		SBS-N-2-A, SBS-IN-2-A, SBS-N-2-C, SBS-IN-2-C, SBS-N-2-T, SBS-IN-2-T	Approved
15 years	\$7.50/Sq	Optional ¹		Optional	Any approved CertainTeed SBS Cap Sheet ⁵	SBS-IN-2-A, SBS-N-2-A	Approved
20 years	\$12.50/Sq	Optional	Glasbase Base Sheet, All Weather/Empire Base Sheet	Flintlastic Base 20 ² , Flintlastic Base 20 T, Black Diamond Base Sheet, Flintlastic Poly SMS		SBS-IN-3-A, SBS-IN-3-C, SBS-IN-3-T	Prior approval required by CertainTeed Commercial Roofing Technical Services Department
20 years	\$12.50/Sq	Single layer, minimum 1.5" and approved cover	CertaFast System with Flintlastic Ultra Poly SMS	—	Flintlastic GMS, Flintlastic FR-P, Flintlastic Premium FR-P, Flintlastic GTS-FR	SBS-IN-2-CF	
25 years	\$15.00/Sq	Single layer, minimum 1.5"	All Weather/Empire Base Sheet, Flintlastic Base 20, Flintlastic Poly SMS	Flintlastic Ultra Poly SMS, Flintlastic Ultra Glass SA	Flintlastic Premium FR-P, Flintlastic GTS-FR	SBS-IN-3-A, SBS-IN-3-C, SBS-IN-3-T	—

Notes: Unless noted, prior approval required by CT Tech Services for recover.

1. If "Optional" Insulation/Coverboard is utilized, refer to "SBS-IN-2-X"
2. If "Optional" Insulation/Coverboard is utilized, refer to "SBS-IN-2-A"
3. If "Optional" Insulation/Coverboard is utilized, refer to "SBS-IN-3-X"

* Please see the Specification Nomenclature chart on the preceding page to determine the X values.

4. CertainTeed's FlintBond[®] SBS Modified Adhesive must be utilized to obtain 20-year warranty duration.