

**CertainTeed**

# **CertaWrap™**

## **STANDARD**

### **Housewrap Specification Sheet**

CertaWrap STANDARD Specifications


Composition		Woven Polypropylene
Weight	(ASTM D-751)	1.9 oz. / 1 yd. <sup>2</sup> (± 5%)
Thickness		Avg 5.0 mils
Dry Tensile Strength	(ASTM D-5034)	53 lbs md, 44 lbs cd
Dry Tear Strength	(ASTM D-5587)	21 lbs md, 19 lbs cd
Water Resistance Test (Boat Test)	(ASTM D-779)	Pass
MTVR / Perms	(ASTM E-96A)	12-15 perms
Ultraviolet Light Exposure Resistance (UV)		3 months
Fire Rating	(ASTM-E-84)	Class A

Roll Size	Width	Length (Rolls / Pallet)
	9 ft	100 ft (78)

ICC #ESR-2514

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. Please refer to the actual warranty for further details.


**9' x 100' ROLL**



**Product Code: 69241**  
**Finish: No Finish**  
**Length: 100'**  
**Width: 9'**  
**Thickness: 5.0 mils**  
**Rolls/Pallet: 78**  
**Sq. Ft./Roll: 900**  
**lbs./Roll: ≤ 15**

<b>Product Code</b>	<b>69241</b> 9' x 100' Roll	<b>69921</b> 1-7/8" x 165' Roll	
No Color (00)	●		
Sandstone Beige (15)		●	

**CERTATAPE™**  
**CONSTRUCTION TAPE**  
**1-7/8" x 165' ROLL**



**Product Code: 69921**  
**Finish: No Finish**  
**Length: 165'**  
**Width: 1-7/8'**  
**Rolls/Case: 24**  
**lbs./Roll: 1 (approx.)**  
**Cases/Pallet: 48**  
**lbs./Case: ≤ 18**

For use to seal overlaps, seams, and penetrations



**CertainTeed Corporation**

20 Moores Road  
 Malvern, PA 19355  
[www.certainteed.com](http://www.certainteed.com)

**ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:**

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE  
 GYPSUM • CEILINGS • INSULATION

Professional: 800-233-8990 Consumer: 800-782-8777