

Chamfer Board

Vertical Siding & Porch Panel

General Description: Chamfer Board vertical siding and porch panel is appropriate for use in new construction for single family homes, multi-housing projects and light commercial developments. Chamfer Board is also an ideal product for remodeling. The panel is appropriate for both vertical sidewall and eaves installation.

Styles:

Profile	Finish	Net Free Air Space Per Sq. Ft.	Panel Projection	Wall Thickness (Nominal)	Lock Design	Colors	Accessory Pocket
Double 5" Solid	Brushed	—	9/16"	.044"	Unique V-Groove	8	1/2", 5/8" or 3/4"

Colors: Chamfer Board profiles are available in a wide selection of colors. All colors are Spectrophotometer controlled and utilize exclusive PermaColor™ color science.

Colonial White	Granite Gray	Light Maple	Savannah Wicker
Cypress	Heritage Cream	Natural Clay	Sterling Gray

Lock: Designed for ease of installation, Chamfer Board panels feature a unique V-Groove lock that gives it the look of beveled-edge wood.

Accessories: CertainTeed manufactures a wide range of siding and soffit accessories which are compatible with Chamfer Board styles and colors. Accessory products include installation components, soffit, window and door trim, corner lineals, corner systems and decorative moldings.

Composition: Chamfer Board vertical siding and porch panel is produced using CertaVin™ custom-formulated PVC resin. This resin is produced exclusively by CertainTeed, allowing CertainTeed to maintain the high quality of its siding products.

Technical Data: Chamfer Board vertical siding and porch panel is in compliance with ASTM specification for Rigid Polyvinyl Chloride (PVC) Siding D3679, D4477 Specification for Rigid Polyvinyl Chloride (PVC) Soffit, the requirements of section R703.11 of the International Residential Code, and section 1404.14 of the International Building Code. Chamfer Board vertical siding and porch panel meets or exceeds the properties noted in Table 1.

Table 1

ASTM E 84	Meets Class A flame spread requirements as tested according to ASTM E84.
ASTM D 635	Material is self-extinguishing with no measurable extent of burn when tested in accordance with this specification.
NFPA 268	Radiant Heat Test - Ignition Resistance of Exterior Walls - Conclusion that CertainTeed met the conditions for allowable use as specified in section 1406 of the International Building Code.

Important Fire Safety Information: When rigid vinyl siding is exposed to significant heat or flame, the vinyl will soften, sag, melt or burn, and may thereby expose material underneath. Care must be exercised when selecting underlayment materials because many underlayment materials are made from organic materials that are combustible. You should ascertain the fire properties of underlayment materials prior to installation. All materials should be installed in accordance with local, state and federal Building Code and fire regulations.

Wind Load Testing: CertainTeed D5" Chamfer Board vertical siding/porch panel has been tested per ASTM D 5206 standard test method for resistance to negative wind load pressures of 28.3 psf, which equates to 147 mph (V_{ASD}) and 190 mph (V_{ULT}), when installed with nails positioned 12" on center. Check with your local building inspector for wind load requirements in your area on the type of structure you are building.

Documents: This product meets the requirements of one or more of the following specifications.

Conforms to ASTM Specification D3679

Conforms to ASTM Specification D4477

Texas Department of Insurance Product Evaluation EC-11

Florida BCIS Approval FL1573

ICC-ES Evaluation Report ESR-1066

For specific product evaluation/approval information, call 800-233-8990.


Installation: Prior to commencing work, verify governing dimensions of building, examine, clean and repair, if necessary, any adjoining work on which the siding is in any way dependent for its proper installation. Sheathing materials must have an acceptable working surface. Siding, soffit and accessories shall be installed in accordance with the latest editions of CertainTeed installation manuals on siding and soffit. Installation manuals are available from CertainTeed and its distributors.

Warranty: CertainTeed supports Chamfer Board products with a Lifetime Limited Warranty including PermaColor Lifetime Fade Protection to the original homeowner. The warranty is transferable if the home is sold.

Technical Services: CertainTeed maintains an Architectural Services staff to assist building professionals with questions regarding CertainTeed siding products. Call 800-233-8990 for samples and answers to technical or installation questions.

Sample Short Form Specification: Product as shown on drawings or specified herein shall be Chamfer Board as manufactured by CertainTeed Corporation, Malvern, PA. The siding shall have a .044" nominal thickness. Installation shall be in accordance with manufacturer's instructions.

Three-part Format Specifications: Long form specifications in three-part format are available from CertainTeed by calling our Architectural Services Staff at 800-233-8990. These specifications are also available on our website at certainteed.com.



CertainTeed Corporation
20 Moores Road
Malvern, PA 19355
certainteed.com
© 01/19